

MasterRoc[®] SLF 47

Soil-conditioning foam for Tunnel Boring Machines

Description

MasterRoc SLF 47 is a highly eco-compatible polymer-reinforced foaming agent especially designed for soil conditioning in tunnel boring machines.

Applications

Soft ground tunneling with tunnel boring machines.

Features

- Based on renewable materials
- Improves soil plasticity
- Reduces permeability and increases sealing of the face
- Creates plastic deformation properties in the soil, which provide an even and controlled support pressure and increased face stability
- Lowers inner friction and abrasiveness of the soil at the cutterhead as well as at the screw conveyor

Benefits

- Reduces power consumption
- Enables quick soil extraction
- Reduces wear
- Compatible with highest environmental standards
- Promotes easier 'mucking'

Performance Characteristics

Technical Data

Typical Values

Form	Liquid
Color	Light brown
Density	64.6 to 65.2 lb/ft ³ at 68 °F (1035 to 1045 kg/m ³ at 20 °C)
pH	6 to 7 at 68 °F (20 °C)
Solubility in water	Total

Guidelines for Use

MasterRoc SLF 47 foam solution can be mixed with air to produce a stable foam. The foam recipe, foam expansion and the foam injection rate into the face, working chamber or screw conveyor depends on soil conditions encountered.

Dosage: Typically, MasterRoc SLF 47 soil conditioning foam is used as a 2 to 3% solution in water (general range 2 to 6%). MasterRoc SLP 1 or MasterRoc SLP 2 polymers (see separate data sheets) can be used simultaneously with MasterRoc SLF 47 soil conditioning foam in order to strengthen the foam or to adjust the properties of the excavated soil.

Foam Equipment: MasterRoc SLF 47 foam can be used with the standard TBM dosing and foaming equipment.

Storage and Handling

Handling: Do not mix pure MasterRoc SLF 47 foam with any other pure soil conditioning additives as this may cause immediate gel formation. If several foaming products or polymers are used on the TBM, it is preferable to reserve a specific transfer or dosing pump for MasterRoc SLF 47 foam. If a transfer or dosing pump is being used for more than one product, it is recommended to clean the pump with water before switching to other products.

Storage Temperature: MasterRoc SLF 47 foam should be stored in unopened, original containers, preferably between 40 °F and 95 °F (5 °C and 35 °C). If stored in original closed containers, MasterRoc SLF 47 foam will have a shelf life of 12 months. Do not allow the product to freeze. It is recommended that your local sales representative be consulted prior to the use of any product that has become frozen.

Safety: Standard precautions for handling chemical products should be observed. Avoid eye and skin contact and wear rubber gloves and goggles.

Packaging

MasterRoc SLF 47 foam is available in standard 54 gal (205 L) drums or 272 gal (1,029 L) totes. Bulk tanker supply is available on request.

Related Documents

Safety Data Sheets: MasterRoc SLF 47 foam

Additional Information

For additional information on MasterRoc SLF 47 foam, contact your local sales representative.

Master Builders Solutions, a brand of MBCC Group, is a global leader of innovative chemistry systems and formulations for construction, maintenance, repair and restoration of structures. The Admixture Systems business provides advanced products, solutions and expertise that improve durability, water resistance, energy efficiency, safety, sustainability and aesthetics of concrete structures, above and below ground, helping customers to achieve reduced operating costs, improved efficiency and enhanced finished products.

Utilizing worldwide resources, the Master Builders Solutions community of experts are passionate about providing solutions to challenges within all stages of construction, as well as the life cycle of a structure. At Master Builders Solutions we create sustainable solutions for construction around the globe.

Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC (“Master Builders Solutions”) warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.