

# MasterRoc® TSG 7

# Tail Sealant for Shielded Tunnel Boring Machines (TBM)

# **Description**

MasterRoc TSG 7 tailshield sealant is used for shielded tunnel boring machines (TBMs). MasterRoc TSG 7 sealant effectively seals the gap between the shield and concrete segments to prevent the ingress of soil, water or grout.

MasterRoc TSG 7 sealant is formulated as a "first fill" product to resist water and ground pressures and not break down under high mechanical pressures. After the initial "first fill" application, the use of MasterRoc TSG 6 sealant is recommended to ensure effective TBM tail shield protection. MasterRoc TSG 7 sealant has excellent pumping properties and adhesion on most surfaces.

### **Applications**

#### Recommended for use in:

Tunneling with shielded TBMs

#### **Features**

- Excellent pumping properties
- Excellent sealing properties
- Adheres to most metal or concrete surface
- Very high washout resistance
- Non-miscible with annulus grout

#### **Benefits**

■ Prevents the ingress of soil, water or grout into shielded TBMs

#### **Performance Characteristics**

**Consumption:** The average consumption for filling a 3 row brush system is 50 kg per meter (34 lb per ft) shield circumference.

#### **Technical Data**

Form	Homogeneous Paste
Color	Light Grey
Smell	Slight Odor
Density at 72.5 °F (22.5 °C)	111.7 lb/ft³ (1.79 g/cm³)
Consistency (ASTM D217), in. (1/10 mm)	0.79 (200)
Matsumara sealing test	493 psi (34 bar) – Passed
Water spray off test (ASTM D4049), % Mass loss	< 5%
Load Hysteresis Value (N @ 10mm penetration)	6.0
Sliding on metal surface (Dropping time), min	> 45
Soluble in water	No

#### **Guidelines for Use**

MasterRoc TSG 7 sealant is designed for use in a wide range of application temperatures.

# Storage and Handling

**Storage Temperature:** MasterRoc TSG 7 sealant should be stored in unopened, original containers, preferably at 41 to 95 °F (5 to 35 °C).

Shelf Life: MasterRoc TSG 7 sealant has a minimum shelf life of 12 months. Depending on storage conditions, the shelf life may be greater than stated. Please contact your local sales representative regarding suitability for use and dosage recommendations if the shelf life of MasterRoc TSG 7 sealant has been exceeded.

Safety: MasterRoc TSG 7 sealant is an inert material and is not hazardous. MasterRoc TSG 7 sealant is ecologically and environmentally preferable and poses no threat to worker safety. However, it is recommended that all normal precautions be taken when handling the product, such as use of eye protection and gloves. Refer to the Safety Data Sheet for MasterRoc TSG 7 sealant for more information.

MasterRoc TSG 7 sealant has passed a risk assessment indicating that the leachable components of the sealant are biodegradable.

# **Packaging**

MasterRoc TSG 7 sealant is packaged in 154 lb (70 kg) and 550 lb (250 kg) drums.

#### **Related Documents**

Safety Data Sheets: MasterRoc TSG 7 sealant

#### Additional Information

For additional information on MasterRoc TSG 7 sealant, contact your local sales representative.

Master Builders Solutions, a brand of MBCC Group, is a global leader of innovative chemistry systems and formulations for construction, maintenance, repair and restoration of structures. The Admixture Systems business provides advanced products, solutions and expertise that improve durability, water resistance, energy efficiency, safety, sustainability and aesthetics of concrete structures, above and below ground, helping customers to achieve reduced operating costs, improved efficiency and enhanced finished products.

Utilizing worldwide resources, the Master Builders Solutions community of experts are passionate about providing solutions to challenges within all stages of construction, as well as the life cycle of a structure. At Master Builders Solutions we create sustainable solutions for construction around the globe.

# **Limited Warranty Notice**

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED. INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product. including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

© MBCC Group ■ 04/21 ■ DAT-0033

® registered trademark of a MBCC Group member in many countries of the world

www.master-builders-solutions.com/en-us