

Tinted Primer

DESCRIPTION

100% acrylic-based primer

PRIMARY USES

- **Tinted Primer** helps alleviate shadowing and enhances performance of the Senergy Wall Systems. For optimum results, **Tinted Primer** should closely match the colour of the selected Senergy Finish.
- **Tinted Primer** is also used when preparing substrates such as poured concrete, unit masonry, conventional stucco (brown coat), veneer plaster or gypsum board (interior only) prior to application of Senergy Finish Coat.

ADVANTAGES

- Improves workability of finish coat application
- 100% acrylic-based primer
- Creates better final appearance, alleviates shadowing of light-coloured, rilled finishes
- Reduces chances of efflorescence in stucco and other cementitious substrates

PACKAGING AND COLORS

Tinted Primer is supplied in 24.9 kg per 19 L unit and available in 126 standard colours and a wide variety of custom colours.

APPLICATION GUIDELINES

MIXING

- Thoroughly mix the factory-prepared **Tinted Primer** with a paddle and drill to a uniform consistency.
- A small amount of clean, potable water may be added to adjust workability.
- Additives are not permitted.
- Close container when not in use.
- Clean tools with soap and water immediately

PLACING / APPLICATION

- Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or any irregularities greater than 6.4mm in 3m.
- Apply **Tinted Primer** to substrate with a sprayer, 10mm nap roller or good quality latex paint brush at a rate of approximately 3.6–6.1m² per litre.
- **Tinted Primer** shall be dry to the touch before proceeding to the Senergy Finish Coat application.

COVERAGE / YIELD

Approximate coverage rate is 69.6–116.1m² per unit. Coverage will vary greatly depending on porosity and condition of surface.

Tinted Primer

WATCHPOINTS

- Protect products during transportation and installation to avoid physical damage.
- Do not apply Senergy materials in ambient temperatures below 4°C. Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C prevail.
- Do not apply to frozen surfaces.

STORAGE AND SHELF LIFE

Store in a cool, dry place protected from freezing. Store at no less than 4°C. Protect from extreme heat and direct sunlight. Shelf life is 6 months when unopened and stored as directed.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes mouth, skin and foodstuffs. If accidentally ingested, seek immediate medical attention. Reseal containers after use. For further information, refer to material safety data sheet.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/Tint_Prm_10_07/v1/12_13/v2/07_20

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

**Master Builders Solutions
Construction Chemicals LLC**
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800
www.master-builders-solutions.com/en-ae

Disclaimer: the TÜV mark relates to certified management system and not to the product mentioned on this datasheet



A brand of
**MASTER®
BUILDERS
SOLUTIONS**