

High range water reducing admixture for concrete EN 934-2: T3.1 & T3.2

DESCRIPTION

MasterGlenium SKY 4414 is an innovative second-generation superplasticizer based on polycarboxylic ether (PCE) polymers. It is derived directly from the Total Performance Control™ concept. MasterGlenium SKY 4414 is specially engineered for ready-mix concrete. Its particular configuration allows its delayed adsorption onto the cement particles and disperses them efficiently. As compared with other PCE superplasticizers, it is possible to obtain a high quality concrete mix with accelerated strength development and extended workability without delayed setting characteristics.

The molecular structure of MasterGlenium SKY 4414 is effective in early strength development. Conventional super plasticizers completely wrap cement particles and prevent them from joining with water by forming a barrier. By this way, the hydration process becomes slower. Differently from this mechanism, MasterGlenium SKY 4414 molecules leave gaps on cement particles that allow sudden hydration. These gaps enable early high strength development.

The Total Performance Control™ concept ensures that ready-mix producers, contractors and engineers get a concrete that is of the same high quality as originally specified; starting from production at the batching plant, to the delivery and application into place, and followed by its hardening process. Utilizing Rheodynamic™ concrete technology it provides a concrete mix with exceptional placing characteristics and accelerated cement hydration for early strength development and high-quality concrete.

FIELDS OF APPLICATION

MasterGlenium SKY 4414 is used for the production of high quality ready-mix concrete. MasterGlenium SKY 4414 may be used in combination with MasterMatrix viscosity modifying admixtures for producing Rheodynamic™ concrete, capable of self-compaction, even in the presence of dense reinforcement.

FEATURES and BENEFITS

MasterGlenium SKY 4414 offers the following benefits for:

The ready-mix producer:

- Capability of delivering high quality concrete at any time to the job site in place.
- Production of a concrete with low water cement ratio that meets EN 206-1 without loss of workability.
- Single product for many application needs.

The contractor / applicator:

- Easier placing and faster strength development.
- Improved concrete surfaces.
- Guarantee to place the same concrete as specified and ordered from ready-mix plant.
- More versatile and forgiving concrete mix.

The engineer:

- Insurance that concrete meets original specification
- High quality concrete with better durability.

DOSAGE

The normally recommended dosage rate of MasterGlenium SKY 4414 is approximately:

• By Weight - 0.8 to 1.5 kg per 100 kg of cement (binder) content.

The dosage rates given above are for typical usages, they are not meant as absolute limits, as other dosages may be utilized in special cases according to specific job conditions. If required consult Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd.Şti.Technical Services Department for advice. Trial mixes should be carried out to ensure optimum dosage and effect. Where the concrete is to be machine finished by utilizing power float or power troweling methods, we recommend that you contact with Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd.Şti Technical Services Department for dosage rate guidance.

MIXING

MasterGlenium SKY 4414 is a ready-to-use admixture to be added to the concrete as a separate component. Optimal performance is obtained if MasterGlenium SKY 4414 is dispensed into the concrete mix right after the addition of the first 80% of the mixing water, i.e. when all solids are wetted out. Avoid adding the admixture to the dry aggregates.



High range water reducing admixture for concrete EN 934-2: T3.1 & T3.2

COMPATIBILITY

MasterGlenium SKY 4414 can be used with all types of **EN 197** Cements. For use with other special cements, contact our Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd.Şti Technical Services Department.

MasterGlenium SKY 4414 should not be pre-mixed with other admixtures. If other admixtures are to be used in concrete containing MasterGlenium SKY 4414 they must be dispensed separately.

MasterGlenium SKY 4414 is not compatible with MasterRheobuild superplasticizers. In order to optimize special requirements the use of the following complementary additives is suggested:

- Viscosity modifying agent MasterMatrix to produce Rheodynamic™ concrete.
- Air entraining agent MasterAir to improve frost/thaw resistance.

When such complimentary admixtures are required it is important that laboratory trials are performed, prior to any supply, to determine the respective dosages of any complimentary admixture, and the suitability, in the fresh and hardened state, of the resultant concrete. In these circumstances we recommend that you consult our Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd.Şti Technical Services Department for further advice.

PACKAGING

MasterGlenium SKY 4414 is supplied in bulk and 1000-kg IBC's.

October 2020 Page 2 of 4



High range water reducing admixture for concrete EN 934-2: T3.1 & T3.2

Product Data	
Structure of the Material	Modified Polycarboxylic Ether Based
Appearance	brown
Specific gravity @ 20°C	1.083 – 1.1 kg/lt
pH-value	5 - 7
Alkali content (%):	≤ 3.00 (by mass)
Chloride content (%)	≤ 0.10 (by mass)
Corrosion behaviour	Contains only components according to BS EN 934-1:2008, Annex A.1
Dangerous substances	Comply with annex AZ.
Logistics	
Shelf life	12 months if stored according to manufacturer's instructions in unopened container.
Storage conditions	Store in original sealed containers and at temperatures between 5°C and 30°C. Store under cover, out of direct sunlight and protect from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.
Handling and transportation	Refer to MasterGlenium SKY 4414 Safety Data Sheet.
Disposal	Refer to MasterGlenium SKY 4414 Safety Data Sheet.

October 2020 Page 3 of 4



High range water reducing admixture for concrete EN 934-2: T3.1 & T3.2

HEALTH AND SAFETY

*For full information on Health and Safety matters regarding this product the relevant Health and Safety Data Sheet should be consulted.

The following general comments apply to all products.

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs, (which may also be tainted with vapor until the product is fully cured and dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Keep away from children and animals. Reseal containers after use.

SPILLAGE

Chemical products can cause damage; clean spillage immediately.

DISCLAIMER

"Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd.Şti." (the Company) endeavors to ensure that advice and information given in Product Data Sheets. Method Statements and Material Safety Data Sheets (all known as Product Literature) is accurate and correct. However, the Company has no control over the selection of its products for particular applications. It is important that any prospective customer, user or specifier, satisfies him/her-self that the product is suitable for the specific application. In this process, due regard should be taken of the nature and composition of the background/base and the ambient conditions both at the time of laying/applying/installing the material and when the completed work is to be brought into use. Accordingly, no liability will be accepted by the Company for the selection, by others, of a product, which is inappropriate to a particular application. Products are sold subject to the Company's standard conditions of sale and all customers, users and specifiers, should ensure that they examine the Company's latest product literature.

CONTACT INFORMATION

Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti.

Head Office Adress : Barbaros Mah. Begonya Sok. Nidakule Ataşehir Kuzey C Kapısı No:3E/5 ,34746

Ataşehir, İstanbul, Türkiye Tel: 0216 217 88 00

Mail: mbs.tr@mbcc-group.com

www.master-builders-solutions.com/tr-tr

MasterGlenium SKY 4414 Technical Data Sheet -

Revision Date: 10/2020

October 2020 Page 4 of 4