

## **DECLARATION OF PERFORMANCE**

according Annex III of the regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No. 574/2014

For the product "MasterTop P 622"

No. <b>162229</b>				
1.	Unique identification code of the product-type: EN 13813: 2002: SR-B1.5-AR1-IR4			
2. A	Intended use/es: <b>Synthetic resin screed for internal uses</b> two component, non-solvented (total solid) primer based on epoxy resin for use on high residual moisture content cementitious screeds			
3.	Manufacturer: Master Builders Solutions Deutschland GmbH Donnerschweer Str. 372 D-26123 Oldenburg			
4.	System/s of assessment and verification of constancy of performance (AVCP): System 4 for internal uses			
5.	Harmonised standard: EN 13813: 2002: SR-B1.5-AR1-IR4			
6.	Notified body/ies: Not relevant			



7. Declared performances determined in System build-up MasterTop 1289 AS:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonisierte technische Spezifikation
Reaction to fire	Efl	System 4	EN 13813:2002
Release of corrosive substances	SR		
Water permeability	NPD		
Wear resistance	≤ AR1		
Bond strength	≥ B1,5		
Impact resistance	≥ IR4		
Sound insulation	NPD		
Sound absorption	NPD		
Thermal resistance	NPD		
Chemical resistance	NPD		

NPD: No Performance Determined

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Performance without any further testing: reaction to fire: Efl

Fulfilled requirements: Efl

Thickness max. of the flooring system: 3 mm

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Atte

Henrik Willem Vetter European Marketing Manager Performance Flooring

Oldenburg, 04.01.2021

## Annex:

Technical data sheets for use in buildings (system build-ups according to respective technical data sheets)