

MasterProtect HB 400 FN Ser P

Version **Revision Date:** SDS Number: Date of last issue: -

07/16/2020 000000260733 Date of first issue: 07/16/2020 1.0

SECTION 1. IDENTIFICATION

Product name MasterProtect HB 400 FN Ser P

Product code 00000000051716222 00000000051716222

Other means of identification No data available

Manufacturer or supplier's details

Company name of supplier MBSCS Canada, Inc.

Address 7111 Syntex Drive, 3rd Floor

Mississauga ON L5N 8C3

Emergency telephone ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use Product for construction chemicals

Restrictions on use Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

2 (Kidney, Immune system)

Carcinogenicity (Inhalation)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Short-term (acute) aquatic

hazard

Long-term (chronic) aquatic

hazard

3

GHS label elements

Hazard pictograms

Signal Word Danger

Hazard Statements H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

exposure if inhaled.

H373 May cause damage to organs through prolonged or re-

peated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 Obtain special instructions before use.

P260 Do not breathe dust or mist.

P202 Do not handle until all safety precautions have been read

and understood.

P273 Avoid release to the environment.

P270 Do not eat, drink or smoke when using this product. P264 Wash face, hands and any exposed skin thoroughly after

handling.

Response:

P314 Get medical advice/ attention if you feel unwell. P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 25
Quartz (SiO2)	14808-60-7	>= 15 - < 20
Titanium dioxide	13463-67-7	>= 7 - < 10
ethyleneglycol	107-21-1	>= 1 - < 3
Poly(oxy-1,2-ethanediyl), .alpha [(1,1,3,3-tetramethylbutyl)phenyl]- .omegahydroxy-	9036-19-5	>= 0 - < 0.2
diuron	330-54-1	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate	55406-53-6	>= 0 - < 0.1

SECTION 4. FIRST AID MEASURES



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

If swallowed accidentally, do not induce vomiting, get medical

help immediately.

Most important symptoms and effects, both acute and

delayed

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Product is not explosive.

Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

: Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Further information on stor-

age stability

No decomposition if stored and applied as directed.



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
ethyleneglycol	107-21-1	TWA value	25 ppm	ACGIHTLV
		(Vapor frac-		
		tion)		
		STEL value	50 ppm	ACGIHTLV
		(Vapor frac-		
		tion)		
		STEL value	10 mg/m3	ACGIHTLV
		(Aerosol,		
		inhalable.)	400 / 0	04.45.051
		(c)	100 mg/m3	CA AB OEL
		TWA (partic- ulate)	10 mg/m3	CA BC OEL
		STEL (par- ticulate)	20 mg/m3	CA BC OEL
		C (aerosol)	100 mg/m3	CA BC OEL
		C (Vapor)	50 ppm	CA BC OEL
		C (Vapour	50 ppm	CA QC OEL
		and mist)	127 mg/m3	
		TWA (Vapor)	25 ppm	ACGIH
		STEL	50 ppm	ACGIH
		(Vapor)		
		STEL (Inhal-	10 mg/m3	ACGIH
		able fraction,		
		Aerosol only)		
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR
				1910.1000
			10 / 0	(Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWA	10 mg/m3	CA BC OEL
		TWAEV	10 mg/m3	CA QC OEL
		TWA	10 mg/m3	ACGIH
Limestone	1317-65-3	REL value	5 mg/m3	NIOSH
		(Respirable)	40 / 0	NUCCUI
		REL value	10 mg/m3	NIOSH
		(Total)	5 / 0	00.055
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)		1910.1000
		DEL /Total	15 mg/m2	(Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000
		uusi)		(Table Z-1)
		TWA value	5 mg/m3	29 CFR
		(Respirable	3 mg/m3	1910.1000
		fraction)		(Table Z-1-A)
		Haction)		(I able 2-1-A)



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000
				(Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWAEV (to- tal dust)	10 mg/m3	CA QC OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		STEL	20 mg/m3	CA BC OEL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (to- tal dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable par-	0.025 mg/m3 (Silica)	ACGIH

MBCC GROUP

MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

ticulate matter)

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) respirator as neces-

sary.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : pigmented

Odor : sweetish, slight odour

pH : 9.5 - 10

Melting point : No applicable information available.

Freezing point No applicable information available.

Boiling point : 192.78 - 205.00 °C

Flash point : 93.34 °C



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

15.3 %(V)

Lower explosion limit / Lower

flammability limit

3.2 %(V)

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 1.57 - 1.70 g/cm3 (20 °C)

Solubility(ies)

Water solubility : partly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.

May cause damage to organs through prolonged or repeated exposure.



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statement has been

derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

Components:

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Biodegradability : aerobic

Inoculum: activated sludge, domestic, non-adapted

Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: Modified OECD-Screening-Test.

Bioaccumulative potential

Components:

Quartz (SiO2):

Partition coefficient: n-

octanol/water

Remarks: not applicable

Titanium dioxide:

Partition coefficient: n-

octanol/water

Remarks: not applicable

ethyleneglycol:

Partition coefficient: n-

octanol/water

log Pow: approx. -1.36 (23 °C) Method: Calculation Hansch/Leo

GLP: no data

Remarks: Information taken from reference works and the

literature.



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Bioaccumulation : Remarks: Accumulation in organisms is not to be expected.

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate:

Partition coefficient: n- : log Pow: 2.81 (25 °C)

octanol/water Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Ecological data are not available.

Do not allow to enter soil, waterways or waste water channels.

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

Time Weighted Average (TWA):

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)

29 CFR 1910.1000 (Table Z-

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / (c) : ceiling occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit

CA BC OEL / C : ceiling limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / C : Ceiling

NIOSH / REL value : Recommended exposure limit (REL):



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 07/16/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE



MasterProtect HB 400 FN Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/16/2020 000000260733 Date of first issue: 07/16/2020

CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN