

**MasterProtect HB 400 FN UDP TB**

Version            Revision Date:            SDS Number:            Date of last issue: 09/24/2020  
1.1                08/08/2022              000000261315           Date of first issue: 09/24/2020

---

**SECTION 1. IDENTIFICATION**

Product name                                : MasterProtect HB 400 FN UDP TB  
Product code                                : 000000000051716328 000000000051716328  
Other means of identification            : No data available

**Manufacturer or supplier's details**

Company name of supplier                : MBSCS Canada, Inc.  
Address                                        : 7111 Syntex Drive, 3rd Floor  
    Mississauga ON L5N 8C3  
Emergency telephone                        : ChemTel: +1-813-248-0585;  
National Emergency Tele-                 : USA: +1-800-255-3924 ChemTel contract no. MIS9240420  
phone Number

**Recommended use of the chemical and restrictions on use**

Recommended use                            : Waterproof coating  
Restrictions on use                           : Reserved for industrial and professional use.

---


**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Carcinogenicity (Inhalation)            : Category 1A  
Specific target organ toxicity            : Category 1 (Lungs)  
- repeated exposure (Inhalation)  
Specific target organ toxicity            : Category 2 (Kidney)  
- repeated exposure  
Specific target organ toxicity            : Category 2 (Kidney, Immune system)  
- repeated exposure (Inhalation)  
Short-term (acute) aquatic                : Category 3  
hazard  
Long-term (chronic) aquatic              : Category 3  
hazard

**GHS label elements**

## MasterProtect HB 400 FN UDP TB

Version 1.1      Revision Date: 08/08/2022      SDS Number: 000000261315      Date of last issue: 09/24/2020  
 Date of first issue: 09/24/2020

- Hazard pictograms : 
- Signal Word : Danger
- Hazard Statements : H350 May cause cancer by inhalation.  
 H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.  
 H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.  
 H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.  
 H402 Harmful to aquatic life.  
 H412 Harmful to aquatic life with long lasting effects.
- Precautionary Statements : **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe mist or vapors.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- Response:**  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
- Storage:**  
 P405 Store locked up.
- Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Aqueous solution

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Limestone	Calcium carbonate	1317-65-3	>= 10 - < 30
crystalline silica	Quartz (SiO <sub>2</sub> )	14808-60-7	>= 10 - < 20
Titanium dioxide	C.I. Pigment	13463-67-7	>= 1 - < 5

## MasterProtect HB 400 FN UDP TB

Version 1.1      Revision Date: 08/08/2022      SDS Number: 000000261315      Date of last issue: 09/24/2020  
 Date of first issue: 09/24/2020

	White 6		
Wollastonite (Ca(SiO <sub>3</sub> ))	Calcium silicate	13983-17-0	>= 1 - < 5
ethylene glycol	1,2-Ethandiol	107-21-1	>= 1 - < 5
diuron	Urea, N'-(3,4-dichlorophenyl)-N,N-dimethyl-	330-54-1	< 0.1
carbendazim	Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	< 0.1
3-iodo-2-propynyl butylcarbamate	Carbamic acid, butyl-, 3-iodo-2-propynyl ester	55406-53-6	< 0.1

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Remove contact lenses, if present.  
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.  
May cause damage to organs through prolonged or repeated exposure.  
Prolonged or repeated inhalation of respirable crystalline silica (quartz) may result in silicosis.
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

## MasterProtect HB 400 FN UDP TB

Version 1.1      Revision Date: 08/08/2022      SDS Number: 000000261315      Date of last issue: 09/24/2020  
Date of first issue: 09/24/2020

---

- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid aerosol formation.  
Avoid inhalation of mists/vapours.  
Avoid skin contact.  
Avoid contact with eyes.
- Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.

## MasterProtect HB 400 FN UDP TB

Version 1.1      Revision Date: 08/08/2022      SDS Number: 000000261315      Date of last issue: 09/24/2020  
 Date of first issue: 09/24/2020

Protect from direct sunlight.

Further information on storage stability : PROTECT FROM FREEZING DURING THE COLD-SEASON (BELOW 40°F / 5°C ).

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
Limestone	1317-65-3	TWA	10 mg/m <sup>3</sup>	CA AB OEL		
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL		
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL		
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL		
		STEL	20 mg/m <sup>3</sup>	CA BC OEL		
crystalline silica	14808-60-7	TWA (Respirable particulates)	0.025 mg/m <sup>3</sup>	CA AB OEL		
		TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	CA ON OEL		
		TWAEV (respirable dust)	0.1 mg/m <sup>3</sup>	CA QC OEL		
		TWA (Respirable)	0.025 mg/m <sup>3</sup> (Silica)	CA BC OEL		
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH		
		Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
				TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
TWA (respirable dust fraction)	3 mg/m <sup>3</sup>			CA BC OEL		
TWAEV (total dust)	10 mg/m <sup>3</sup>			CA QC OEL		
TWA	10 mg/m <sup>3</sup> (Titanium dioxide)			ACGIH		
Wollastonite (Ca(SiO <sub>3</sub> ))	13983-17-0	TWAEV (respirable dust)	5 mg/m <sup>3</sup>	CA QC OEL		
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL		
		TWA (Inhalable)	1 mg/m <sup>3</sup>	CA BC OEL		

## MasterProtect HB 400 FN UDP TB

Version 1.1      Revision Date: 08/08/2022      SDS Number: 000000261315      Date of last issue: 09/24/2020  
 Date of first issue: 09/24/2020

		TWA (Inhalable particulate matter)	1 mg/m <sup>3</sup>	ACGIH
ethylene glycol	107-21-1	(c)	100 mg/m <sup>3</sup>	CA AB OEL
		TWA (particulate)	10 mg/m <sup>3</sup>	CA BC OEL
		STEL (particulate)	20 mg/m <sup>3</sup>	CA BC OEL
		C (aerosol)	100 mg/m <sup>3</sup>	CA BC OEL
		C (Vapor)	50 ppm	CA BC OEL
		C (Vapour and mist)	50 ppm 127 mg/m <sup>3</sup>	CA QC OEL
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m <sup>3</sup>	ACGIH
diuron	330-54-1	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA	10 mg/m <sup>3</sup>	CA BC OEL
		TWAEV	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	10 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Ensure adequate ventilation.

#### Personal protective equipment

**Respiratory protection** : Wear appropriate certified respirator when exposure limits may be exceeded.  
 Use NIOSH approved respiratory protection.

**Hand protection**

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Wear safety glasses with side shields or goggles.

**Skin and body protection** : Impermeable protective clothing  
 Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

**Protective measures** : Do not inhale gases/vapours/aerosols.  
 Avoid contact with the skin, eyes and clothing.  
 Avoid exposure - obtain special instructions before use.  
 Handle in accordance with good building materials hygiene and safety practice.  
 Wearing of closed work clothing is recommended.

**Hygiene measures** : When using, do not eat, drink or smoke.  
 Hands and/or face should be washed before breaks and at the end of the shift.  
 At the end of the shift the skin should be cleaned and skin-

## MasterProtect HB 400 FN UDP TB

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.1	08/08/2022	000000261315	Date of first issue: 09/24/2020

---

care agents applied.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	pigmented
Odor	:	sweetish, slight odour
Odor Threshold	:	No data available
pH	:	9.5 - 10
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	193 - 205 °C
Flash point	:	93.34 °C
Evaporation rate	:	No data available
Flammability (liquids)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	15.3 %(V)
Lower explosion limit / Lower flammability limit	:	3.2 %(V)
Vapor pressure	:	No data available
Relative vapor density	:	Heavier than air.
Relative density	:	1.57 - 1.70
Density	:	1.57 - 1.70 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	
Water solubility	:	partly soluble
Solubility in other solvents	:	No data available

## MasterProtect HB 400 FN UDP TB

Version 1.1      Revision Date: 08/08/2022      SDS Number: 000000261315      Date of last issue: 09/24/2020  
Date of first issue: 09/24/2020

---

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong oxidizing agents  
Strong bases  
Strong acids

Hazardous decomposition products : irritant gases/vapours  
carbon oxides

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.



## MasterProtect HB 400 FN UDP TB

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.1	08/08/2022	000000261315	Date of first issue: 09/24/2020

---

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

<b>IARC</b>	Group 1: Carcinogenic to humans crystalline silica (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans Titanium dioxide	13463-67-7

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

May cause damage to organs (Kidney) through prolonged or repeated exposure.

May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

## MasterProtect HB 400 FN UDP TB

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.1	08/08/2022	000000261315	Date of first issue: 09/24/2020

---

**Components:****diuron:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

**carbendazim:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

**3-iodo-2-propynyl butylcarbamate:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

## MasterProtect HB 400 FN UDP TB

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.1	08/08/2022	000000261315	Date of first issue: 09/24/2020

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains one or more components not listed on the Canadian DSL or NDSL. All other components are on the Canadian DSL.

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / (c)	:	ceiling occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value

## MasterProtect HB 400 FN UDP TB

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.1	08/08/2022	000000261315	Date of first issue: 09/24/2020

---

CA QC OEL / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 08/08/2022  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN