

## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

#### **SECTION 1. IDENTIFICATION**

Product name : MasterSeal 630

Product code : 00000000050274383 00000000050274383

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : MBSCS Canada, Inc.

Address : 7111 Syntex Drive, 3rd Floor

Mississauga ON L5N 8C3

Emergency telephone : ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

FLAMMABLE LIQUIDS : 2

Skin corrosion/irritation : 2

Skin sensitization : Category 1

Carcinogenicity : 2

Specific target organ toxicity

- single exposure

: 3

Short-term (acute) aquatic

hazard

3

**GHS** label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

# **MBCC** GROUP

## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

H351 Suspected of causing cancer.

H402 Harmful to aquatic life.

Precautionary Statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P201 Obtain special instructions before use.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P243 Take action to prevent static discharges.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P242 Use only non-sparking tools.

P240 Ground and bond container and receiving equipment. P264 Wash face, hands and any exposed skin thoroughly after handling.

### Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P233 Keep container tightly closed.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

#### Other hazards

No data available.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No data available.



## MasterSeal 630

Version **Revision Date:** SDS Number: Date of last issue: -

08/27/2020 000000525767 Date of first issue: 08/27/2020 1.0

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
methyl methacrylate	80-62-6	>= 50 - <= 100
1,4-butanediol dimethacrylate	2082-81-7	>= 1 - < 5
N,N-dimethyl-p-toluidine	99-97-8	>= 0.1 - < 1
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3	>= 0.1 - < 1

#### **SECTION 4. FIRST AID MEASURES**

General advice Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact If skin irritation persists, call a physician.

> If on skin, rinse well with water. If on clothes, remove clothes.

Flush eyes with water as a precaution. In case of eye contact

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction. May cause respiratory irritation. Suspected of causing cancer.

Notes to physician Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

> Foam Drv powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.



## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec-:

tive equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapors accumulating to form explosive concentra-

tions. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-

miculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

egulations.

Persons susceptible to skin sensitization problems or asthma,



## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : no smoking

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep container tightly closed and in a well-ventilated place.

Keep away from heat.

Avoid all sources of ignition: heat, sparks, open flame.

Materials to avoid : Segregate from foods and animal feeds.

Further information on stor-

age stability

No data available

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA value	50 ppm	ACGIHTLV
		STEL value	100 ppm	ACGIHTLV
		REL value	100 ppm 410 mg/m3	NIOSH
		PEL	100 ppm	29 CFR
			410 mg/m3	1910.1000 (Table Z-1)
		TWA value	100 ppm	29 CFR
			410 mg/m3	1910.1000
				(Table Z-1-A)
		STEL	100 ppm 410 mg/m3	CA AB OEL
		TWA	50 ppm 205 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm	CA QC OEL
			205 mg/m3	
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH

**Engineering measures** : No applicable information available.

# **MBCC** GROUP

## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Avoid inhalation of dusts/mists/vapours.

Avoid contact with the skin, eyes and clothing.

Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : bluish

Odor : sweetish, ester-like

Odor Threshold : No data available

pH : not applicable

Melting point : No applicable information available.

Freezing point No applicable information available.

boiling temperature : approx. 100 °C

(1,013 hPa)

Flash point : 10 °C

Method: Flashpoint test using closed cup, determination of

flashpoint.

Evaporation rate : > 1

# **MBCC** GROUP

## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

Flammability (solid, gas) : Highly flammable.

Upper explosion limit / Upper

flammability limit

12.5 %(V) Medium: air

Lower explosion limit / Lower

flammability limit

2.1 %(V)

Medium: air

Vapor pressure : No data available

Relative vapor density : not determined

Relative density : No applicable information available.

Density : approx. 0.97 g/cm3 (20 °C)

Solubility(ies)

Water solubility

Solubility in other solvents : No applicable information available.

Autoignition temperature : 430 °C

Decomposition temperature : Vapors may form explosive mixture with air.

No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : approx. 5 - 7 mPa.s ( 20 °C)

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : not fire-propagating

Sublimation point : No applicable information available.

Molecular weight : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No hazardous reactions if stored and handled as pre-

scribed/indicated.

Polymerization coupled with heat formation.

Risk of dangerous polymerization in the presence of heat

and/or contamination.

# **MBCC** GROUP

## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Reducing agents

Heavy metal compounds

alkalies Amines

Sulfur compounds

Peroxides

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

### Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

**Product:** 

Remarks : Causes sensitization.



## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

#### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration hazard expected.

#### **Further information**

**Product:** 

Remarks : The product has not been tested. The statement has been

derived from the properties of the individual components.

Remarks : Solvents may degrease the skin.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

### Persistence and degradability

No data available

### **Bioaccumulative potential**

#### **Components:**

### methyl methacrylate:

Partition coefficient: n- : log Pow: 1.38 (20 °C)

octanol/water GLP: no data

### 1,1'-(p-tolylimino)dipropan-2-ol:

Partition coefficient: n- : log Pow: 2.1 (24 °C)

octanol/water pH: 7.5

Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes



## MasterSeal 630

Version **Revision Date:** SDS Number: Date of last issue: -

08/27/2020 000000525767 Date of first issue: 08/27/2020 1.0

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging should be emptied as far as possible Contaminated packaging

and disposed of in the same manner as the sub-

stance/product.

**SECTION 14. TRANSPORT INFORMATION** 

International Regulations

**UNRTDG** 

UN number UN 1866

**RESIN SOLUTION** Proper shipping name

Class 3 Packing group Ш Labels 3

**IATA-DGR** 

UN/ID No. UN 1866

**RESIN SOLUTION** Proper shipping name

Class 3 Packing group Ш

Labels Flammable Liquids

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

353

364

**IMDG-Code** 

**UN** number UN 1866

**RESIN SOLUTION** Proper shipping name

Class 3 Ш Packing group Labels 3 **EmS Code** F-E, S-E



## MasterSeal 630

Version **Revision Date:** SDS Number: Date of last issue: -

08/27/2020 000000525767 Date of first issue: 08/27/2020 1.0

Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

**TDG** 

UN number UN 1866

Proper shipping name **RESIN SOLUTION** 

Class 3 Packing group Ш Labels 3 **ERG Code** 127 Marine pollutant no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

### The ingredients of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

#### **SECTION 16. OTHER INFORMATION**

### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000 1)

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

American Conference of Governmental Industrial Hygienists -**ACGIHTLV** 

threshold limit values (US)

CA AB OEL Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL Canada. British Columbia OEL

Québec. Regulation respecting occupational health and safe-CA QC OEL

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

NIOSH NIOSH Pocket Guide to Chemical Hazards (US) Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z- :

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA 8-hour, time-weighted average Short-term exposure limit ACGIH / STEL

Short Term Exposure Limit (STEL): ACGIHTLV / STEL value ACGIHTLV / TWA value Time Weighted Average (TWA):

### MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

CA AB OEL / TWA : 8-hour Occupational exposure limit CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA QC OEL / TWAEV : Time-weighted average exposure value NIOSH / REL value : Recommended exposure limit (REL):

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 08/27/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO



## MasterSeal 630

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/27/2020 000000525767 Date of first issue: 08/27/2020

DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN