

**MasterSeal 658 fre gry**

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
Date of first issue: 08/12/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterSeal 658 fre gry  
Product code : 000000000056585385 000000000056585385  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : MBSCS Canada, Inc.  
Address : 7111 Syntex Drive, 3rd Floor  
Mississauga ON L5N 8C3  
Emergency telephone : ChemTel: +1-813-248-0585;

**Recommended use of the chemical and restrictions on use**



Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Skin corrosion/irritation : 2  
Serious eye damage/eye irritation : Category 2A  
Skin sensitization : Category 1  
Carcinogenicity : 2  
Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lung)  
Short-term (acute) aquatic hazard : 3  
Long-term (chronic) aquatic hazard : 3

**GHS label elements**

Hazard pictograms :  

Signal Word : Danger

## MasterSeal 658 fre gry

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
Date of first issue: 08/12/2020

---

Hazard Statements : H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Lung) through prolonged or repeated exposure.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P260 Do not breathe dust or mist.  
P273 Avoid release to the environment.  
P202 Do not handle until all safety precautions have been read and understood.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.

**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.  
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.  
P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

**Storage:**  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**  
No data available.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Components**

## MasterSeal 658 fre gry

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
Date of first issue: 08/12/2020

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO <sub>2</sub> )	14808-60-7	>= 25 - < 50
Limestone	1317-65-3	>= 3 - < 5
Titanium dioxide	13463-67-7	>= 1 - < 3
ammonia	7664-41-7	>= 0.3 - < 1
2-dimethylaminoethanol	108-01-0	>= 0.3 - < 1
chlorothalonil	1897-45-6	>= 0.2 - < 0.3
ammonia, aqueous solution	1336-21-6	>= 0.2 - < 0.3
bronopol	52-51-7	>= 0.2 - < 0.3

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of causing cancer.  
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

**MasterSeal 658 fre gry**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/12/2020	000000260208	Date of first issue: 08/12/2020

---

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Product is not explosive.  
  
Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and

## MasterSeal 658 fre gry

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
 Date of first issue: 08/12/2020

kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Recommended storage temperature : 5 °C

Further information on storage stability : Minimum storage temperature:

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
ammonia, aqueous solution	1336-21-6	STEL value	35 ppm	ACGIHTLV
		TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 18 mg/m <sup>3</sup>	NIOSH

## MasterSeal 658 fre gry

Version  
1.0Revision Date:  
08/12/2020SDS Number:  
000000260208Date of last issue: -  
Date of first issue: 08/12/2020

		STEL value	35 ppm 27 mg/m3	NIOSH
		PEL	50 ppm 35 mg/m3	29 CFR 1910.1000 (Table Z-1)
		STEL value	35 ppm 27 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm (Ammonia)	ACGIH
		STEL	35 ppm (Ammonia)	ACGIH
		TWA	25 ppm 18 mg/m3 (Ammonia)	NIOSH REL
		ST	35 ppm 27 mg/m3 (Ammonia)	NIOSH REL
ammonia	7664-41-7	STEL value	35 ppm	ACGIHTLV
		TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 18 mg/m3	NIOSH
		STEL value	35 ppm 27 mg/m3	NIOSH
		PEL	50 ppm 35 mg/m3	29 CFR 1910.1000 (Table Z-1)
		STEL value	35 ppm 27 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm 17 mg/m3	CA AB OEL
		STEL	35 ppm 24 mg/m3	CA AB OEL
		TWA	25 ppm	CA BC OEL
		STEL	35 ppm	CA BC OEL
		TWAEV	25 ppm 17 mg/m3	CA QC OEL
		STEV	35 ppm 24 mg/m3	CA QC OEL
		TWA	25 ppm (Ammonia)	ACGIH
		STEL	35 ppm (Ammonia)	ACGIH
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWA (Total	10 mg/m3	CA BC OEL

## MasterSeal 658 fre gry

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
 Date of first issue: 08/12/2020

		dust)		
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH

**Engineering measures** : No applicable information available.

**Personal protective equipment**

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing

## MasterSeal 658 fre gry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/12/2020	000000260208	Date of first issue: 08/12/2020

---

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : pigmented

Odor : product specific

Odor Threshold : No data available

pH : 9

Melting point : No applicable information available.

Freezing point : No applicable information available.

Boiling point : No applicable information available.

Flash point : not applicable

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : No data available

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : approx. 1.47 g/cm<sup>3</sup> (20 °C)



## MasterSeal 658 fre gry

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
Date of first issue: 08/12/2020

---

Solubility(ies)  
Water solubility : dispersible

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : No applicable information available.  
Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

## MasterSeal 658 fre gry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/12/2020	000000260208	Date of first issue: 08/12/2020

---

**Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks : May cause irreversible eye damage.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Product:**

Remarks : Causes sensitization.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Suspected of causing cancer.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Lung) through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration hazard expected.

**Further information****Product:**

## MasterSeal 658 fre gry

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
Date of first issue: 08/12/2020

---

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****bronopol:**

M-Factor (Acute aquatic toxicity) : 10

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Quartz (SiO<sub>2</sub>):**

Partition coefficient: n-octanol/water : Remarks: not applicable

**Titanium dioxide:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**ammonia:**

Partition coefficient: n-octanol/water : log Pow: 0.23 (20 °C)  
Method: other (calculated)  
Remarks: The value has not been determined because the substance is inorganic.

**2-dimethylaminoethanol:**

Partition coefficient: n-octanol/water : log Pow: -0.55 (23 °C)  
Method: internal method

**chlorothalonil:**

Partition coefficient: n-octanol/water : log Pow: 2.94 (25 °C)

**ammonia, aqueous solution:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**bronopol:**

Partition coefficient: n-octanol/water : Pow: 1.64 (24 °C)  
log Pow: 0.22 (24 °C)  
pH: 7

**MasterSeal 658 fre gry**

Version 1.0      Revision Date: 08/12/2020      SDS Number: 000000260208      Date of last issue: -  
Date of first issue: 08/12/2020

---

Method: Partition coefficient  
GLP: yes

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

Not regulated as a dangerous good

---

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

DSL : On the inventory, or in compliance with the inventory

---

## MasterSeal 658 fre gry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/12/2020	000000260208	Date of first issue: 08/12/2020

## SECTION 16. OTHER INFORMATION

**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A)	:	OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	:	OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1001-1050	:	OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH	:	NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
29 CFR 1910.1000 (Table Z-1-A) / STEL value	:	Short Term Exposure Limit (STEL):
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
29 CFR 1910.1001-1050 / OSHA Action level	:	OSHA Action level:
29 CFR 1910.1001-1050 / TWA value	:	Time Weighted Average (TWA):
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIHTLV / STEL value	:	Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH / STEL value	:	Short Term Exposure Limit (STEL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for

## MasterSeal 658 fre gry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/12/2020	000000260208	Date of first issue: 08/12/2020

---

Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 08/12/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE

**MasterSeal 658 fre gry**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/12/2020	000000260208	Date of first issue: 08/12/2020

---

ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN