

MasterSeal 658TB neu

Version Revision Date: SDS Number: Date of last issue: -
1.0 08/05/2020 000000261613 Date of first issue: 08/05/2020

SECTION 1. IDENTIFICATION

Product name : MasterSeal 658TB neu
Product code : 000000000056586551 000000000056586551
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : MBSCS Canada, Inc.
Address : 7111 Syntex Drive, 3rd Floor
 Mississauga ON L5N 8C3
Emergency telephone : ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.


SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Skin corrosion/irritation : 2
Serious eye damage/eye irritation : Category 2A
Skin sensitization : Category 1
Carcinogenicity : 1A
Specific target organ toxicity : Category 1
- repeated exposure (Inhalation)
Specific target organ toxicity : 2 (Kidney, Immune system)
- repeated exposure (Inhalation)
Short-term (acute) aquatic hazard : 3
Long-term (chronic) aquatic hazard : 3

GHS label elements

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

- Hazard pictograms : 
- Signal Word : Danger
- Hazard Statements : H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H372 Causes damage to organs through prolonged or repeated exposure if inhaled.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
P260 Do not breathe dust or mist.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
- Response:**
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.
- Storage:**
P405 Store locked up.
- Disposal:**
P501 Dispose of contents/container to appropriate hazardous waste collection point.

MasterSeal 658TB neu

Version 1.0 Revision Date: 08/05/2020 SDS Number: 000000261613 Date of last issue: -
 Date of first issue: 08/05/2020

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	>= 25 - < 50
Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	25265-77-4	>= 1 - < 3
2-dimethylaminoethanol	108-01-0	>= 0.3 - < 1
ammonia	7664-41-7	>= 0.3 - < 1
bronopol	52-51-7	>= 0.2 - < 0.3
ammonia, aqueous solution	1336-21-6	>= 0.2 - < 0.3
chlorothalonil	1897-45-6	>= 0.2 - < 0.3
Limestone	1317-65-3	>= 0.1 - <= 0.3
Titanium dioxide	13463-67-7	>= 0.1 - < 0.3

SECTION 4. FIRST AID MEASURES

- General advice** : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
- If inhaled** : Keep patient calm, remove to fresh air, seek medical attention. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact** : Immediately wash thoroughly with soap and water, seek medical attention. If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact** : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
- Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure if inhaled.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Product is not explosive.

Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	REL value (Respirable)	5 mg/m ³	NIOSH

MasterSeal 658TB neu

Version 1.0 Revision Date: 08/05/2020 SDS Number: 000000261613 Date of last issue: -
 Date of first issue: 08/05/2020

		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		STEL	20 mg/m3	CA BC OEL
ammonia, aqueous solution	1336-21-6	STEL value	35 ppm	ACGIHTLV
		TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 18 mg/m3	NIOSH
		STEL value	35 ppm 27 mg/m3	NIOSH
		PEL	50 ppm 35 mg/m3	29 CFR 1910.1000 (Table Z-1)
		STEL value	35 ppm 27 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm (Ammonia)	ACGIH
		STEL	35 ppm (Ammonia)	ACGIH
		TWA	25 ppm 18 mg/m3 (Ammonia)	NIOSH REL
		ST	35 ppm 27 mg/m3 (Ammonia)	NIOSH REL
ammonia	7664-41-7	STEL value	35 ppm	ACGIHTLV
		TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 18 mg/m3	NIOSH
		STEL value	35 ppm 27 mg/m3	NIOSH
		PEL	50 ppm 35 mg/m3	29 CFR 1910.1000 (Table Z-1)

MasterSeal 658TB neu

Version
1.0Revision Date:
08/05/2020SDS Number:
000000261613Date of last issue: -
Date of first issue: 08/05/2020

		STEL value	35 ppm 27 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm 17 mg/m ³	CA AB OEL
		STEL	35 ppm 24 mg/m ³	CA AB OEL
		TWA	25 ppm	CA BC OEL
		STEL	35 ppm	CA BC OEL
		TWAEV	25 ppm 17 mg/m ³	CA QC OEL
		STEV	35 ppm 24 mg/m ³	CA QC OEL
		TWA	25 ppm (Ammonia)	ACGIH
		STEL	35 ppm (Ammonia)	ACGIH
Quartz (SiO ₂)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m ³	ACGIH TLV
		TWA value	0.05 mg/m ³ (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m ³ (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m ³	NIOSH
		TWA (Res- pirable par- ticulates)	0.025 mg/m ³	CA AB OEL
		TWA (Res- pirable frac- tion)	0.1 mg/m ³	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m ³	CA QC OEL
		TWA (Res- pirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m ³ (Silica)	ACGIH

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Protective measures	:	Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	pigmented
Odor	:	product specific
Odor Threshold	:	No data available
pH	:	9 - 9.7
Melting point	:	No applicable information available.
Freezing point	:	No applicable information available.
Boiling point	:	No data available.
Flash point	:	not applicable
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not determined
Upper explosion limit / Upper flammability limit	:	No applicable information available.
Lower explosion limit / Lower	:	No applicable information available.

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

flammability limit

Vapor pressure : No data available

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : approx. 1.5 g/cm³ (20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

MasterSeal 658TB neu

Version 1.0 Revision Date: 08/05/2020 SDS Number: 000000261613 Date of last issue: -
Date of first issue: 08/05/2020

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.
May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information**Product:**

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****bronopol:**

M-Factor (Acute aquatic toxicity) : 10

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Quartz (SiO₂):**

Partition coefficient: n-octanol/water : Remarks: not applicable

Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol:

Partition coefficient: n-octanol/water : log Pow: 3.2 (25 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), HPLC method.
GLP: no

2-dimethylaminoethanol:

Partition coefficient: n-octanol/water : log Pow: -0.55 (23 °C)
Method: internal method

ammonia:

Partition coefficient: n-octanol/water : log Pow: 0.23 (20 °C)

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

octanol/water

Method: other (calculated)

Remarks: The value has not been determined because the substance is inorganic.

bronopol:

Partition coefficient: n-octanol/water

: Pow: 1.64 (24 °C)
 log Pow: 0.22 (24 °C)
 pH: 7
 Method: Partition coefficient
 GLP: yes

ammonia, aqueous solution:

Partition coefficient: n-octanol/water

: Remarks: not applicable

chlorothalonil:

Partition coefficient: n-octanol/water

: log Pow: 2.94 (25 °C)

Titanium dioxide:

Partition coefficient: n-octanol/water

: Remarks: not applicable

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
 Harmful to aquatic life.
 Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues

: Do not contaminate ponds, waterways or ditches with chemical or used container.
 Dispose of in accordance with national, state and local regulations.
 Do not discharge into drains/surface waters/groundwater.

Contaminated packaging

: Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**The ingredients of this product are reported in the following inventories:**

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1001-1050	: OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
29 CFR 1910.1000 (Table Z-1-A) / STEL value	: Short Term Exposure Limit (STEL):
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-	: Permissible exposure limit

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

1) / PEL
 29 CFR 1910.1001-1050 / : OSHA Action level:
 OSHA Action level
 29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):
 TWA value
 ACGIH / TWA : 8-hour, time-weighted average
 ACGIH / STEL : Short-term exposure limit
 ACGIH TLV / STEL value : Short Term Exposure Limit (STEL):
 ACGIH TLV / TWA value : Time Weighted Average (TWA):
 CA AB OEL / TWA : 8-hour Occupational exposure limit
 CA AB OEL / STEL : 15-minute occupational exposure limit
 CA BC OEL / TWA : 8-hour time weighted average
 CA BC OEL / STEL : short-term exposure limit
 CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
 CA QC OEL / TWA EV : Time-weighted average exposure value
 CA QC OEL / STEV : Short-term exposure value
 NIOSH / REL value : Recommended exposure limit (REL):
 NIOSH / STEL value : Short Term Exposure Limit (STEL):
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
 workday during a 40-hour workweek
 NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
 at any time during a workday

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

MasterSeal 658TB neu

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2020	000000261613	Date of first issue: 08/05/2020

Revision Date : 08/05/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN