

MasterSeal AWB 600 FL

Version 1.0 Revision Date: 09/04/2020 SDS Number: 000000594500 Date of last issue: -
Date of first issue: 09/04/2020

SECTION 1. IDENTIFICATION

Product name : MasterSeal AWB 600 FL
Product code : 000000000050372864 000000000050372864
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : MBSCS Canada, Inc.
Address : 7111 Syntex Drive, 3rd Floor
Mississauga ON L5N 8C3
Emergency telephone : ChemTel: +1-813-248-0585;


Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Skin sensitization : Category 1
Carcinogenicity (Inhalation) : 1A
Specific target organ toxicity : Category 1
- repeated exposure (Inhalation)
Specific target organ toxicity : 2 (Kidney, Immune system)
- repeated exposure (Inhalation)

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

MasterSeal AWB 600 FL

Version 1.0 Revision Date: 09/04/2020 SDS Number: 000000594500 Date of last issue: -
 Date of first issue: 09/04/2020

Precautionary Statements : **Prevention:**
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P201 Obtain special instructions before use.
 P260 Do not breathe dust or mist.
 P202 Do not handle until all safety precautions have been read and understood.
 P270 Do not eat, drink or smoke when using this product.
 P264 Wash face, hands and any exposed skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.

Response:
 P314 Get medical advice/ attention if you feel unwell.
 P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
 P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
 P405 Store locked up.

Disposal:
 P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Components**

| Chemical name | CAS-No. | Concentration (% w/w) |
|------------------------------------|------------|-----------------------|
| Limestone | 1317-65-3 | >= 25 - < 100 |
| Quartz (SiO ₂) | 14808-60-7 | >= 10 - < 50 |
| Kieselguhr, soda ash flux-calcined | 68855-54-9 | >= 3 - < 5 |
| Titanium dioxide | 13463-67-7 | >= 0.3 - < 1 |
| 2-(Hydroxymethylamino)ethanol | 34375-28-5 | >= 0.1 - < 0.2 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this material safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical

MasterSeal AWB 600 FL

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 09/04/2020 | 000000594500 | Date of first issue: 09/04/2020 |

- advice.
- In case of skin contact : If on skin, rinse well with water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure if inhaled.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

MasterSeal AWB 600 FL

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 09/04/2020 | 000000594500 | Date of first issue: 09/04/2020 |

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Materials to avoid : No applicable information available.
- Recommended storage temperature : 5 °C
- Further information on storage stability : Minimum storage temperature:

MasterSeal AWB 600 FL

Version 1.0 Revision Date: 09/04/2020 SDS Number: 000000594500 Date of last issue: -
 Date of first issue: 09/04/2020

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------------|------------|--|--|--------------------------------------|
| Limestone | 1317-65-3 | REL value (Respirable) | 5 mg/m ³ | NIOSH |
| | | REL value (Total) | 10 mg/m ³ | NIOSH |
| | | PEL (Respirable fraction) | 5 mg/m ³ | 29 CFR 1910.1000 (Table Z-1) |
| | | PEL (Total dust) | 15 mg/m ³ | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Respirable fraction) | 5 mg/m ³ | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA value (Total dust) | 15 mg/m ³ | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA | 10 mg/m ³ | CA AB OEL |
| | | TWAEV (total dust) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Total dust) | 10 mg/m ³ | CA BC OEL |
| | | TWA (respirable dust fraction) | 3 mg/m ³ | CA BC OEL |
| | | STEL | 20 mg/m ³ | CA BC OEL |
| Quartz (SiO ₂) | 14808-60-7 | TWA value (Respirable fraction) | 0.025 mg/m ³ | ACGIHTLV |
| | | TWA value (Respirable dust) | 0.05 mg/m ³ | 29 CFR 1910.1001-1050 |
| | | OSHA Action level (Respirable dust) | 0.025 mg/m ³ | 29 CFR 1910.1001-1050 |
| | | REL value (Respirable dust) | 0.05 mg/m ³ | NIOSH |
| | | TWA (Respirable particulates) | 0.025 mg/m ³ | CA AB OEL |
| | | TWA (Respirable fraction) | 0.1 mg/m ³ | CA ON OEL |
| | | TWAEV (respirable dust) | 0.1 mg/m ³ | CA QC OEL |
| | | TWA (Res- | 0.025 mg/m ³ | CA BC OEL |

MasterSeal AWB 600 FL

Version 1.0 Revision Date: 09/04/2020 SDS Number: 000000594500 Date of last issue: -
 Date of first issue: 09/04/2020

| | | | | |
|------------------------------------|------------|-------------------------------------|--|------------------------------|
| | | pirable) | (Silica) | |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |
| Kieselguhr, soda ash flux-calcined | 68855-54-9 | REL value | 6 mg/m3 | NIOSH |
| | | TWA value | 20 millions of particles per cubic foot of air | 29 CFR 1910.1000 (Table Z-3) |
| | | TWA value | 0.8 mg/m3 | 29 CFR 1910.1000 (Table Z-3) |
| | | OSHA Action level | 0.025 mg/m3 (Respirable dust) | 29 CFR 1910.1001-1050 |
| | | TWA value | 0.05 mg/m3 (Respirable dust) | 29 CFR 1910.1001-1050 |
| | | TWA (Dust) | 20 Million particles per cubic foot (Silica) | OSHA Z-3 |
| | | TWA (Dust) | 80 mg/m3 / %SiO2 (Silica) | OSHA Z-3 |
| | | TWA | 6 mg/m3 (Silica) | NIOSH REL |

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

MasterSeal AWB 600 FL

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 09/04/2020 | 000000594500 | Date of first issue: 09/04/2020 |

When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|---|
| Appearance | : | viscous |
| Color | : | white |
| Odor | : | faint odour |
| Odor Threshold | : | No data available |
| pH | : | 8.5 - 9 (73 °F) |
| Melting point | : | No applicable information available. |
| Freezing point | : | No applicable information available. |
| Boiling point | : | No applicable information available. |
| Flash point | : | does not flash |
| Evaporation rate | : | No applicable information available. |
| Flammability (solid, gas) | : | not determined |
| Self-ignition | : | Based on the water content the product does not ignite. |
| Upper explosion limit / Upper flammability limit | : | No applicable information available. |
| Lower explosion limit / Lower flammability limit | : | No applicable information available. |
| Vapor pressure | : | No data available |
| Relative vapor density | : | No applicable information available. |
| Relative density | : | No applicable information available. |
| Density | : | 1.74 g/cm ³ (22.78 °C) |
| Solubility(ies) | : | |
| Water solubility | : | No data available |
| Solubility in other solvents | : | No applicable information available. |
| Partition coefficient: n-octanol/water | : | No applicable information available. |

MasterSeal AWB 600 FL

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 09/04/2020 | 000000594500 | Date of first issue: 09/04/2020 |

| | | |
|---------------------------|---|--|
| Autoignition temperature | : | not applicable |
| Decomposition temperature | : | No decomposition if stored and handled as prescribed/indicated. |
| Viscosity | | |
| Viscosity, dynamic | : | No applicable information available. |
| Viscosity, kinematic | : | No applicable information available. |
| Oxidizing properties | : | Based on its structural properties the product is not classified as oxidizing. |
| Sublimation point | : | No applicable information available. |
| Molecular weight | : | No data available |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Reactivity | : | No decomposition if stored and applied as directed. |
| Chemical stability | : | No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed. |
| Conditions to avoid | : | See SDS section 7 - Handling and storage. |
| Incompatible materials | : | Strong acids Strong bases Strong oxidizing agents Strong reducing agents |
| Hazardous decomposition products | : | No hazardous decomposition products if stored and handled as prescribed/indicated. |

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapors may cause irritation to the eyes, respiratory system and the skin.

MasterSeal AWB 600 FL

Version 1.0 Revision Date: 09/04/2020 SDS Number: 000000594500 Date of last issue: -
Date of first issue: 09/04/2020

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.
May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Quartz (SiO₂):**

Partition coefficient: n- : Remarks: not applicable
octanol/water

Kieselguhr, soda ash flux-calcined:

Partition coefficient: n- : Remarks: not applicable

MasterSeal AWB 600 FL

Version 1.0 Revision Date: 09/04/2020 SDS Number: 000000594500 Date of last issue: -
Date of first issue: 09/04/2020

octanol/water

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

2-(Hydroxymethylamino)ethanol:

Partition coefficient: n-octanol/water : log Pow: -2.205
Method: other (calculated)
GLP: no data

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

MasterSeal AWB 600 FL

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 09/04/2020 | 000000594500 | Date of first issue: 09/04/2020 |

Domestic regulation**TDG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**The ingredients of this product are reported in the following inventories:**

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

| | |
|--|---|
| 29 CFR 1910.1000 (Table Z-1-A) | : OSHA - Table Z-1-A (29 CFR 1910.1000) |
| 29 CFR 1910.1000 (Table Z-1) | : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000 |
| 29 CFR 1910.1000 (Table Z-3) | : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000 |
| 29 CFR 1910.1001-1050 | : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050) |
| ACGIH | : USA. ACGIH Threshold Limit Values (TLV) |
| ACGIHTLV | : American Conference of Governmental Industrial Hygienists - threshold limit values (US) |
| CA AB OEL | : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL) |
| CA BC OEL | : Canada. British Columbia OEL |
| CA ON OEL | : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act. |
| CA QC OEL | : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants |
| NIOSH | : NIOSH Pocket Guide to Chemical Hazards (US) |
| NIOSH REL | : USA. NIOSH Recommended Exposure Limits |
| OSHA Z-3 | : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| 29 CFR 1910.1000 (Table Z-1-A) / TWA value | : Time Weighted Average (TWA): |
| 29 CFR 1910.1000 (Table Z-1) / PEL | : Permissible exposure limit |
| 29 CFR 1910.1000 (Table Z-3) / TWA value | : Time Weighted Average (TWA): |
| 29 CFR 1910.1001-1050 / OSHA Action level | : OSHA Action level: |
| 29 CFR 1910.1001-1050 / TWA value | : Time Weighted Average (TWA): |
| ACGIH / TWA | : 8-hour, time-weighted average |
| ACGIHTLV / TWA value | : Time Weighted Average (TWA): |
| CA AB OEL / TWA | : 8-hour Occupational exposure limit |
| CA BC OEL / TWA | : 8-hour time weighted average |
| CA BC OEL / STEL | : short-term exposure limit |
| CA ON OEL / TWA | : Time-Weighted Average Limit (TWA) |

MasterSeal AWB 600 FL

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 09/04/2020 | 000000594500 | Date of first issue: 09/04/2020 |

CA QC OEL / TWAEV : Time-weighted average exposure value
 NIOSH / REL value : Recommended exposure limit (REL):
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
 workday during a 40-hour workweek
 OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 09/04/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR

MasterSeal AWB 600 FL

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 09/04/2020 | 000000594500 | Date of first issue: 09/04/2020 |

TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN