

## MasterSeal AWB 900

Version 3.0      Revision Date: 06/09/2023      SDS Number: 000000699016      Date of last issue: 02/01/2023  
Date of first issue: 05/27/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterSeal AWB 900  
Product code : 000000000050500960 000000000050500960  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : MBSCS Canada, Inc.  
Address : 7111 Syntex Drive, 3rd Floor  
Mississauga ON L5N 8C3  
Emergency telephone : ChemTel: +1-813-248-0585;  
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

**Recommended use of the chemical and restrictions on use**


Recommended use : Waterproof coating  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Skin sensitization : Category 1  
Carcinogenicity (Inhalation) : Category 1A  
Reproductive toxicity : Category 1B  
Short-term (acute) aquatic hazard : Category 3  
Long-term (chronic) aquatic hazard : Category 3

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.  
H350 May cause cancer by inhalation.

## MasterSeal AWB 900

Version 3.0      Revision Date: 06/09/2023      SDS Number: 000000699016      Date of last issue: 02/01/2023  
 Date of first issue: 05/27/2020

H360 May damage fertility or the unborn child.  
 H402 Harmful to aquatic life.  
 H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P261 Avoid breathing mist or vapors.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P363 Wash contaminated clothing before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Mixture based on:  
 polymers

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
calcium carbonate	Carbonic acid calcium salt (1:1)	471-34-1	>= 30 - < 50
Limestone	Calcium carbonate	1317-65-3	>= 10 - < 20
Titanium dioxide	C.I. Pigment White 6	13463-67-7	>= 1 - < 5
Triethoxyoctylsilane	Silane, triethoxyoctyl-	2943-75-1	>= 1 - < 5
Calcium distearate	Octadecanoic acid, calcium salt	1592-23-0	>= 1 - < 5

## MasterSeal AWB 900

Version 3.0      Revision Date: 06/09/2023      SDS Number: 000000699016      Date of last issue: 02/01/2023  
 Date of first issue: 05/27/2020

Carbon black	Lampblack	1333-86-4	>= 0.1 - < 1
Aminoethyl aminopropyl trimethoxy silane	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-	1760-24-3	>= 0.1 - < 1
Proprietary amide wax**	Proprietary amide wax	Proprietary**	>= 0.1 - < 1
bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate	Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidiny) ester	52829-07-9	>= 0.1 - < 1
Dibutyltin diacetylacetonate	Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	22673-19-4	>= 0.1 - < 1
Quartz (SiO <sub>2</sub> )	Crystalline silica	14808-60-7	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

\*\* See Section 15 for HMIRA information.

\*\*The masked component(s) has only environmental hazards; HMIRA claims are not required for masked components with only environmental hazards.

## SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Remove contaminated clothing.
- If inhaled : If generated vapours are inhaled, move to fresh air. Seek medical attention.
- In case of skin contact : Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Remove contact lenses, if present, after first 5 minutes, then continue rinsing for an additional 15 minutes.
- If swallowed : Rinse mouth and then drink 200-300 ml of water. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction. May cause cancer by inhalation. May damage fertility or the unborn child.
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

## MasterSeal AWB 900

Version 3.0      Revision Date: 06/09/2023      SDS Number: 000000699016      Date of last issue: 02/01/2023  
Date of first issue: 05/27/2020

---

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Sweep/shovel up.  
Dispose of absorbed material in accordance with regulations.
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid contact with the skin, eyes and clothing.
- Conditions for safe storage : Keep only in the original container in a cool, well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Protect from direct sunlight.  
Store protected against freezing.
- Recommended storage temperature : > 4 °C

## MasterSeal AWB 900

Version  
3.0Revision Date:  
06/09/2023SDS Number:  
000000699016Date of last issue: 02/01/2023  
Date of first issue: 05/27/2020

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	10 mg/m <sup>3</sup> (Calcium carbonate)	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Limestone	1317-65-3	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable particulate matter)	0.2 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
Calcium distearate	1592-23-0	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Inhalable)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (Respirable)	3 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable particulate matter)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable particulate matter)	3 mg/m <sup>3</sup>	ACGIH

## MasterSeal AWB 900

Version  
3.0Revision Date:  
06/09/2023SDS Number:  
000000699016Date of last issue: 02/01/2023  
Date of first issue: 05/27/2020

Dibutyltin diacetyldiacetate	22673-19-4	ter)		
		TWA value	0.1 mg/m3 (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m3 (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m3 (tin (Sn))	NIOSH
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	CA AB OEL
		STEL	0.2 mg/m3 (Tin)	CA AB OEL
		TWAEV	0.1 mg/m3 (Tin)	CA QC OEL
		STEV	0.2 mg/m3 (Tin)	CA QC OEL
		TWA	0.1 mg/m3 (Tin)	CA BC OEL
		STEL	0.2 mg/m3 (Tin)	CA BC OEL
		TWA	0.1 mg/m3 (Tin)	CA ON OEL
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.  
Use NIOSH approved respiratory protection.

## MasterSeal AWB 900

Version	Revision Date:	SDS Number:	Date of last issue: 02/01/2023
3.0	06/09/2023	000000699016	Date of first issue: 05/27/2020

---

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Avoid contact with the skin, eyes and clothing.  
No special measures necessary if stored and handled correctly.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : gray

Odor : faint odour

Odor Threshold : No data available

pH : insoluble

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : 93.34 °C

Method: Standard Method of Test for Flash Point by Setaflash Closed Tester

Evaporation rate : No data available

## MasterSeal AWB 900

Version 3.0      Revision Date: 06/09/2023      SDS Number: 000000699016      Date of last issue: 02/01/2023  
Date of first issue: 05/27/2020

---

Flammability (solid, gas)	:	not flammable Method: derived from flash point
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	approx. 12.65 lb/USg (23 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	approx. 7,000 mPa.s ( 23 °C) Method: Adhesives - Determination of viscosity
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Sublimation point	:	No data available
Molecular weight	:	Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.



## MasterSeal AWB 900

Version	Revision Date:	SDS Number:	Date of last issue: 02/01/2023
3.0	06/09/2023	000000699016	Date of first issue: 05/27/2020

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

## SECTION 11. TOXICOLOGICAL INFORMATION

**Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

<b>IARC</b>	Group 1: Carcinogenic to humans	
	Quartz (SiO <sub>2</sub> ) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans	
	Carbon black	1333-86-4

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

## MasterSeal AWB 900

Version 3.0      Revision Date: 06/09/2023      SDS Number: 000000699016      Date of last issue: 02/01/2023  
Date of first issue: 05/27/2020

---

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Calcium distearate:**

Partition coefficient: n-octanol/water : log Pow: 0.8  
Method: OECD Test Guideline 107

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into drains/surface waters/groundwater.

---

## MasterSeal AWB 900

Version	Revision Date:	SDS Number:	Date of last issue: 02/01/2023
3.0	06/09/2023	000000699016	Date of first issue: 05/27/2020

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

## SECTION 14. TRANSPORT INFORMATION

## International Regulations

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

**The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

## SECTION 16. OTHER INFORMATION

**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)

29 CFR 1910.1000 (Table Z-) : Time Weighted Average (TWA):

## MasterSeal AWB 900

Version	Revision Date:	SDS Number:	Date of last issue: 02/01/2023
3.0	06/09/2023	000000699016	Date of first issue: 05/27/2020

1-A) / TWA value  
 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit  
 ACGIH / TWA : 8-hour, time-weighted average  
 ACGIH / STEL : Short-term exposure limit  
 ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):  
 ACGIHTLV / TWA value : Time Weighted Average (TWA):  
 CA AB OEL / TWA : 8-hour Occupational exposure limit  
 CA AB OEL / STEL : 15-minute occupational exposure limit  
 CA BC OEL / TWA : 8-hour time weighted average  
 CA BC OEL / STEL : short-term exposure limit  
 CA ON OEL / TWA : Time-Weighted Average Limit (TWA)  
 CA QC OEL / TWAEV : Time-weighted average exposure value  
 CA QC OEL / STEV : Short-term exposure value  
 NIOSH / REL value : Recommended exposure limit (REL):

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 06/09/2023  
 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

**MasterSeal AWB 900**

Version	Revision Date:	SDS Number:	Date of last issue: 02/01/2023
3.0	06/09/2023	000000699016	Date of first issue: 05/27/2020

---

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN