

## MasterSeal M 205 SL

Version 1.0      Revision Date: 07/09/2020      SDS Number: 000000722889      Date of last issue: -  
Date of first issue: 07/09/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterSeal M 205 SL  
Product code : 000000000050465381 000000000050465381  
Other means of identification : MSeal M 205 SL

**Manufacturer or supplier's details**

Company name of supplier : MBSCS Canada, Inc.  
Address : 7111 Syntex Drive, 3rd Floor  
Mississauga ON L5N 8C3  
Emergency telephone : ChemTel: +1-813-248-0585;

**Recommended use of the chemical and restrictions on use**

Recommended use : Product for construction chemicals  
Water repellent  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 3  
Acute toxicity (Inhalation - vapour) : Category 3  
Reproductive toxicity : Category 1B  
Respiratory sensitization : Category 1  
Skin sensitization : Category 1  
Carcinogenicity : Category 2  
Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

H331 Toxic if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H360 May damage fertility or the unborn child.

## Precautionary Statements

:

**Prevention:**

P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take action to prevent static discharges.  
P202 Do not handle until all safety precautions have been read and understood.  
P284 In case of inadequate ventilation wear respiratory protection.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.

**Response:**

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P311 Call a POISON CENTER or doctor/ physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.  
Collect solid spillage.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P233 Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

## MasterSeal M 205 SL

Version 1.0      Revision Date: 07/09/2020      SDS Number: 000000722889      Date of last issue: -  
 Date of first issue: 07/09/2020

**Other hazards**

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : polyurethane

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 0 - < 50
talc	14807-96-6	>= 7 - < 10
4-Chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	98-56-6	>= 5 - < 7
Stoddard solvent	8052-41-3	>= 5 - < 7
Calcium sulphate	7778-18-9	>= 1 - < 3.5
Titanium dioxide	13463-67-7	>= 0 - < 5
4-methyl-m-phenylene diisocyanate	584-84-9	>= 1 - < 3
trimethoxy(3-(oxiranylmethoxy)propyl)silane	2530-83-8	>= 0.3 - < 1
toluene-2,6-diisocyanate	91-08-7	>= 0.2 - < 0.3
dibutyltin dilaurate	77-58-7	>= 0.1 - < 0.2

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this material safety data sheet to the doctor in attendance.  
 Symptoms of poisoning may appear several hours later.  
 Do not leave the victim unattended.  
 Take off immediately all contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.  
 Assist in breathing if necessary.  
 Immediate medical attention required.
- In case of skin contact : Wash affected areas thoroughly with soap and water.  
 If irritation develops, seek medical attention.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
 If easy to do, remove contact lens, if worn.

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

- Seek medical advice.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.  
Do NOT induce vomiting.  
Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.  
Immediate medical attention required.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Toxic if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing cancer.  
May damage fertility or the unborn child.  
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)  
Foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : nitrous gases  
fumes/smoke  
isocyanate  
vapor
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Use personal protective equipment.

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

- Remove all sources of ignition.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Dike spillage.  
If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal.  
Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information).  
Shovel into open container.  
Spill area can be decontaminated with the following recommended decontamination solution:  
Mixture of 90 % water, 5-8 % household ammonia, 2-5 % detergent.  
Wash down spill area with decontamination solution.  
Allow solution to stand for at least 10 minutes.  
Pick up with suitable absorbent material.  
Place into appropriately labeled waste containers.  
Do not make container pressure tight.  
Move container to a well-ventilated area (outside).  
Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.  
Dispose of absorbed material in accordance with regulations.

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Product is not explosive.
- Keep away from open flames, hot surfaces and sources of ignition.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national

## MasterSeal M 205 SL

Version 1.0      Revision Date: 07/09/2020      SDS Number: 000000722889      Date of last issue: -  
Date of first issue: 07/09/2020

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Ensure thorough ventilation of stores and work areas.  
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.  
Wear respiratory protection when spraying.  
If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.  
Protect against moisture.

- Conditions for safe storage : Prevent unauthorized access.  
no smoking  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Observe VCI storage rules.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m <sup>3</sup> (tin (Sn))	NIOSH
		PEL	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m <sup>3</sup> (Tin)	CA AB OEL
		STEL	0.2 mg/m <sup>3</sup> (Tin)	CA AB OEL
		TWAEV	0.1 mg/m <sup>3</sup> (Tin)	CA QC OEL
		STEV	0.2 mg/m <sup>3</sup> (Tin)	CA QC OEL

**SAFETY DATA SHEET**

**MasterSeal M 205 SL**

Version 1.0      Revision Date: 07/09/2020      SDS Number: 000000722889      Date of last issue: -  
 Date of first issue: 07/09/2020

		TWA	0.1 mg/m3 (Tin)	CA BC OEL
		STEL	0.2 mg/m3 (Tin)	CA BC OEL
		TWA	0.1 mg/m3 (Tin)	CA ON OEL
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
toluene-2,6-diisocyanate	91-08-7	STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		Skin Designation (Inhalable fraction and vapor)		ACGIHTLV
		TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm 0.04 mg/m3	CA AB OEL
		(c)	0.02 ppm 0.1 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
4-methyl-m-phenylene diisocyanate	584-84-9	TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		Skin Designation (Inhalable fraction and vapor)		ACGIHTLV
		STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		CLV	0.02 ppm 0.14 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA	0.005 ppm	CA BC OEL

## MasterSeal M 205 SL

Version  
1.0Revision Date:  
07/09/2020SDS Number:  
000000722889Date of last issue: -  
Date of first issue: 07/09/2020

		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm 0.04 mg/m <sup>3</sup>	CA AB OEL
		(c)	0.02 ppm 0.1 mg/m <sup>3</sup>	CA AB OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
Limestone	1317-65-3	REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Calcium sulphate	7778-18-9	TWA value (Inhalable fraction)	10 mg/m <sup>3</sup>	ACGIHTLV
		REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)



## MasterSeal M 205 SL

Version  
1.0Revision Date:  
07/09/2020SDS Number:  
000000722889Date of last issue: -  
Date of first issue: 07/09/2020

		TWA value (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Inhalable)	10 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (respirable dust)	5 mg/m <sup>3</sup>	CA QC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Calcium)	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Inhalable particulate matter)	10 mg/m <sup>3</sup>	ACGIH
Titanium dioxide	13463-67-7	TWA value	10 mg/m <sup>3</sup>	ACGIHTLV
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Titanium dioxide)	10 mg/m <sup>3</sup>	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIHTLV
		TWAEV (fibers)	1 fibres per cubic centimeter	CA QC OEL
		TWAEV (respirable dust)	3 mg/m <sup>3</sup>	CA QC OEL
		TWA	0.1 fibres per cubic centimeter	CA BC OEL
		TWA (Respirable particulates)	2 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable)	2 mg/m <sup>3</sup>	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	CA ON OEL
		TWA	0.1 fibres per cubic centimeter	ACGIH

## MasterSeal M 205 SL

Version 1.0      Revision Date: 07/09/2020      SDS Number: 000000722889      Date of last issue: -  
 Date of first issue: 07/09/2020

		TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIH TLV
		REL value	350 mg/m <sup>3</sup>	NIOSH
		Ceil_Time	1,800 mg/m <sup>3</sup>	NIOSH
		PEL	500 ppm 2,900 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm 572 mg/m <sup>3</sup>	CA AB OEL
		TWA	290 mg/m <sup>3</sup>	CA BC OEL
		STEL	580 mg/m <sup>3</sup>	CA BC OEL
		TWAEV	100 ppm 525 mg/m <sup>3</sup>	CA QC OEL
		TWA	525 mg/m <sup>3</sup>	CA ON OEL
		TWA	100 ppm	ACGIH

**Engineering measures** : Provide local exhaust ventilation to maintain recommended P.E.L.

**Personal protective equipment**

**Respiratory protection** : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.  
 When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.  
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection

**Remarks** : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) depending upon conditions of use.  
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Tightly fitting safety goggles (chemical goggles).  
 Wear face shield if splashing hazard exists.

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

- Skin and body protection : Cover as much of the exposed skin as possible to prevent all skin contact.  
Suitable materials may include saran-coated material depending upon conditions of use.  
Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Wear protective clothing as necessary to prevent contact.  
Eye wash fountains and safety showers must be easily accessible.  
Observe the appropriate PEL or TLV value.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.  
Wash soiled clothing immediately.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : gray
- Odor : aromatic, solvent
- Odor Threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling range : 220 - 300 °C
- Flash point : 49.3 °C  
Method: Flash-Point by Pensky-Martens Closed Cup Tester.
- Evaporation rate : No applicable information available.
- Flammability (solid, gas) : Flammable.  
Method: derived from flash point
- Upper explosion limit / Upper : No applicable information available.

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

flammability limit

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : No data available

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : approx. 1.2500 g/cm<sup>3</sup> (20 °C)

Bulk density : not applicable

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Oxidizing properties : not determined

Sublimation point : No applicable information available.

Molecular weight : No data available

---

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : Reacts with water, with formation of carbon dioxide.  
Risk of bursting.  
Reacts with alcohols.  
Reacts with acids.  
Reacts with alkalis.  
Reacts with amines.  
Risk of exothermic reaction.  
Risk of polymerization.

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Avoid moisture.

Incompatible materials : Acids  
Amines  
Alcohols  
Water  
Alkalines  
Strong bases  
Substances/products that react with isocyanates.

Hazardous decomposition products : nitrogen oxides  
Aromatic isocyanates  
gases/vapours

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Toxic if inhaled.

**Product:**

Acute inhalation toxicity : ATE: 9.62 mg/l  
Remarks: Determined for vapor

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Vapors may cause irritation to the eyes, respiratory system and the skin.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Suspected of causing cancer.

## MasterSeal M 205 SL

Version 1.0      Revision Date: 07/09/2020      SDS Number: 000000722889      Date of last issue: -  
Date of first issue: 07/09/2020

---

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****talc:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**4-Chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene:**

Partition coefficient: n-octanol/water : log Pow: 3.6  
Method: other (calculated)  
Remarks: Information taken from reference works and the literature.

**Stoddard solvent:**

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (20 °C)  
Method: Partition coefficient (n-octanol/water), HPLC method.

**Calcium sulphate:**

Partition coefficient: n-octanol/water : GLP: no  
Remarks: The value has not been determined because the substance is inorganic.

**Titanium dioxide:**

Partition coefficient: n-octanol/water : Remarks: not applicable

---

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

**4-methyl-m-phenylene diisocyanate:**

Partition coefficient: n-octanol/water : log Pow: 3.43 (22 °C)  
pH: 7  
Method: Partition coefficient (n-octanol/water), HPLC method.  
GLP: no  
Remarks: Based on data from similar materials

**trimethoxy(3-(oxiranylmethoxy)propyl)silane:**

Partition coefficient: n-octanol/water : log Pow: -0.915  
Method: other (calculated)  
Remarks: unmeasurable

**toluene-2,6-diisocyanate:**

Partition coefficient: n-octanol/water : log Pow: 3.74  
Method: other (calculated)

**dibutyltin dilaurate:**

Partition coefficient: n-octanol/water : log Pow: 3.17 (20.8 °C)  
pH: 6.1 - 6.3  
Method: Partition coefficient (n-octanol/water), Shake-flask method  
GLP: yes

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : No data available  
An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Incinerate or dispose of in a licensed facility.  
Do not discharge substance/product into sewer system.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations**

IATA-DGR

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

UN/ID No. : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
 Proper shipping name : PAINT  
 (4-METHYL-META-PHENYLENEDIISOCYANATE, 2-METHYL-META-PHENYLENEDIISOCYANATE, STODDARD SOLVENT)  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 ERG Code : 128  
 Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.  
 DSL : All components of this product are on the Canadian DSL

**TSCA list**

This product contains the following component which is subject to a TSCA § 5(a) proposed Significant New Use Restriction (SNUR):



## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

4-methyl-m-phenylene diisocyanate	584-84-9
toluene-2,6-diisocyanate	91-08-7

## SECTION 16. OTHER INFORMATION

**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)

29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z-1) / CLV : Ceiling Limit Value:

29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

ACGIHTLV / Skin Designation : Skin Designation:

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):

ACGIHTLV / TWA value : Time Weighted Average (TWA):

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA AB OEL / (c) : ceiling occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / STEL : short-term exposure limit

CA BC OEL / C : ceiling limit

CA ON OEL / C : Ceiling Limit (C)

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)

CA QC OEL / TWA EV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

NIOSH / Ceil\_Time : Ceiling Limit Value and Time Period (if specified):

NIOSH / REL value : Recommended exposure limit (REL):

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with

## MasterSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	000000722889	Date of first issue: 07/09/2020

---

x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 07/09/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

**MasterSeal M 205 SL**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/09/2020	00000722889	Date of first issue: 07/09/2020

---

CA / EN