

MasterTop SRS 41P

Version 2.0 Revision Date: 03/29/2021 SDS Number: 000000260446 Date of last issue: 08/04/2020
Date of first issue: 08/04/2020

SECTION 1. IDENTIFICATION

Product name : MasterTop SRS 41P
Product code : 000000000056433911 000000000056433911
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : MBSCS Canada, Inc.
Address : 7111 Syntex Drive, 3rd Floor
Mississauga ON L5N 8C3
Emergency telephone : ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 2
Skin corrosion/irritation : Category 2
Skin sensitization : Category 1B
Carcinogenicity : Category 2
Specific target organ toxicity - single exposure : Category 3
Short-term (acute) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

MasterTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	03/29/2021	000000260446	Date of first issue: 08/04/2020

H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H402 Harmful to aquatic life.

Precautionary Statements

:

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P201 Obtain special instructions before use.
P271 Use only outdoors or in a well-ventilated area.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P243 Take action to prevent static discharges.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ .? / equipment.
P272 Contaminated work clothing should not be allowed out of the workplace.
P242 Use only non-sparking tools.
P240 Ground and bond container and receiving equipment.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P233 Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : acrylic polymers

MasterTop SRS 41P

Version 2.0 Revision Date: 03/29/2021 SDS Number: 000000260446 Date of last issue: 08/04/2020
 Date of first issue: 08/04/2020

methacrylic ester

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
methyl methacrylate	methyl methacrylate	80-62-6	$\geq 50 - \leq 100$
1,4-butanediol dimethacrylate	1,4-butanediol dimethacrylate	2082-81-7	$\geq 5 - < 10$
1,1'-(p-tolylimino)dipropan-2-ol	1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3	$\geq 1 - < 5$
N,N-dimethyl-p-toluidine	N,N-Dimethyl-p-toluidine	99-97-8	$\geq 0.01 - < 1$

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Remove contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.
 If breathing difficulties develop, aid in breathing and seek immediate medical attention.
 If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash thoroughly with soap and water
 Under no circumstances should organic solvent be used.
 If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.
 Do not induce vomiting due to aspiration hazard.
 Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 May cause an allergic skin reaction.
 May cause respiratory irritation.
 Suspected of causing cancer.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Dry powder
 Alcohol-resistant foam

MasterTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	03/29/2021	000000260446	Date of first issue: 08/04/2020

- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil barriers).
Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.

MasterTop SRS 41P

Version 2.0 Revision Date: 03/29/2021 SDS Number: 000000260446 Date of last issue: 08/04/2020
 Date of first issue: 08/04/2020

Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : no smoking
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep container tightly closed and in a well-ventilated place.
 Keep away from heat.
 Avoid all sources of ignition: heat, sparks, open flame.
 Contamination with other substances must be avoided.
 Keep at temperature not exceeding 25 °C.
 Keep only in the original container.

Vapours may travel along floor and ignite at a location distant from the handling point.

Materials to avoid : Segregate from incompatible substances.
 See SDS section 10 - Stability and reactivity.

Recommended storage temperature : < 25 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA value	50 ppm	ACGIHTLV
		STEL value	100 ppm	ACGIHTLV
		REL value	100 ppm 410 mg/m ³	NIOSH
		PEL	100 ppm 410 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 410 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)

MasterTop SRS 41P

Version 2.0 Revision Date: 03/29/2021 SDS Number: 000000260446 Date of last issue: 08/04/2020
 Date of first issue: 08/04/2020

		STEL	100 ppm 410 mg/m ³	CA AB OEL
		TWA	50 ppm 205 mg/m ³	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 205 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
 Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.
 Antistatic apron

Protective measures : Avoid inhalation of dusts/mists/vapours.
 Avoid contact with the skin, eyes and clothing.
 Avoid prolonged and/or repeated contact with the skin.
 Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.
 Hands and/or face should be washed before breaks and at the end of the shift.
 At the end of the shift the skin should be cleaned and skin-care agents applied.
 Gloves must be inspected regularly and prior to each use.
 Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colourless, cloudy

Odor : sweetish, ester-like

MasterTop SRS 41P

Version 2.0 Revision Date: 03/29/2021 SDS Number: 000000260446 Date of last issue: 08/04/2020
Date of first issue: 08/04/2020

Odor Threshold : No data available

pH : Not applicable

Melting point : No data available

Freezing point : No data available

Boiling point : 100 °C
(1,013 hPa)

Flash point : 10 °C

Evaporation rate : > 1

Flammability (liquids) : Highly flammable liquid and vapor.

Upper explosion limit / Upper flammability limit : 12.5 %(V)

Lower explosion limit / Lower flammability limit : 2.1 %(V)

Vapor pressure : 37.8 hPa

Relative vapor density : No data available

Relative density : No data available

Density : 0.94 g/cm³ (20 °C)

Solubility(ies)

 Water solubility : approx. 16 g/l (20 °C)

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : No data available

Decomposition temperature : Vapors may form explosive mixture with air.
No decomposition if stored and handled as prescribed/indicated.

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : No data available

Explosive properties : Not explosive

MasterTop SRS 41P

Version Revision Date: SDS Number: Date of last issue: 08/04/2020
2.0 03/29/2021 000000260446 Date of first issue: 08/04/2020

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : No hazardous reactions if stored and handled as prescribed/indicated.
Risk of dangerous polymerization in the presence of heat and/or contamination.
Heat develops during polymerization.
Vapors may form explosive mixture with air.

Conditions to avoid : Avoid all sources of ignition: heat, sparks, open flame.
Avoid contamination.
Heat, strong UV sources

Incompatible materials : Strong oxidizing agents
Reducing agents
Heavy metals
Amines
Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

MasterTop SRS 41P

Version Revision Date: SDS Number: Date of last issue: 08/04/2020
2.0 03/29/2021 000000260446 Date of first issue: 08/04/2020

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Observe national and local legal requirements.
Residues should be disposed of in the same manner as the substance/product.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : II
Labels : 3

IATA-DGR

- UN/ID No. : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

- UN number : UN 1866
Proper shipping name : RESIN SOLUTION
- Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

- UN number : UN 1866
Proper shipping name : RESIN SOLUTION
- Class : 3
Packing group : II
-

MasterTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	03/29/2021	000000260446	Date of first issue: 08/04/2020

Labels	:	3
ERG Code	:	127
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**The ingredients of this product are reported in the following inventories:**

DSL	:	All components of this product are on the Canadian DSL
TSCA	:	All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A)	:	OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	:	OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH	:	NIOSH Pocket Guide to Chemical Hazards (US)
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIHTLV / STEL value	:	Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWA EV	:	Time-weighted average exposure value
NIOSH / REL value	:	Recommended exposure limit (REL):

MasterTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	03/29/2021	000000260446	Date of first issue: 08/04/2020

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/29/2021
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN