

MasterTop TC 504 cust color PART A Bold

Version **Revision Date:** SDS Number: Date of last issue: -

02/25/2021 000000260705 Date of first issue: 02/25/2021 1.0

SECTION 1. IDENTIFICATION

Product name MasterTop TC 504 cust color PART A Bold

Product code 00000000051651244 00000000051651244

Other means of identification No data available

Manufacturer or supplier's details

Company name of supplier MBSCS Canada, Inc.

Address 7111 Syntex Drive, 3rd Floor

Mississauga ON L5N 8C3

Emergency telephone ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use Functional surface coating

Restrictions on use Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids Category 4

Skin irritation Category 2

Eye irritation Category 2A

Skin sensitization Category 1

Carcinogenicity (Inhalation) Category 1A

Reproductive toxicity Category 2

Specific target organ toxicity

- repeated exposure (Inhalation)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Short-term (acute) aquatic

hazard

Category 2

Category 1 (Lungs)

Category 2 (Kidney, Immune system)

Long-term (chronic) aquatic

hazard

Category 3

Version **Revision Date:** SDS Number: Date of last issue: -

02/25/2021 000000260705 Date of first issue: 02/25/2021 1.0

GHS label elements

Hazard pictograms





Signal Word Danger

Hazard Statements H227 Combustible liquid.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H350 May cause cancer by inhalation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.



MasterTop TC 504 cust color PART A Bold

Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Preparation based on:

polymers

inorganic compounds

Components

Chemical name	CAS-No.	Concentration (% w/w)
Reaction product: bisphenol-A- (epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)	25068-38-6	>= 20 - < 30
Limestone	1317-65-3	>= 20 - < 30
Quartz (SiO2)	14808-60-7	>= 20 - < 30
1-methoxy-2-propanol	107-98-2	>= 1 - < 5
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 1 - < 5
Iron oxide	1309-37-1	>= 1 - < 5
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	25085-99-8	>= 0.1 - < 1
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 0.1 - < 1
2-Propenoic acid, ethyl ester, polymer with 2-ethylhexyl 2-propenoate	26376-86-3	>= 0.1 - < 1
Titanium dioxide	13463-67-7	>= 0.1 - < 1
Carbon black	1333-86-4	>= 0.1 - < 1
hexane-1,6-diol diacrylate	13048-33-4	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15

to 20 minutes. Remove contact lenses, if present, after first 5



Version **Revision Date:** SDS Number: Date of last issue: -

02/25/2021 000000260705 Date of first issue: 02/25/2021 1.0

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water,

> seek medical attention. Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer by inhalation.

Suspected of damaging the unborn child. May cause damage to organs if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Treat symptomatically. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black carbon oxides

The degree of risk is governed by the burning substance and Further information

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-



Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

Large spills should be collected mechanically (remove by

pumping) for disposal.

Pick up with inert absorbent material (e.g. sand, earth etc.). Spilled product should be disposed in accordance with all

applicable government regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Product is not explosive.

Advice on safe handling : Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact. Avoid contact with eyes.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWAEV (to-	10 mg/m3	CA QC OEL



Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

		tal dust)		1
		TWA (Total	10 mg/m3	CA BC OEL
		dust)		
		TWA (respir-	3 mg/m3	CA BC OEL
		able dust fraction)		
		STEL	20 mg/m3	CA BC OEL
Quartz (SiO2)	14808-60-7	TWA value	0.025 mg/m3	ACGIHTLV
	14000 00 7	(Respirable fraction)	0.020 mg/mo	7.0011112
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
1-methoxy-2-propanol	107-98-2	TWA value	50 ppm	ACGIHTLV
		STEL value	100 ppm	ACGIHTLV
		REL value	100 ppm 360 mg/m3	NIOSH
		STEL value	150 ppm 540 mg/m3	NIOSH
		TWA value	100 ppm 360 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 540 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL	150 ppm 553 mg/m3	CA AB OEL
		TWA	100 ppm 369 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	100 ppm 369 mg/m3	CA QC OEL



MasterTop TC 504 cust color PART A Bold

Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

		STEV	150 ppm 553 mg/m3	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
Iron oxide	1309-37-1	TWA value (Respirable fraction)	5 mg/m3	ACGIHTLV
		REL value (Dust and fume)	5 mg/m3 (iron (Fe))	NIOSH
		PEL (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	CA AB OEL
		TWA (Fumes)	5 mg/m3 (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m3 (Iron)	CA BC OEL
		STEL (Fumes)	10 mg/m3 (Iron)	CA BC OEL
		TWAEV (fume and dust)	5 mg/m3 (Iron)	CA QC OEL
		TWA (Respirable particulate matter)	5 mg/m3	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified

respirators.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Tightly fitting safety goggles (chemical goggles).

Skin and body protection : Body protection must be chosen based on level of activity



MasterTop TC 504 cust color PART A Bold

Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : pigmented

Odor : aromatic, mild

pH : neutral to slightly alkaline

Melting point : No data available

Freezing point No data available

Boiling point : 163 °C

Flash point : 74 °C

Method: Standard Method of Test for Flash Point by Setaflash

Closed Tester

Evaporation rate : No applicable information available.

Flammability (liquids) : Combustible liquid.

Upper explosion limit / Upper

flammability limit

No data available.

Lower explosion limit / Lower

flammability limit

No data available.

Vapor pressure : No applicable information available.



MasterTop TC 504 cust color PART A Bold

Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 1.57 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents
Strong reducing agents

Hazardous decomposition

products

: Traces of the substances/groups of substances are released

as decomposition products of the dry substance.

carbon oxides

Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

nitrogen oxides Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.



MasterTop TC 504 cust color PART A Bold

Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Solvent naphtha (petroleum), light arom.:

Partition coefficient: n- : log Pow: 3.17

octanol/water Method: other (calculated)

GLP: no

hexane-1,6-diol diacrylate:

Partition coefficient: n- : log Pow: 2.81 (25 °C) octanol/water : Method: other (measured)

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Residues should be disposed of in the same manner as the

substance/product.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

Packs that cannot be cleaned should be disposed of in the



Version **Revision Date:** SDS Number: Date of last issue: -

02/25/2021 000000260705 Date of first issue: 02/25/2021 1.0

same manner as the contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)

Class 9 **EHSM** Subsidiary risk Packing group Ш

Labels 9 (EHSM)

IATA-DGR

UN/ID No. UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)

Class 9 Subsidiary risk **EHSM**

Packing group Ш

Labels Miscellaneous, Environmentally hazardous

Packing instruction (cargo

aircraft)

Packing instruction (passen-

964

964

ger aircraft)

IMDG-Code

UN number UN 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, Proper shipping name

N.O.S.

(BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)

Class 9 **EHSM** Subsidiary risk Packing group Ш

Labels 9 (EHSM) EmS Code F-A, S-F Marine pollutant yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



Version **Revision Date:** SDS Number: Date of last issue: -

000000260705 Date of first issue: 02/25/2021 1.0 02/25/2021

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory

DSL All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z-OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1001-1050 OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

CA AB OEL Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL Canada, British Columbia OEL

CA ON OEL Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

Short Term Exposure Limit (STEL):

CA QC OEL Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH

29 CFR 1910.1000 (Table Z-

1-A) / STEL value

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 / **OSHA** Action level:

OSHA Action level

29 CFR 1910.1001-1050 / Time Weighted Average (TWA):

TWA value

ACGIH / TWA 8-hour, time-weighted average ACGIH / STEL Short-term exposure limit

Short Term Exposure Limit (STEL): ACGIHTLV / STEL value Time Weighted Average (TWA): ACGIHTLV / TWA value 8-hour Occupational exposure limit CA AB OEL / TWA CA AB OEL / STEL 15-minute occupational exposure limit

CA BC OEL / TWA 8-hour time weighted average CA BC OEL / STEL short-term exposure limit

CA ON OEL / TWA Time-Weighted Average Limit (TWA) Time-weighted average exposure value CA QC OEL / TWAEV

Short-term exposure value CA QC OEL / STEV

NIOSH / REL value Recommended exposure limit (REL): NIOSH / STEL value Short Term Exposure Limit (STEL):



Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen. Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 02/25/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE



MasterTop TC 504 cust color PART A Bold

Version Revision Date: SDS Number: Date of last issue: -

1.0 02/25/2021 000000260705 Date of first issue: 02/25/2021

SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN