

MasterTop TC 504 light tan PART A

Version 1.0 Revision Date: 10/08/2020 SDS Number: 000000260708 Date of last issue: -
Date of first issue: 10/08/2020

SECTION 1. IDENTIFICATION

Product name : MasterTop TC 504 light tan PART A
Product code : 000000000051651138 000000000051651138
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : MBSCS Canada, Inc.
Address : 7111 Syntex Drive, 3rd Floor
Mississauga ON L5N 8C3
Emergency telephone : ChemTel: +1-813-248-0585;


Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

FLAMMABLE LIQUIDS : Category 4
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Skin sensitization : Category 1A
Short-term (acute) aquatic hazard : Category 2
Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H227 Combustible liquid.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

MasterTop TC 504 light tan PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/08/2020	000000260708	Date of first issue: 10/08/2020

H317 May cause an allergic skin reaction.
H401 Toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
bisphenol A-epichlorohydrin resin	25068-38-6	>= 25 - < 50
Quartz (SiO ₂)	14808-60-7	>= 20 - < 25
1-methoxypropan-2-ol	107-98-2	>= 3 - < 5

MasterTop TC 504 light tan PART A

Version 1.0 Revision Date: 10/08/2020 SDS Number: 000000260708 Date of last issue: -
Date of first issue: 10/08/2020

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	$\geq 0.3 - < 1$
1,6-hexanediol diacrylate	13048-33-4	$\geq 0 - < 1$
Limestone	1317-65-3	$\geq 10 - < 25$
Titanium dioxide	13463-67-7	$\geq 3 - < 7$

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
- If inhaled : Keep patient calm, remove to fresh air, seek medical attention.

If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Immediately wash thoroughly with soap and water, seek medical attention.

If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
- Notes to physician : Treat symptomatically.

MasterTop TC 504 light tan PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/08/2020	000000260708	Date of first issue: 10/08/2020

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Product is not explosive.
- Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.

MasterTop TC 504 light tan PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/08/2020	000000260708	Date of first issue: 10/08/2020

Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Conditions for safe storage : no smoking
 Keep in a well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
 Protect from direct sunlight.
- Materials to avoid : Observe VCI storage rules.
- Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-methoxypropan-2-ol	107-98-2	TWA value	50 ppm	ACGIHTLV
		STEL value	100 ppm	ACGIHTLV
		REL value	100 ppm 360 mg/m3	NIOSH
		STEL value	150 ppm 540 mg/m3	NIOSH
		TWA value	100 ppm 360 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 540 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL	150 ppm 553 mg/m3	CA AB OEL
		TWA	100 ppm 369 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL

MasterTop TC 504 light tan PART A

Version
1.0Revision Date:
10/08/2020SDS Number:
000000260708Date of last issue: -
Date of first issue: 10/08/2020

		TWAEV	100 ppm 369 mg/m ³	CA QC OEL
		STEV	150 ppm 553 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
Limestone	1317-65-3	REL value (Respirable)	5 mg/m ³	NIOSH
		REL value (Total)	10 mg/m ³	NIOSH
		PEL (Respirable fraction)	5 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m ³	CA AB OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		STEL	20 mg/m ³	CA BC OEL
Titanium dioxide	13463-67-7	TWA value	10 mg/m ³	ACGIHTLV
		PEL (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Quartz (SiO ₂)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m ³	ACGIHTLV
		TWA value (Respirable dust)	0.05 mg/m ³	29 CFR 1910.1001- 1050

MasterTop TC 504 light tan PART A

Version 1.0 Revision Date: 10/08/2020 SDS Number: 000000260708 Date of last issue: -
 Date of first issue: 10/08/2020

		OSHA Action level	0.025 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		REL value (Respirable dust)	0.05 mg/m ³	NIOSH
		TWA (Respirable particulates)	0.025 mg/m ³	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m ³	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m ³	CA QC OEL
		TWA (Respirable) (Silica)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

MasterTop TC 504 light tan PART A

Version 1.0 Revision Date: 10/08/2020 SDS Number: 000000260708 Date of last issue: -
Date of first issue: 10/08/2020

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	pigmented
Odor	:	aromatic, mild
Odor Threshold	:	No data available
pH	:	neutral to slightly alkaline
Melting point	:	No applicable information available.
Freezing point	:	No applicable information available.
Boiling point	:	163 °C
Flash point	:	74 °C
		Method: Standard Method of Test for Flash Point by Setaflash Closed Tester, closed cup
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not determined
Upper explosion limit / Upper flammability limit	:	No data available.
Lower explosion limit / Lower flammability limit	:	No data available.
Vapor pressure	:	No data available.
Relative vapor density	:	Heavier than air.
Relative density	:	1.57
Density	:	approx. 1.0 g/cm ³ (20 °C)
Bulk density	:	not applicable
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	insoluble
Partition coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	No data available

MasterTop TC 504 light tan PART A

Version 1.0 Revision Date: 10/08/2020 SDS Number: 000000260708 Date of last issue: -
Date of first issue: 10/08/2020

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
 Viscosity, dynamic : No data available.

 Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapors may form explosive mixture with air.

Conditions to avoid : Avoid all sources of ignition: heat, sparks, open flame.

Heat, flames and sparks.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : Traces of the substances/groups of substances are released as decomposition products of the dry substance.
carbon oxides
nitrogen oxides
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

MasterTop TC 504 light tan PART A

Version 1.0 Revision Date: 10/08/2020 SDS Number: 000000260708 Date of last issue: -
Date of first issue: 10/08/2020

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information**Product:**

Remarks : No data available

MasterTop TC 504 light tan PART A

Version 1.0 Revision Date: 10/08/2020 SDS Number: 000000260708 Date of last issue: -
Date of first issue: 10/08/2020

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****bisphenol A-epichlorohydrin resin:**

- Toxicity to fish : LC50 (Oryzias latipes): 1.41 mg/l
Exposure time: 96 h
Test Type: semistatic
Method: Acute toxicity testing with Fish, semistatic procedure
(Method: Japanese Industrial Standard: Testing methods for industrial wastewater)
- Toxicity to daphnia and other aquatic invertebrates : EC50 (daphnia): 1 - 10 mg/l
Remarks: Information taken from reference works and the literature.

EC50 (Daphnia magna): 12 mg/l
Exposure time: 48 h
Test Type: static
Method: Daphnia test acute
- Toxicity to algae/aquatic plants : EC50 (green algae): 9.1 mg/l
Exposure time: 96 h
Test Type: static
Method: Algal growth inhibition test
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : No observed effect concentration (Daphnia magna): 0.3 mg/l
End point: Reproduction rate
Exposure time: 21 d
Test Type: semistatic
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Test Type: aquatic
Remarks: Information taken from reference works and the literature.

Persistence and degradability**Components:****bisphenol A-epichlorohydrin resin:**

- Biodegradability : aerobic
Inoculum: Inoculum conforming to MITI requirements (OECD 301C)
Biodegradation: 0 %
Exposure time: 28 d
Method: MITI-Test (I), ready

MasterTop TC 504 light tan PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/08/2020	000000260708	Date of first issue: 10/08/2020

Bioaccumulative potential**Components:****bisphenol A-epichlorohydrin resin:**

Bioaccumulation : Remarks: Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is possible. Information taken from reference works and the literature.

Partition coefficient: n-octanol/water : log Pow: > 3

Quartz (SiO₂):

Partition coefficient: n-octanol/water : Remarks: not applicable

1-methoxypropan-2-ol:

Partition coefficient: n-octanol/water : log Pow: -0.43 (25 °C)
Method: other (measured)
GLP: no
Remarks: Information taken from reference works and the literature.

1,6-hexanediol diacrylate:

Partition coefficient: n-octanol/water : log Pow: 2.81 (25 °C)
Method: other (measured)

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

MasterTop TC 504 light tan PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/08/2020	000000260708	Date of first issue: 10/08/2020

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**The ingredients of this product are reported in the following inventories:**

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1001-1050	: OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)

MasterTop TC 504 light tan PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/08/2020	000000260708	Date of first issue: 10/08/2020

29 CFR 1910.1000 (Table Z-1-A) / STEL value : Short Term Exposure Limit (STEL):

29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit

29 CFR 1910.1001-1050 / OSHA Action level : OSHA Action level:

29 CFR 1910.1001-1050 / TWA value : Time Weighted Average (TWA):

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):

ACGIHTLV / TWA value : Time Weighted Average (TWA):

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / STEL : short-term exposure limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

NIOSH / REL value : Recommended exposure limit (REL):

NIOSH / STEL value : Short Term Exposure Limit (STEL):

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

MasterTop TC 504 light tan PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/08/2020	000000260708	Date of first issue: 10/08/2020

Revision Date : 10/08/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN