

MasterRoc® BSG 1

Main Bearing Sealing Grease (Excluder Grease) for Tunnel Boring Machines (TBM)

DESCRIPTION

MasterRoc BSG 1 is an excluder grease for tunnel boring machines. It effectively protects the main bearing and prevents soil, water or dust ingress into the main bearing sealing. It is formulated to resist high water and ground pressures, has excellent lubrication and pumping properties as well as adhesion to all surfaces. It is highly biodegradable and based on renewable raw materials.

FEATURES AND BENEFITS

- Excellent sealing and anti-washout properties
- Excellent adhesion to any metal or concrete surfaces
- Excellent pumping and lubricating properties
- 'Bio-grease': entirely based on renewable and natural raw materials

PACKAGING

MasterRoc BSG 1 is available in standard 230 kg or 60 kg steel drums for press plate pumps.

STORAGE

MasterRoc BSG 1 should be stored at 5 - 35°C. If stored in original tightly closed containers it has a shelf life of 12 months.

TECHNICAL DATA*

Form	Homogenous paste,
	fibrous
Color	Black
Odor	None
Density [kg/m3] 20°C	1200 ± 50
Consistency ISO 2137 [1/10 mm]	250- 280
4-ball wear DIN 51350:5 [mm]	< 0.9
Water wash out (38°C) ISO 11009 [%]	< 5
Water spray off (38°C) ASTM D4049 [%]	< 7
Water resistance DIN 51807/1	0
Sealing elastomer compatibility	Approved by Merkel & J. Walker
Flash point (base oil)	> 285°C
Biodegradation (base oil) CEC-L-33-A-93	> 90%

The recommended minimum service temperature is +10°C.

SAFETY PRECAUTIONS

MasterRoc BSG 1 is not hazardous. It is ecologically and environmentally friendly and poses no threat to worker safety or the environment. However, it is recommended that all normal precautions be taken when handling the product, such as the use of eye protection and gloves.

* Properties listed are based on laboratory controlled tests.

Registered trademark of a MBCC Group member in many countries of the world

Master_Builders_Solutions_CC-UAE/Roc_BSG1/v1/10_13

STATEMENT OF RESPONSIBILITY	The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.
NOTE	Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions Construction Chemicals UAE LLCP.O. Box 37127, Dubai, UAETel: +971 4 8090800Fax: +971 4 8851002





A brand of

MBCC GROUP