

MasterSeal® 754

Pre-applied FPO waterproofing membrane for below ground concrete structures

DESCRIPTION

MasterSeal 754 is a pre-applied sheet membrane waterproofing system consisting of highly flexible polyolefin membrane and a designed non-woven fleece. This unique system provides a durable mechanical bond, which is created when the fleece is completely adhered to the fresh concrete. **MasterSeal 754** is cold-applied and pre-applied, as it is installed without heat or open flames and before the steel reinforcement is placed and the concrete is poured.

FIELDS OF APPLICATIONS

- Below grade concrete slabs
- Below grade walls with both single (blindsided forming) and double-faced formwork (open cut)
- For prefabricated construction
- Residential and industrial buildings such as housing, commercial, leisure facilities, manufacturing plants and warehouses
- Engineered structures, such as retaining walls, tunnel galleries, potable water tanks, waste water storage treatment structures and tanks

FEATURES & BENEFITS

- No need for protection screed.
- Provides time and labor saving.
- Fast installation: layout, jointing and detailing.
- Weather resistant with temporary UV-stability during installation.
- No lateral water migration in the event of damage.
- Resistant to aggressive mediums in soil.
- Crack bridging ability.
- Overlapping areas are self-adhesive. No need for any extra tape to overlap.

- High elasticity at low temperatures.
- It is resistant to 5 bar water pressure.
- High mechanical impact resistance.

PACKAGING AND ROLL SIZES

MasterSeal 754 is supplied as 1.6mm thick, width of 1.0 meters and length of 20 meters.

COLOUR

Grey membrane / Black fleece

APPLICATION PROCEDURE

Synthetic waterproofing membranes applications should be done by approved applicators. For the further information please apply application manual.

Note: MasterSeal 754 does not have UV resistance. The membrane can be exposed during the application of 3 months.

COVERAGE

In order to calculate total consumption of synthetic waterproofing membranes, it must be added quantity of 10% overlapping and 2-3% of loss depending upon the project conditions on the total application area.

STORAGE & SHELF LIFE

MasterSeal 754 membrane rolls have a shelf-life of 12 months from date of production if stored properly in unopened, undamaged, original packaging, in a horizontal position, in dry conditions and at temperatures between +5°C and +30°C.

MasterSeal[®] 754

PHYSICAL / CHEMICAL PROPERTIES*

Material composition	Membrane: FPO - flexible polyolefin Upper bonding layer: Polypropylene needle-punch non-woven Self-adhesive strip: Butyl rubber, high elastic, resistant to ageing and release liner	
Physical properties	Value	Tolerance
Total weight	850g/m ²	±75g/m ²
Resistance to temperature	-30°C to 60°C	
Tear resistance (length-wise) DIN EN 12311-2 Method A	400N/50mm	≥300N/50mm
Tear resistance (across) DIN EN 12311-2 Method A	340N/50mm	≥250N/50mm
Elongation at break longitudinal DIN EN 12311-2 Method A	90%	≥75%
Elongation at break lateral DIN EN 12311-2 Method A	120%	≥85%
Tear resistance (nail shank) DIN EN 12310-1	370N	≥300N
Tear resistance (nail shank) DIN EN 12310-1	380N	≥300N
Water vapour permeability DIN EN 1931 Method B	60m	≥40m
Water tightness DIN EN 1928-A - 60kPa/24 Std.	watertight	
Water tightness DIN EN 1928-A - 400kPa/72 Std.	watertight	
Water migration test (non-woven area)	max 5 bar	
Reaction to fire DIN ISO 11925-2, EN 13501-1	Class E	
Chemical resistance	Resistant to a wide range of chemicals	
Approval	CE Marking according to DIN EN 13967 – Certificate No. 0761-CPR-0514	

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Master Builders Solutions representative.

Master Builders Solutions reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from Master Builders Solutions's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001:2015, ISO 14001:2015 & OHSAS 18001:2007 standards.

* Properties listed are based on laboratory controlled tests.

® Registered trademark of a MBCC Group member in many countries of the world

Master_Builders_Solutions_CC-UAE/SI_754_04_17/v1/

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions
Construction Chemicals UAE LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800, Fax: +971 4 8851002
www.master-builders-solutions.ae

Disclaimer: the LRQA mark relates to certified management system and not to the product mentioned on this datasheet

