

MasterTile® 530

Coloured, latex modified grout for ceramic tiles

DESCRIPTION

MasterTile 530 is a fine coloured powder which, when mixed with water, gives a smooth, easily applied creamy paste for clean grouting of ceramic tiles. It sets to a decorative water resistant finish.

ADVANTAGES

- Water-resistant (suitable for swimming pools).
- Available in a range of colours.
- Resistant to cracking in joints up to 4mm wide.
- Ideal for internal and exterior applications.
- Formulated for Middle East conditions.

PACKAGING

MasterTile 530 is available in 15kg sacks.

COMPOSITION

MasterTile 530 is a blend of hydrophobic cement, fillers and organic additives.

STANDARDS

BS 5980 - Cementitious Adhesives and Grouts ANSI 118.7 (Polymer Modified Cement Grouts)

APPLICATION PROCEDURES

Allow at least 24 hours between fixing tiles and grouting. Mix grout powder with water to give a smooth, thick consistency.

Gauging water for 15 kg sack is approx. 3.9 - 4.3 ltr.

Leave to stand for 15 minutes before using. Apply to tile joints with a squeegee, brush or sponge. Remove surplus grout with a damp sponge. When grouting is completed, polish tiles with a dry cloth.

WATCHPOINTS

Certain types of tile may stain when in contact with coloured cement grouts, it is therefore advisable to consult the tile manufacturer and carry out trials before use.

COVERAGE

1 kg is sufficient for approximately 4 square metres using standard 150 x 150mm tiles.

STORAGE

Store out of direct sunlight, clear of the ground on pallets protected from rainfall. Avoid excessive compaction.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which may also be tainted with vapour until product is fully cured). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Reseal containers after use.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Master Builders Solutions representative. Master Builders Solutions reserves the right to have the true cause of any difficulty determined by accepted test methods.

MasterTile® 530

QUALITY AND CARE

All products manufactured by Master Builders Solutions Egypt, or imported from Master Builders Solutions affiliate companies world- wide, are manufactured to procedures certified to conform to the quality, environment, health & safety management systems described in the ISO 9001:2015, ISO 14001:2015 & OHSAS 18001:2007 standards.

* Properties listed are based on laboratory controlled tests.

® Registered trademark of a MBCC Group member in many countries of the world

Master_Builders_Solutions_CC-EG/Tile_530_09_12/v1/05_14

MBS Construction Chemicals Egypt (S.A.E), Business Park A, Building A1, Cairo Festival City, Ring Road, New Cairo, Egypt

Hotline: 15560, Phone: +202 2128 7800, Fax: +202 2128 7801

Website: <https://www.master-builders-solutions.com/en-eg>



15560