

DECLARATION OF PERFORMANCE

Reference Number: No. 01110369

For the product: **Ucrete IF** consisting of:

A primer layer of:- Ucrete PSC, Ucrete PFS, Ucrete PLC, Ucrete BC4, Ucrete BC6, Ucrete FL, Ucrete MF, or NONE.

A topcoat layer of:- Ucrete IF

As described in the relevant technical data sheets and when installed according to the manufacturer's instructions.

1. Unique identification code of the product type(s):

BS EN 13813 SR

2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):

Batch number: See product packaging

3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:

Synthetic resin screed material

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

Master Builders Solutions UK Ltd 19 Broad Ground Road Redditch B98 8YP United Kingdom

5. When applicable, the name and contact address of the authorised representative who has received a mandate for the tasks set out in Article 12 (2):

Not applicable





DECLARATION OF PERFORMANCE

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

System 4

System 3 for fire behaviour

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard:

The notified body, Exova Warringtonfire, UK, Identification Number 0833, performed the reaction to fire (EN 13501-1) according to System 3 and reported the following:

Classification Report No. 393374

8. In the case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued:

Not Relevant

9. Declared Performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Fire classification	B _{FL} – S ₁	EN 13813: 2002
Release of corrosive substances	NPD	EN 13813: 2002
Water permeability	NPD	EN 13813: 2002
Mechanical Resistance	NPD	EN 13813: 2002
Wear resistance	AR 0,5	EN 13813: 2002
Bond strength	B > 2,0	EN 13813: 2002
Impact resistance	IR >4	EN 13813: 2002
Subsonic noise insulation	NPD	EN 13813: 2002
Acoustical absorption	NPD	EN 13813: 2002
Heat insulation	NPD	EN 13813: 2002
Chemical resistance	NPD	EN 13813: 2002
Electrical resistance	NPD	EN 13813: 2002

NPD: No Performance Determined





2.DBentu

DECLARATION OF PERFORMANCE

When specific technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

Not applicable

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Prepared on behalf of Master Builders Solutions UK Ltd:

Name: David Bell Position: QC Manager

Place and date: Redditch, 12th February 2021 Signature:

Signed for and on behalf of Master Builders Solutions UK Ltd:

Name: Robert Bentley Position: Marketing Manager Europe, Ucrete

Place and

date:

Redditch, 12th February 2021

Signature:



