

MasterTop[®] XTC

High Performance, Odorless Self-smoothing flooring system based on Xolutec technology

DESCRIPTION

MasterTop XTC a high performance, odorless, self-smoothing & long-lasting flooring system based on Xolutec technology. It provides a seamless surface with exceptional resistance to abrasion & impact and easy to clean. Being moisture tolerant the system can be applied on 10-day old concrete floors.

Xolutec[™]

A new dimension in versatility & durability

Xolutec is an innovative and smart way of combining complementary chemistries to solve the problems of challenging technical environments with a cross-linked interpenetrating network (XIPN).

By controlling the chemistry of the polymer chains and cross-linking density, the properties of **Xolutec** can be adjusted to meet the required product performance, such as different degrees of toughness and flexibility.

Xolutec is very low in volatile organic components (VOC), is quick and easy to apply. It cures fast even at low temperature, insensitive to moisture and tolerates a wide variety of different site conditions.

RECOMMENDED USES

MasterTop XTC is recommended for new floors & floors needing refurbishment, where protection from mechanical abuse & aggressive chemical attack is required.

MasterTop XTC is used to provide a hard wearing, abrasion resistant and easy to clean surface.

Application areas include:

- Automotive Production and assembly lines
- Pharmaceutical Plants
- Heavy Engineering workshops
- Aircraft Maintenance and assembly
- Industrial & Warehousing floors
- Laboratories

FEATURES AND BENEFITS

- **Odorless** – Environment friendly & comfortable application
- **Scratch resistance** – Longer retention of surface appearance.

- **Fast curing at low temperature** – Reduced waiting times even at low temperatures
- **Impact Resistance** – Longer life even under aggressive mechanical abuse
- **High Early Strength** – Fast return to service; Open to Light vehicular traffic in 24 hrs.
- **Moisture Tolerant** – Faster application; Can be applied on 10-day old concrete
- **Chemical resistance** – Unaffected by chemical spillages

SYSTEM BUILD UP

MasterTop XTC is composed of

1. **Scratch coat – MasterTop BC 920** – a 4 component, odorless flooring system based on Xolutec Technology
2. **Bodycoat – MasterTop BC 920** a 4 component, odorless flooring system based on Xolutec Technology

Layer	Product	Consumption* (Kgs /m ²)
Scratch coat	MasterTop BC 920	0.7 – 0.9
Body Coat	MasterTop BC 920	2.3 – 2.5

* The total consumption of material including the scratch coat shall be a minimum of 3.0Kgs /m².

- Total thickness approx. 2.0mm minimum
- Consumption figures are a guide only and may be higher in rough or porous substrates.


APPLICATION

For detailed, product specific application instructions, see individual product technical data sheets.

PRECAUTIONS

For the full health and safety hazard information and how to safely handle and use this product, please make sure that you obtain a copy of the Master Builders Solutions Material Safety Data Sheet (MSDS) from our office or our website.

MasterTop[®] XTC



			Consumption (Kgs /m ²)
■	Concrete Substrate		
■	Scratch Coat	MasterTop BC 920 4 Component Self Smoothing Flooring System based on Xolutec Technology	0.7 – 0.9
■	Bodycoat	MasterTop BC 920 4 Component Self Smoothing Flooring System based on Xolutec Technology	2.3 – 2.5
Total Thickness of System			Minimum 2mm

® = registered trademark of MBCC Group member in many countries of the world

MAP#MasterTop XTC v3. 12.2020

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

MB Solutions Singapore Pte Ltd
 1 Harbourfront Avenue #07-07/08
 Keppel Bay Tower, Singapore 098632
 Tel : +65 6232 4888