

Ucrete® MFAS

Anti-Static, Heavy Duty Polyurethane finish

DESCRIPTION

Ucrete MF AS is a unique HD Polyurethane resin floor which provides a smooth protective antistatic floor finish suitable for applications in predominantly dry environments.

Ucrete MFAS is used in the electronics industry to protect sensitive electronic devices and in explosion hazarded areas.

It is dense and impervious, providing the ideal floor finish for applications in the electronics, food, pharmaceutical and manufacturing industries including clean room, laboratory, packing hall and warehouse applications and wherever a robust, long lived floor is required.

Ucrete Industrial Flooring has been widely used through-out industry for more than 40 years; many of the older floors are still in service. A detailed project reference list is available upon request.

Ucrete MF AS meets the antistatic flooring specifications DIN 51953, BS 2050 (explosive handling areas) and obtain ESD approval according to IEC 61340.

RECOMMENDED USES

Ucrete MF AS is recommended for conditions requiring maximum chemical resistance in an antistatic environment.

Specific applications include:

- Electronics and component assembly
- Clean rooms
- Pharmaceutical production
- Explosive and ammunition storage & handling
- Textile and fibre production
- Chemical plants

FEATURES AND BENEFITS

- **Expert Application-** Installed only by trained and approved specialist contractors.
- **Fast application-** Can be applied to 5-day-old concrete/2 day old polymer screed.
- **Short curing time** - 8 hour access to foot traffic; 20 hours for vehicles.
- **Hygienic/safe-** Slip resistant; non-tainting; non-dusting; monolithic (minimum joints); easy to maintain; microbiologically inert.
- **Durable / long life-** Wide chemical resistance; wear and impact resistant; resists temperature from -20°C to 80°C at 6 mm thickness.

- **Prepacked-** Pre-weighed / prepacked for immediate use; batch-to-batch colour matched for consistency.

ACCREDITATION

- Ucrete flooring systems are accredited for use in facilities operating HACCP based food safety systems.
- Ucrete has been awarded the Indoor **Air Comfort Gold Label** following extensive VOC emission chamber testing and auditing of quality management and production control procedures.
- All Ucrete grades give very low emissions and conform to all the emissions requirements for indoor flooring systems in Europe including **AgBB in Germany**, rated **A+** for VOC emissions from **Afset in France** and **M1 in Finland**.
- **Ucrete MF AS** is non tainting from the end of mixing, as tested by the Campden Technology Ltd

PERFORMANCE DATA

Density (Kg/m ³) (BS6319:Part 5)	1,970
Compressive Strength (MPa) (BS6319:Part 2)	48-53
Tensile Strength (MPa) (ISO R527)	9
Flexural Strength (MPa) (ISO 178)	21
Compressive Modulus (MPa) (BS 6319 – Part 6)	3250 – 4000
Concrete Adhesion(EN 13892 - 8)	Concrete Failure
Coeff. Thermal Expansion (°C ⁻¹) (ASTM C531:Part 4.05)	3.6x10 ⁻⁵
Thermal Conductivity (BS8740)	0.9 W/m°C
Water absorption (CP:BM 2/67/2)	0 mL
Fire Resistance (EN 13501: Part 1)	B _{FL} – S ₁
Sensory evaluation (C & CFRA method TES-S-002)	No taint
Resistance to earth (Ω)	
EN 61340-4-1	< 10 ⁶
EN 1081	< 10 ⁶
Resistance of man to earth (MΩ) (EN 61340-4-5)	<35

Ucrete[®] MFAS

Body voltage generation (V)	<100
VOC content: (HK prod code P10-05)	10 g/L
Slip Resistance	
EN 13036 (4S Rubber)	35
DIN 51130	R10
Service temperature	
4 mm	-15°C to 70°C
6 mm	-15°C to 80°C
<i>Samples cured for 28 days at 20°C. The performance data is typical and based upon controlled laboratory conditions. Actual performance on the job site may vary from these values based on actual site conditions.</i>	

UV Resistance

The **Ucrete** resin systems have been formulated to provide the very highest chemical and heat resistance. UV exposure though not affecting the performance of the **Ucrete** will result in yellowing of the floor which is most apparent in light colors.

Impact Resistance

With high mechanical strengths and a low elastic modulus, **Ucrete MFAS** is very resilient and able to withstand severe impact loads. While no material is indestructible and sur-face chipping may occur, brittle modes of failure resulting in cracking and debonding are unknown with Ucrete floors.

Chemical Resistance

Ucrete MF AS offers exceptional resistance to a wide range of chemical aggressors. For example, Ucrete is resistant to spillages of the following commonly encountered classes of chemicals:

- Most dilute and concentrated organic acids such as, Acetic Acid, Lactic Acid, Oleic Acid and Citric Acid as commonly found in the food industry,
- Dilute and concentrated acids: hydrochloric, nitric, phosphoric and Sulphuric.
- Dilute and concentrated alkalis, including sodium hydroxide to 50% concentration.
- Animal fats and vegetable oils, sugars flavorings and essences.
- Mineral oils, kerosene, gasoline and brake fluids
- A wide range of organic solvents including Methanol, Xylene Ethers and Chlorinated solvents

Note: some staining or discoloration may occur with some chemicals, depending upon the nature of the spillage and the standards of housekeeping employed.

Extensive chemical resistance tables are available in the separate data sheet 'A guide to the chemical resistance of Ucrete Flooring'.

For detailed information, please contact your local Master Builders Solutions office for guidance.

COLORS

Ucrete MF AS is available in Grey, Green, Cream, Yellow, Orange, Red, Blue, Light grey & Light green colors.

APPLICATION

Substrate Quality

Concrete substrates should be visibly dry and have a minimum tensile strength of 1.5 MPa. Refer to the guide 'The Design & Preparation of substrates for Ucrete Industrial Flooring'.

All joints in the substrate concrete subject to movement should be reflected through the Ucrete floor and sealed with a suitable sealant.

For information about application, please obtain a copy of the Master Builders Solutions "Application Guide for **Ucrete[®]**" from your local representative.

ESTIMATING DATA

Ucrete MF AS should be installed as per the consumption rates given below:

Thickness	Consumption
4mm	8 - 10 Kgs/m ²
6mm	12 - 14 Kgs/m ²

PACKAGING

Ucrete MF AS is supplied as a unit for immediate use, consisting of:

Ucrete MF AS Part 1	2.52kg
Ucrete MF AS Part 2	2.86kg
Ucrete MF AS Part 3	11.00kg
Ucrete Liquid Polykit Pigment	0.5Kg

PRECAUTIONS

For the full health and safety hazard information and how to safely handle and use this product, please make sure that you obtain a copy of the Master Builders Solutions Material Safety Data Sheet (MSDS) from our office or our website.

Ucrete[®] MFAS

® = registered trademark of MBCC Group member in many countries of the world

MAP#Ucrete MFAS v3. 12.2020

**STATEMENT OF
RESPONSIBILITY**

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability, or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

PT Master Builders Solutions Indonesia
Jl. Jababeka V Blok I/1
Cikarang Industrial Estate, Bekasi 17530,Indonesia
Tel : +62 21 893 4339