

MasterSeal[®] 936

Double-sided sticky tape for MasterSeal 730PA/730UVS/731 HDPE pre-applied waterproofing system

DESCRIPTION

MasterSeal 936 is a white or light yellow double sided sticky, HDPE self-adhesive tape.

It is designed for use in underground waterproofing termination detailing along with **MasterSeal 730PA/730UVS/731** membrane system.

The specially-made high density thermoplastic polyethylene (HDPE) film works as a waterproof base material. On both sides the HDPE film is covered with macromolecule self-adhesive film and on the exposed surface the composite adhesive. The weather-resistant protective and insulating layer, belongs to macromolecule self-adhesive film.

TYPICAL APPLICATIONS

MasterSeal 936 is used for end lap treatment as part of the **MasterSeal 730PA/730UVS/731** membrane system.

MasterSeal 936 is applied to waterproofing and damp-proofing engineering's for various underground building structures and basements.

PACKAGING

MasterSeal 936 is supplied as:
 80mm x 50m x 0.3mm thickness double side sticky tape.

STANDARDS

National standard GB 27789-2011

TYPICAL PROPERTIES*

| | |
|-----------------------------|-----------------|
| Low temperature flexibility | -25°C, No crack |
| Peel strength to concrete | 1.0 N/mm |
| Shear strength GB/T 328.23 | 5 N/mm |

APPLICATION GUIDELINES

MasterSeal 936 is part of the **MasterSeal 730PA/730UVS/731** system, please refer to the relevant method statement or contact your local Master Builders Solutions Technical Services department.

STORAGE AND SHELF LIFE

MasterSeal 936 has a shelf-life of 12 months from date of production if stored properly in unopened, undamaged, original packaging in dry conditions and at temperatures between +5°C and +30°C.

* Properties listed are based on laboratory controlled tests.

MasterSeal[®] 936

© = registered trademark of a MBCC Group member in many countries of the world

MasterSeal 936 /Sept 2023

**STATEMENT OF
RESPONSIBILITY
(Disclaimer)**

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions India Private Limited
Registered office: Plot No D-126,
TTC Industrial Area, MIDC,
Shiravane, Navi Mumbai - 400706,
Maharashtra, India
Tel: +91 8657906776
E-mail: Construction-india@mbcc-group.com
www.master-builders-solutions.com/en-in

