

Belgian Lace Finish

An acrylic polymer finish coat

DESCRIPTION

Factory-mixed, 100% acrylic polymer finish coat with advanced technology to improve long-term performance and dirt pick-up resistance. **Belgian Lace Finish** has a fine “worm-hole” appearance which is achieved by the random aggregate sizes in the finish. The small “worm-hole” look can be circular, random vertical or horizontal.



PRIMARY USES

- Provides an aesthetically pleasing surface colour and texture for the Exterior Insulation and Finish System.
- Can also be utilized as a textured coating for poured concrete or unit masonry, conventional; stucco, **Classic PB System**, **Secondary Weather Barrier System**, certain insulating concrete forms, and veneer plaster or gypsum wallboard (interior applications only).

ADVANTAGES

- 100% acrylic polymer chemistry - long-term durability and weather resistance
- Integral colour - reduced maintenance and recoating
- Weather resistant - repels water and resists wind-driven rain
- Protects - seals existing, non-moving hairline cracks
- Breathable - doesn't blister, peel or flake

PACKAGING AND COLORS

Belgian Lace Finish is supplied in 25 kg units and available in a wide variety of standard and custom colours.

APPLICATION GUIDELINES

MIXING

- Thoroughly mix the factory-prepared **Belgian Lace Finish** with a mixer until thoroughly blended.
- A small amount of clean, potable water may be added to adjust workability.
- Additives are not permitted.
- Close container when not in use.
- Clean tools with soap and water immediately after use.

PLACING / APPLICATION

- Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m.
- Apply **Belgian Lace Finish** directly to the **Tinted Primer** with a clean, stainless steel trowel.
Note: In order to minimize the possibility of **Alpha Dry Base Coat** read-through in **Belgian Lace Finish**, we recommend the use of **Tinted Primer**.
- Apply and level **Belgian Lace Finish** during the same operation to minimum obtainable thickness consistent with uniform coverage.
- Maintain a wet edge on **Belgian Lace Finish** by applying and texturing continually over the wall surface.
- Work **Belgian Lace Finish** to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area.
- Float **Belgian Lace Finish** to achieve final texture

A brand of

Belgian Lace Finish

Note: Minor colour deviations caused by the use of natural stone granular material are possible in different batches. Therefore, only use material from the same batch number for continuous surfaces. Mix the last few pails from one batch with a different batch to minimise any colour differences.

COVERAGE / YIELD

Approximately 11.6 m²/25 kg

WATCHPOINTS

- Protect products during transportation and installation to avoid physical damage.
- Do not apply in ambient temperatures below 4°C. Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C prevail.
- Do not apply to frozen surfaces.
- Samples of **Belgian Lace Finish** are available for colour approval only. Samples for job approval must be made in the field by the applicator and approved prior to ordering.

STORAGE AND SHELF LIFE

Store in a cool, dry place protected from freezing. Store at no less than 4°C. Protect from extreme heat and direct sunlight. Shelf life is 12 months when unopened and stored as directed.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes mouth, skin and foodstuffs. If accidentally ingested, seek immediate medical attention. Reseal containers after use. For further information, refer to material safety data sheet.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries

MBS_CC-UAE/Snf_BelgLace_14_08/v4/10_17/v5/07_20

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions
Construction Chemicals LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800
www.master-builders-solutions.com/en-ae

Disclaimer: the TUV mark relates to certified management system and not to the product mentioned on this datasheet



A brand of
**MASTER®
BUILDERS
SOLUTIONS**