

Corner Bead Alu with Mesh

Aluminium corner bead with mesh for Senerflex Wall Systems

DESCRIPTION

Corner bead is made up of a perforated aluminium angle (round, oval or triangular hole), which is impact-resistant and break-proof. The fibre glass reinforcement which is adhered to the aluminium angle is alkali-proof and dislocation resistant.

PRIMARY USES

- Protection of Exterior Insulation and Finish System at edges and openings.
- Reinforcement of vulnerable corners.

ADVANTANGES

- Provides straight edges
- Saves application time and labour

PACKAGING

Length of profiles	2500mm
Leg width of the mesh	100 x 150mm
Packing unit	100 pieces / box
Packing content	250m / box

APPLICATION GUIDELINES

- 1. The Corner Bead Alu with Mesh should be fixed onto the substrate using Alpha Dry Base Coat.
- 2. The bead should be laid into a fresh applied layer of Alpha Dry Base Coat.
- 3. The Corner Bead Alu with Mesh must be overlapped at the ends to prevent cracking.
- 4. Aluminium angles must be butt joined.

STORAGE AND SHELF LIFE

Store in a cool, dry place, ensuring horizontal transporting and stocking.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/Corner_Bead_07_09/v1/12_13

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its RESPONSIBILITY accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

STATEMENT OF

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions **Construction Chemicals LLC** P.O. Box 37127, Dubai, UAE Tel: +971 4 8090800 www.master-builders-solutions.com/en-ae Disclaimer: the TUV mark relates to certified management system and not to the product mentioned on this datasheet



