

MasterGlenium® ACE 3735W

A latest generation high-performance polycarboxylate ether (PCE) superplasticizer for the Precast/Readymix industry. Essential component of ZERO ENERGY SYSTEM

DESCRIPTION

MasterGlenium ACE 3735W (Admixture Controlled Energy) consists of an innovative patented latest generation modified polycarboxylate ether polymer. The particular molecular configuration allows **MasterGlenium ACE 3735W** to firstly give workability retention and then to accelerate cement hydration. As a result, it is possible to obtain earlier development of the heat of hydration, rapid development of the hydration products and, as a consequence, higher strengths at very early age. The polymer structure of **MasterGlenium ACE 3735W** is specially designed to improve rheology of concrete, making it flowable and less viscous even at very low water/cement ratios. Robustness is a distinctive feature of concrete produced with **MasterGlenium ACE 3735W**.

TYPICAL APPLICATIONS

MasterGlenium ACE 3735W is suitable for making precast concrete elements with highly-fluid concrete without segregation at low water cement ratios with consequently high early and ultimate strengths. **MasterGlenium ACE 3735W** may be used in combination with **MasterMatrix** for producing advanced Self Compacting Concrete (SCC) or Smart Dynamic Concrete (SDC) without the aid of vibration, for economic, ecological and ergonomic precast production.

ADVANTAGES

MasterGlenium ACE 3735W offer the following benefits for the precast/readymix concrete industry:

- Production of highly flowable, robust self-compacting concrete having a low water cement ratio along with an optimal rheology
- Enhanced workability retention and improved consistency of concrete quality with low stickiness
- Environmentally friendly, CO₂ reduced mix design optimization
- Elimination or reduction of heat curing

- Improved surface appearance
- Durable precast concrete elements as per EN 206-1
- Elimination of the energy required for placing, compaction and curing
- Optimization of the curing cycles by reducing curing time or curing temperature
- Increased productivity

PACKAGING

MasterGlenium ACE 3735W is available in bulk or drums.

STANDARDS

MasterGlenium ACE 3735W meets the requirements of EN 934-2 & ASTM C494 Type F.

TYPICAL PROPERTIES*

Appearance and Form	Whitish to light, medium brown colored liquid
Specific gravity @ 25°C	1.090
pH value @ 25°C	4.0 - 7.0
Chloride ion content	"Chloride Free" to EN 934

APPLICATION GUIDELINES

MasterGlenium ACE 3735W is a ready to use liquid admixture that is added to the concrete at the time of batching.

The maximum effect is achieved when the **MasterGlenium ACE 3735W** is added after the addition of 70% of the water. **MasterGlenium ACE 3735W** must not be added to the dry materials.

Thorough mixing is essential and a minimum mixing cycle, after the addition of the **MasterGlenium 3735W**, of 60 seconds for forced action mixers is recommended.

MasterGlenium® ACE 3735W

The recommended dosage rate is 0.5 to 2.0 L/100kg of cementitious material. Other dosages may be used in special cases according to specific production conditions. In this case please consult our Technical Services Department.

MIXING

MasterGlenium ACE 3735W is compatible and recommended for use with:

- **MasterMatrix** to modify the viscosity of SCC.
- **MasterAir**, air entraining admixture to improve freeze-thaw resistance.
- **MasterFinish**, demoulding agent for easy formwork removal and improved finish.
- **MasterKure**, user friendly curing compound for highly efficient water retention.

MasterGlenium ACE 3735W is suitable for mixes containing all types of Portland cement and cementitious materials as follows:

- Microsilica
- Fly ash (PFA)
- Ground granulated blastfurnace slag GGBS

Note: **MasterGlenium ACE 3735W** is not compatible with **MasterRheobuild** superplasticizers.

STORAGE AND SHELF LIFE

MasterGlenium ACE 3735W should be stored above 0°C in closed containers or storage tanks to protect from evaporation.

The shelf life is 12 months when stored as above.

The occurrence of a surface layer with **MasterGlenium ACE 3735W** is normal and will have no effect on the performance of the product.

HEALTH AND SAFETY

MasterGlenium ACE 3735W contains no hazardous substances requiring labelling. For further information refer to the Material Safety Data Sheet.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions
Construction Chemicals LLC
 P.O. Box 37127, Dubai, UAE
 Tel: +971 4 8090800
www.master-builders-solutions.com/en-ae

Disclaimer: the TUV mark relates to certified management system and not to the product mentioned on this datasheet



A brand of
MBCC GROUP

MBS_CC-UAE/GI_ACE3735W_07_17/v1/01_23