

MasterGlenium[®] SKY 504W

New polycarboxylic ether superplasticizer for the production of high-quality ready-mix concrete with low water cement ratio and exceptional workability.

DESCRIPTION

MasterGlenium SKY 504W is an innovative second-generation superplasticizer based on polycarboxylic ether (PCE) polymers. It is derived directly from the Total Performance Control[™] concept. MasterGlenium SKY 504W is specially engineered for ready-mix concrete. Its particular configuration allows its delayed adsorption onto the cement particles and disperses them efficiently. As compared with other PCE superplasticizers, it is possible to obtain a high-quality concrete mix with accelerated strength development and extended workability without delayed setting characteristics.

The Total Performance Control[™] concept ensures that ready-mix producers, contractors and engineers get a concrete that is of the same high quality as originally specified; starting from production at the batching plant, to the delivery and application into place, and followed by its hardening process. Utilizing Smart Dynamic Concrete (SDC) concrete technology it provides a exceptional concrete mix with placing characteristics and accelerated cement hydration for early strength development and high-quality concrete.

MasterGlenium SKY 504W may be used in combination with **MasterMatrix** for producing Smart Dynamic Concrete (SDC). The technology produces advanced self-compacting concrete, without the aid of vibration. For economic, ecological and ergonomic ready-mix / precast concrete production.

TYPICAL APPLICATIONS

MasterGlenium SKY 504W is used for the production of high-quality ready-mix concrete.

MasterGlenium SKY 504W may be used in combination with **MasterMatrix** admixtures for producing Smart Dynamic Concrete, capable of self-compaction, even in the presence of dense reinforcement.

ADVANTAGES

MasterGlenium SKY 504W offers the following benefits for:

The ready-mix producer:

- Capability of delivering high performance concrete at any time to the job site in place
- Production of a concrete with low water cement ratios without loss of workability
- Single product for many application needs

The contractor / applicator:

- Easier placing and faster strength development
- Improved concrete surfaces
- Guarantee to place the same concrete as specified and ordered from ready-mix plant

The engineer:

- Insurance that concrete meets original specification
- High quality durable concrete

PACKAGING

MasterGlenium Sky 504W is supplied in 210 L drums, 1,000 L containers or in bulk.

STANDARDS

ASTM C-494 Type F&G ASTM C-1017 Type I & II EN-934-2

TYPICAL PROPERTIES*

Appearance	Medium to dark brown
Specific gravity @ 25°C	1.110
pH value	4.0 - 7.0
Chloride ion content	0.01%



MasterGlenium[®] SKY 504W

APPLICATION GUIDELINES

The normally recommended dosage rate of MasterGlenium SKY 504W is 0.8 - 1.5 L/100kg of total cementitious material.

Other dosages may be recommended in special cases according to the specific site conditions. In this case please consult our Technical Services Department for advice.

MIXING

MasterGlenium SKY 504W is a ready-to-use admixture to be added to the concrete as a separate component. Optimal result is obtained if MasterGlenium SKY 504W is poured into the concrete mix right after the addition of the first 80% of the mixing water, i.e. when all solids are wetted. Avoid adding the admixture to the dry aggregates.

MasterGlenium SKY 504W is not compatible with MasterRheobuild superplasticizers.

In order to optimize special requirements, the use of the following complementary additives is suggested:

- Viscosity modifying agent MasterMatrix to produce Smart Dynamic Concrete.
- Air entraining agent MasterAir to improve frost/thaw resistance

STORAGE AND SHELF LIFE

MasterGlenium SKY 504W should be stored out of direct sunlight and protected from extremes of temperature. The shelf life is 12 months when stored as above.

The occurrence of a surface layer with

MasterGlenium SKY 504W is normal and will have no effect on the performance of the product.

HEALTH AND SAFETY

No special requirements must be observed during use. Protection gloves and glasses are recommended. MasterGlenium SKY 504W is non-flammable, non-toxic or irritant and is not subject to special transport requirements.

MasterGlenium SKY 504W contains no hazardous substances requiring labelling. For further information refer to the Material Safety Data Sheet.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the guality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/GI_SKY504W_11_05/v1/12_13/v2/08_19/v3/01_23

SUD

STATEMENT OF

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user RESPONSIBILITY is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions **Construction Chemicals LLC** P.O. Box 37127, Dubai, UAE Tel: +971 4 8090800 www.master-builders-solutions.com/en-ae

Disclaimer: the TUV mark relates to certified management system and not to the product mentioned on this datasheet





