

MasterProtect[®] 1860TIX

Single component, thixotropic putty for repair of blow holes and minor surface imperfections

DESCRIPTION

MasterProtect 1860TIX is a single component thixotropic putty for the filling of minor blow holes and surface imperfections in concrete surfaces that are to receive **MasterProtect 1860** as a final finish.

MasterProtect 1860TIX requires no mixing or diluting and can be applied directly from the opened container using a suitable flexible scrapper or palette knife.

PRIMARY USES

MasterProtect 1860TIX is to be used to close up minor surface blow holes in the concrete surfaces to be coated and closing of any pin holes in the first coat prior to application of the second coat.

If the surface to be treated requires the use of a primer (see MasterProtect 1860 technical data sheet and method statement) it is advisable to apply the **MasterProtect 1860TIX** after the installation of the primer.

ADVANTAGES

- Single component – no mixing required
- Rapid hardening (air drying)
- Can be applied onto damp concrete surfaces
- Waterproof – can be left temporarily exposed to rising tide if necessary
- Easily sanded to a smooth finish

PACKAGING AND COLORS

MasterProtect 1860TIX is supplied in 1kg sealed tubs and available in Grey.

APPLICATION METHOD

MasterProtect 1860TIX can be applied to the prepared concrete surfaces using a flexible scrapper / palette knife and should be forced into any blow holes etc. and ALL excess material scraped off. Once hard (30-60 minutes dependent upon temperatures) the surface can be lightly sanded and then wiped with a clean damp cloth to remove any surface dust.

MasterProtect 1860TIX should only be used to fill minor surface defects and is NOT intended to be used as a fairing coat to cover entire areas.

Holes and surface defects in excess of approx. 3mm in depth may require filling in multiple layers allowing each application to harden before re filling.

STORAGE AND SHELF LIFE

Store in original containers, tightly sealed under dry conditions and temperatures between 15–25°C. Do NOT leave exposed to direct sunlight or any source of heat.

The shelf life is 6 months in unopened containers when correctly stored – see above.

HEALTH AND SAFETY

Avoid any inhalation of vapour and contact with skin. Wear protective gloves, goggles and clothing. In case of skin contact, rinse immediately with soap and water! In case of eye contact, bathe eyes with water at once, then consult a doctor.

DO NOT EAT, DO NOT SMOKE AND DO NOT USE AN OPEN FLAME WHEN HANDLING THE PRODUCT.

MasterProtect[®] 1860TIX

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Master Builders Solutions representative.

DO NOT THIN MasterProtect 1860TIX WITH SOLVENTS.

Master Builders Solutions reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/Pr_1860_TIX_09_14/v2/10_14

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions
Construction Chemicals LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800
www.master-builders-solutions.com/en-ae

Disclaimer: the TUV mark relates to certified management system and not to the product mentioned on this datasheet



A brand of
MBCC GROUP