

MasterSeal® 730W

Post-applied, self-adhesive HDPE waterproofing membrane

DESCRIPTION

MasterSeal 730W is a tough HDPE membrane treated with Pressure Sensitive Adhesive, designed for post waterproofing applications.

MasterSeal 730W is compatible with **MasterSeal 730PA** and **MasterSeal 730UVS** pre-applied HDPE membranes. **MasterSeal 730W** is applied on cast in-situ or precast concrete segments.

TYPICAL APPLICATIONS

MasterSeal 730W is intended for use in below grade waterproofing applications at retaining wall and top slabs of various underground construction, tunnels and subways.

ADVANTAGES

- · Excellent mechanical properties
- Excellent Adhesion prevents water migration
- Chemically resistant can be used in all soil and subsoil conditions
- Simple and easy to install

PACKAGING AND ROLL SIZES

MasterSeal 730W is supplied in rolls of 20 m with a width of 1.0 m and membrane thickness of 1.2 mm.

TYPICAL PROPERTIES*

Elongation ASTM D412	500% Minimum
Tensile strength ASTM D412	> 22 N/mm ²
Puncture resistance ASTM E154	> 800 N
Peel adhesion to concrete	> 1.0 N/mm
ASTM D903	
Lap adhesion ASTM D1876	> 1.0 N/mm
Resistance to hydrostatic pressure	> 70 m
at 1hr	

The performance data is typical and based upon controlled laboratory conditions. Actual performance on the job site may vary from these values based on actual site conditions.

APPLICATION GUIDELINES

SURFACE PREPARATION

Substrate shall be sound, regular, smooth and should have clean surface free from laitance, oil, grease, mold release agent, residual curing compound, dust, loose aggregates, or other contaminants that could impair adhesion.

Substrates must be primed with MasterTop P 650 or MasterTile P 302 primer.

PLACING / APPLICATION

The detailed installation of the membrane can be referred from installation manual. Contact our Master Builders Solutions representative for further support.

Membrane repair

Damaged **MasterSeal 730W** can be easily repaired by patching method using the same material. Ensure that the surface is thoroughly cleaned prior to patching application.

Protection

Protect the installed membrane with geotextile. Contact our Master Builders Solutions representative for further information on required protection based on actual conditions.

STORAGE

Stored in original containers, under dry conditions and at temperature between 10-30°C.



MasterSeal® 730W

HEALTH AND SAFETY

For the full health and safety hazard information and how to safely handle and use this product, please make sure that you obtain a copy of the Master Builders Solutions Material Safety Data Sheet (MSDS) from our office or our website.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational Health & Safety standards ISO 9001 and ISO 14001.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/SI_730W_04_22/v1/06_23

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions Construction Chemicals LLC P.O. Box 37127, Dubai, UAE Tel: +971 4 8090800 www.master-builders-solutions.com/en-ae **Disclaimer:** the TUV mark relates to certified management system and not to the product mentioned on this datasheet





