

THIS INSTALLATION GUIDELINES COVERS THE GENERAL PREPARATION AND APPLICATION OF **MasterSeal 931** FLEXIBLE BUTYL RUBBER TAPE WITH A NON-WOVEN BACKING.

METHOD STATEMENT: MasterSeal 931

1. PREPARATION:

- 1.1. All surface to be coated shall be dry, free from oil, grease, and friable matters.
- 1.2. Brittle, porous, or fragile surfaces shall be primed and sealed with **MasterSeal P 102** primer or as recommended by Master Builders Solutions technical personnel prior to application.

2. APPLICATION:

- 2.1. Align the tape, centrally placed along the treatment area, then start peeling the release film.
- 2.2. Simultaneously press down the tape firmly for adhesion and avoid air bubble, ensuring that the surface profile is followed. Pressure rollers can be used to ensure firm adhesion to substrate.
- 2.3. Ensure to maintain minimum of 50mm overlap at all joints.

3. OVERCOATING:

- 3.1. The non-woven material of **MasterSeal 931** can be overcoated with paint or waterproof coating.
- 3.2. **MasterSeal 931** is solvent sensitive and shall be protected in direct contact with solvents.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.
