


MasterSeal® 938

Waterproofing repair tape for MasterSeal application

DESCRIPTION

MasterSeal 938 is a waterproofing repair tape with butyl rubber coating. The tape consists of high flexible polyolefin membrane and a designed non-woven fleece with butyl rubber coating tape with release liner and overlaps for easy removal.



TYPICAL APPLICATIONS

MasterSeal 938 is self-adhesive tape which is used with **MasterSeal 754** pre-applied waterproofing applications at overlapping and damaged areas.

Waterproofing repair tape in conjunction with the Fully Bonded Sheet Membrane.

ADVANTAGES

- Provides easy application at end points of membrane
- It is used for damaged areas on membrane
- Combines perfectly with **MasterSeal 754** membrane

TYPICAL PROPERTIES*

Material composition	Substrate: Polypropylene needle-punch non-woven Membrane: FPO – Flexible Polyolefin Coating: Self-adhesive butyl rubber, high elastic, resistant to ageing Protection: Release foil
Total width Total thickness	200mm 2.2mm (without release liner) 2.4mm (with release liner)
Length per roll	20 meters
Material weight	1525g/m ² (without release liner) 1615g/m ² (with release liner)
Resistance to temperature	-30°C to 60°C
Extension break longitudinal DIN EN ISO 527-3	82.3%

PACKAGING AND ROLL SIZES

MasterSeal 938 is supplied in rolls of: 200mm x 2.4mm x 20m (the thickness 2.4mm includes release liner of 0.2mm).

COLOUR

Grey / Black

APPLICATION GUIDELINES

In **MasterSeal 754** pre-applied membrane applications, **MasterSeal 938** is placed to the edges, end points and damaged areas. Protection foil is removed from the accessory. **MasterSeal 754** is combined with self-adhesive surface of **MasterSeal 938**.

COVERAGE / YIELD

Application requirements can vary according to the total consumption of the project

STORAGE AND SHELF LIFE

MasterSeal 938 has a shelf-life of 12 months from date of production if stored properly in unopened, undamaged, original packaging in dry conditions and at temperatures between +5°C and +30°C.

MasterSeal[®] 938

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/SI_938_05_17/v1/

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions
Construction Chemicals LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800
www.master-builders-solutions.com/en-ae

Disclaimer: the TUV mark relates to certified management system and not to the product mentioned on this datasheet



A brand of
MBCC GROUP