


MasterSeal[®] 948

Pre-punched galvanized bar


DESCRIPTION

MasterSeal 948 is a galvanized steel sheet characterized by the presence of holes drilled every 25mm.



CHARACTERISTICS

Total width	а	30mm
Internal length	b	15.6mm
Single step	С	25mm
Double step	d	50mm
Big hole diameter	х	8.5mm
Little hole diameter	Z	6.5mm



PRIMARY USE

MasterSeal 948 is used for the mechanical fastening of PVC and TPO waterproofing membranes, used as a perimeter and vertical fixing element on the roofing system.

MasterSeal 948 is made of galvanized steel sheet, therefore is not suitable for use in situations where it can come in contact with aggressive substances (corrosive liquids and gases, etc.). For any further clarification please contact the Master Builders Solutions Technical Services department.

ADVANTAGES

- Easy to install
- Light-weight

PACKAGING

MasterSeal 948 is supplied in a packing of 10 pc per box.

Thickness	1.2 mm
Weight	0.5 kg/m
Length	2 m / 3 m

APPLICATION GUIDELINES

MasterSeal 948 is placed above the waterproofing membrane and is fixed with specific fasteners at the bottom of all vertical elements. Through the bar, the load is evenly distributed.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational Health & Safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.



MBS_CC-UAE/SI_948_03_18/v1/

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions Construction Chemicals LLC P.O. Box 37127, Dubai, UAE Tel: +971 4 8090800 www.master-builders-solutions.com/en-ae **Disclaimer:** the TUV mark relates to certified management system and not to the product mentioned on this datasheet



