

THIS METHOD STATEMENT COVERS PREPARATION AND APPLICATION OF A ONE-COMPONENT, WATER VAPOR PERMEABLE WATER BASED SILICA FORTIFIED BLOCK FILLER AND SMOOTHING COMPOUND.

METHOD STATEMENT: MasterSeal AWB 661FL

1. PREPARATION:

- 1.1. The prepared surface must be dry, clean, sound and free of release agents, paint or other residual coatings.
- 1.2. Verify the substrate is flat, masonry joints and struck flush or struck clean, and the substrate is continuous and unbroken.
- 1.3. Any missing or damaged mortar or blocks shall be repaired or replaced to provide a flat surface prior to the application of the **MasterSeal AWB 661FL**.
- 1.4. Allow mortared surfaces to cure for a minimum of 10 days prior to the application of **MasterSeal AWB 661FL**.
- 1.5. Point or seal any cracks or voids greater than 2mm.

2. ROLLER APPLICATION:

- 2.1. A 19mm (3/4) nap roller or high volume, low pressure spray equipment capable of handling abrasive materials are recommended for the application of **MasterSeal AWB 661FL**.
- 2.2. Prewet new roller pads and spin out excess water, this should be done once only to ensure the new roller pads fully saturate with the **MasterSeal AWB 661FL**.
- 2.3. Apply the **MasterSeal AWB 661FL** uniformly onto the wall maintaining a wet edge.
- 2.4. Always ensure the roller is fully loaded to ensure an even thickness of **MasterSeal AWB 661FL**.
- 2.5. Once the **MasterSeal AWB 661FL** has cured to a hardened state moderately tacky state, (this typically occurs within 4 hours) **MasterSeal AWB 661HP** or **MasterSeal AWB 661I** can be applied.

NOTE: Temperature, humidity, wind and substrate moisture can all affect curing time.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.
