

MasterTile® WP Tape

Object 120mm x 50m
Sealing Tape 200mm x 50m and 100mm x 50m
Gasket 42.5cm x 42.5cm and 10cm x 10cm

Special waterproofing tapes / gasket systems for waterproof corner and perimeter joints, pipe culverts and floor drains

DESCRIPTION

MasterTile WP Tape is a special rubber tape that is designed to reinforce and waterproof joints, corners, covers, angles, changes of plane, pipe penetrations and changes in material, as part of the **MasterTile WP 668** waterproofing system.

TYPICAL APPLICATIONS

- For indoor and outdoor use.
- For walls and floors.
- For wet areas with non pressurised water such as showers, in residential buildings, hotels, old peoples homes and hospitals.
- For permanently wet areas with pressurised water such as swimming pools.
- For embedding in the waterproof coatings **MasterTile WP 668**, **MasterSeal 588**.
- For waterproofing according to
 - ZDB leaflet "Bonded waterproofing", edition 2005.
 - Building regulation list A part 2 no. 1.10 "Waterproofing substances to be applied in liquid condition directly under tiles."

ADVANTAGES

- Special rubber tape
- Crack-bridging, high security when cracks in the substrates form at a later stage
- Waterproof and resistant to frost, all-purpose use indoors and out

- Resistant to ageing, insensitive to environmental influences
- Secure adhesion, bonding with the waterproofing products **MasterTile WP 668**
- Resistant to limewater as well as chlorinated water, all-purpose use indoors and out as well as in chlorinated swimming pools

APPLICATION GUIDELINES

In the connection area floor/wall and/or wall/wall apply **MasterTile WP 668** in a width of approx. 10cm and/or 15cm by brush or trowel. Press **MasterTile WP 668** into the wet waterproofing material. Do not use sharp-edged tools!

When applying the waterproofing material to the entire area make sure that **MasterTile WP Tape** is fully covered.

PREPARATION OF SUBSTRATE

The substrate must be sound, dry, even, clean and free of oil, grease and other bond-inhibiting residues. The requirements for substrate preparation for the product **MasterTile WP 668**.

TECHNICAL DATA - MATERIAL

Material base	special rubber tape
Components	1 part
Colour	blue
Impermeability in combination with PCI Seccoral	up to head of water of 15m
Tear-out force extensibility diagonal	>15 Mpa
Elongation at break extensibility diagonal	>200%
Temperature resistance	-20°C to +80°C
MasterTile WP 668	50 m roll


MasterTile® WP Tape

Examples

MasterTile WP Tape in combination with MasterTile WP 668


Detail: Floor / wall connection

- ① MasterTile WP Tape
- ② : Waterproofing layer MasterTile WP 668
- ③ Tile adhesive: waterproofing layer MasterTile WP 668




Detail: Pipe culvert / wall

- ① MasterTile WP Tape
- ② MasterTile WP 668
- ③ Tile adhesives on waterproofing layer MasterTile WP 668
- ④ Joint grout



Detail: Installation of a waterproof wall-mounted housing for fittings (e.g. Hansa DAL)

- ① MasterTile WP Tape
- ② MasterTile WP 668
- ③ Tile Adhesive
- ④ Jointing Grout
- ⑤ Gypsum plasterboard




MasterTile® WP Tape

Examples

MasterTile WP Tape in combination with MasterSeal 588

Waterproofing the heads of swimming pools



QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/MTile_WP_Tape_01_09/v3/11_17

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions
Construction Chemicals LLC
 P.O. Box 37127, Dubai, UAE
 Tel: +971 4 8090800
www.master-builders-solutions.com/en-ae

Disclaimer: the TÜV mark relates to certified management system and not to the product mentioned on this datasheet



A brand of
MBCC GROUP