

MasterTop[®] F 585

High-quality, decorative aggregates for use in conjunction with MasterTop systems, especially MasterTop CTZ cementitious terrazzo and MasterTop 1354SC stone carpet

DESCRIPTION

MasterTop F 585 aggregates are a pre-blended mixtures of decorative natural stone chips, graded in size according to the NTMA specifications. **MasterTop F 585** aggregates are designed to be mixed with **MasterTop BC 354** to create **MasterTop 1354SC** stone carpet and with **MasterTop 585** to create **MasterTop CTZ** body coat as part of the cementitious terrazzo system.

Sizes:

For **MasterTop CTZ**
3.0-6.0 mm

For **MasterTop 1354SC**
1.5 - 2.2 mm
2.0 - 3.2 mm
3.0 - 5.6 mm

TYPICAL APPLICATIONS

MasterTop F 585 decorative aggregates can be used in internal and external applications where highly aesthetic flooring is required.

Note: This product is a natural product, which means that colours may slightly differ from batch to batch.

ADVANTAGES

- High impact resistance
- Durable
- Highly decorative
- Colour-fast
- Wear resistant
- Non-oxidising
- Pre-blended for size and matrix

PACKAGING AND COLORS

MasterTop F 585 aggregates are available in 23kg bags and in following standard mixes:

Natural, Mocha, Pepper, Chocolate, Sunflower

For bespoke blends contact your Master Builders Solutions representative.

COVERAGE / YIELD

As per the relevant Master Builders Solutions Product Method Statements and Technical Data Sheets.

MasterTop CTZ: 1 x 20kg bag of **MasterTop 585** is mixed with 1 x 23kg bag of **MasterTop F 585** decorative aggregates.

MasterTop 1354SC: the ratio binder : aggregates (**MasterTop BC 354** : **MasterTop F 585**) depends on the aggregates' size and typically is between 6 and 10% by weight.

STORAGE AND SHELF LIFE

Store out of direct sunlight, clear of the ground on pallets protected from rainfall. Avoid excessive compaction. The shelf life is 12 months when stored as above.

MasterTop[®] F 585

HEALTH AND SAFETY

MasterTop F 585 aggregates are inert and harmless however, may cause irritation. In case of contact with eyes, immediately flush with plenty of water for at least 15 minutes. Call a physician. In case of contact with skin, wash skin thoroughly. For further information refer to the material safety data sheet.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational Health & Safety standards ISO 9001 and ISO 14001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/Top_F 585_02_20/v1/04_21

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions
Construction Chemicals LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800
www.master-builders-solutions.com/en-ae

Disclaimer: the TUV mark relates to certified management system and not to the product mentioned on this datasheet



A brand of
MBCC GROUP