

MasterTop® P 651

Three-component, high-build solvent free epoxy surface sealer and primer

DESCRIPTION

MasterTop P 651 is a high grade; high-build, three-component epoxy primer and surface sealer. MasterTop P 651 is used as a sealer or scratch coat with, and without, the addition of quartz sand.

TYPICAL APPLICATIONS

MasterTop P 651 is suitable for the sealing of concrete surfaces, as well as for the filling of fissures and joints.

MasterTop P 651 may be mixed with sand to the desired consistency to repair patches or form covings. In either case the mixed mortar must be applied to a surface previously coated with MasterTop P 651 resin and whilst still tacky.

Consult your Master Builders Solutions representative.

PACKAGING AND COLORS

MasterTop P 651 is available in 25.4 kg units and is Off-White.

TYPICAL PROPERTIES*

	25°C	40°C
Pot life	40 min	22 min
Curing time	15 h	10 h
Maximum service temp	60°C	
** Flexural Strength ASTM C580	>40 N/mm²	
** Tensile Strength ASTM C307	>15 N/mm²	
Slip resistance BS 7976 Part 2	85	
Bond strength ASTM D4541	>2 N/mm²	

^{**}tested at 25°C

APPLICATION GUIDELINES

Cement bound substrates

The surface to be coated must be clean and required free of dust, oil and grease; it must be capable of bearing loads. Laitance must be removed by means of captive blasting, grinding or other suitable method.

MIXING

For mixing and application instructions, please refer to the relevant product system method statement.

COVERAGE / YIELD

From 0.3-0.35 kg/m² depending on surface texture and porosity.

STORAGE AND SHELF LIFE

Shelf life is minimum 12 months. Store under cover, out of direct sunlight and protect from extremes of temperature. In tropical climates the product must be stored in an air-conditioned environment.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult Master Builders Solutions Technical Services Department.



MasterTop® P 651

HEALTH AND SAFETY

Avoid any inhalation of vapours, avoid skin contact. Wear protective gloves and protective goggles. in case of skin contact, rinse immediately with soap and water. In case of eye contact, bathe eyes with water at once, then consult a doctor. Observe the guidelines concerning the handling of epoxy resins and amines issued by the Employer's Liability Insurance Associations.

QUALITY AND CARE

All products originating from Master Builders Solutions Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001 and ISO 14001.

® = Registered trademark of the MBCC Group in many countries.

MBS_CC-UAE/Top_P651_07_15/v1/09_19

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by Master Builders Solutions either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Master Builders Solutions, are responsible for carrying out procedures appropriate to a specific application

Master Builders Solutions Construction Chemicals LLC P.O. Box 37127, Dubai, UAE Tel: +971 4 8090800 www.master-builders-solutions.com/en-ae









^{*} Properties listed are based on laboratory controlled tests.