

MasterGlenium[®] ACE 8577

High-range superplasticiser for precast manufacturing

DESCRIPTION

MasterGlenium ACE 8577 is an advanced polycarboxylic ether (PCE) based superplasticiser developed to achieve high early strength ideally suited for the precast industry where highest durability and performance are demanded. With specifically tailored constitution of the active material, **MasterGlenium ACE 8502** shows excellent dispersion of cement and still provides good slump retention even at low water binder ratio.

The superior development of early strength with **MasterGlenium ACE 8577** allows for zero or minimum accelerated heat curing processes in precast manufacturing. **MasterGlenium ACE 8577** is compatible with all Portland cements meeting international standards and is formulated to comply with ASTM C494 for Type F admixtures. **MasterGlenium ACE 8577** is not to be used with sulphonated polymer based admixtures.

CHEMISTRY AND MECHANISM

MasterGlenium ACE 8577 is differentiated from conventional superplasticisers in that it is based on a unique polycarboxylate ether polymer with long lateral chains. This greatly improves cement dispersion. Conventional superplasticisers, such as those based on sulphonated melamine and naphthalene formaldehyde condensates, at the time of mixing, become absorbed onto the surface of the cement particles. This absorption takes place at a very early stage in the hydration process. The sulphonic groups of the polymer chains increase the negative charge on the surface of the cement particle and dispersion of the cement occurs by electrostatic repulsion.

At the start of the mixing process the same electrostatic dispersion occurs as described previously, but the presence of the lateral chains, linked to the polymer backbone, generate a steric hindrance, which stabilises the cement particles capacity to separate and disperse. This mechanism provides flowable concrete with greatly reduced water demand.

FEATURES AND BENEFITS

MasterGlenium ACE 8577 offers the following benefits for the precast concrete industry:

- Produce rheoplastic and self-consolidating

concrete using low w/c ratio

- Ease of placing and compaction. Less vibration required even in case of steel reinforcement congestion. Less workmanship required.
- Optimize curing cycle by shortening curing time or decreasing curing temperature
- Eliminate heat curing processes.
- Reduced slump loss to avoid re-tempering of concrete
- Improve surface appearance and concrete quality.
- Produce durable precast concrete elements
- As compared to the traditional superplasticisers, improve engineering properties such as early and ultimate compressive and flexural strengths.

APPLICATION

Dispensing

MasterGlenium ACE 8577 is a ready-to-use admixture that is added to the concrete at the time of batching.

The maximum effect is achieved when **MasterGlenium ACE 8577** is added after all the components are already in the mixer and after the addition of at least 80% of the total water. **MasterGlenium ACE 8577** must not be added to dry materials. A separate dispenser and feed line must be used.

DOSAGE

The normally recommended dosage rate is 0.5 to 1.2 litres per 100 kg of binder. Other dosages may be used in special cases according to specific job site conditions. In this case please consult our MBCC Group representative.

MasterGlenium[®] ACE 8577

PACKAGING

MasterGlenium ACE 8577 is available in bulk and 1000L IBC.

SHELF LIFE

MasterGlenium ACE 8577 must be stored in a place where the temperature is not below 0°C. In case the product freezes, increase the temperature of the product to 30°C and remix.

PRECAUTIONS

Health: MasterGlenium ACE 8577 does not contain any hazardous substances requiring labelling.

It is safe for use with standard precautions followed in the construction industry, such as use of handgloves, safety goggles, etc.

For detailed Health, Safety and Environmental Recommendations, please consult and follow all instructions on the product Material Safety Data Sheet.

® = registered trademark of MBCC Group member in many countries of the world

MY#MasterGlenium ACE 8577 v1-0418

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this MBCC Group publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by MBCC Group either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not MBCC Group, are responsible for carrying out procedures appropriate to a specific application.

Master Builders Solutions Malaysia Sdn Bhd
No. 8, Jalan Keluli 2, Kawasan Perindustrian Bukit Raja,
41050 Klang, Selangor, Malaysia.
Tel : +603 3082 1000
www.master-builders-solutions.com/en-asiapacific