

MasterBrace[®] ADH 4000

Adhesive for MasterBrace LAM Fibre Reinforced Polymer Strengthening Systems

DESCRIPTION

MasterBrace ADH 4000 is the adhesive for the **MasterBrace LAM** system.

The **MasterBrace LAM** system is based on ready to use carbon fiber laminate (pultruded plate) that provides high tensile strength combined with light-weight and is used for flexural reinforcement of concrete and other building materials.

FIELDS OF APPLICATION

For use as a structural adhesive when used in conjunction with **MasterBrace LAM** system.

FEATURES AND BENEFITS

- High Strength
 - Non-Slump
 - Strong Adhesion
 - Chemical Resistant
 - Easy to use
- Supplied in pre-weighed units.

TECHNICAL DATA / TYPICAL PROPERTIES

Performance of MasterBrace ADH 4000	
Composition	Two component epoxy based adhesive
Color	Grey
Specific gravity @ 25°C	1.75
Compressive strength	>80 N/mm ²
Flexural strength	>20 N/mm ²
Tensile strength	>15 N/mm ²
Bond strength to Concrete	>3 N/mm ² (failure in concrete)
Pot life @ 40°C	45 Minutes

PACKAGING

MasterBrace ADH 4000 is available in 6 kg units.)

APPLICATION PROCEDURE PREPARATION

The surfaces of the elements to be strengthened should be ground or treated by abrasive blasting to remove any existing coatings, laitance and other loose material.

The prepared substrates should be free of all oils, grease, dust or any curing membranes.

Following preparation the elements to be strengthened should be vacuumed to ensure the removal of all dirt and dust before application of the **MasterBrace ADH 4000**.

Clean the surface of the **MasterBrace LAM** with suitable solvent (**MasterTop THN 2**, MEK or Acetone) to ensure all carbon dust, and any oil or grease is removed.

Note: The minimum adhesive tensile strength of the substrate should be 1.5 N/mm².

MIXING:

Mechanically mix component A and Component B for approximately 3 minutes until a smooth mix has been obtained and no streaks are visible in the material.

APPLICATION:

Apply one layer of **MasterBrace ADH 4000** a minimum of 1.5 mm thick onto both the surface of the substrate and **MasterBrace LAM**. Immediately install the **MasterBrace LAM** by hand onto the substrate. Using a roller, exert a constant pressure onto the installed by moving the tool both ways in the direction of the fibers so that the adhesive squeezes out of the sides of the laminate.

Remove excess adhesive.

MasterBrace[®] ADH 4000

Adhesive for MasterBrace LAM Fibre Reinforced Polymer Strengthening Systems

CLEANING:

Tools must be cleaned immediately after use with **MasterTop THN 2**.

CURING

MasterBrace ADH 4000 will cure at temperatures as low as 5°C although at lower temperatures cure is retarded.

COVERAGE

A 6 kg pack will be sufficient to bond @ 3mm thickness approximately 14 Lm of 80mm wide **MasterBrace LAM** (excluding wastage).

STORAGE

Store at ambient temperatures in cool, dry warehouse conditions in manufacturer's sealed containers.

SHELF LIFE

Up to 12 months if stored according to manufacturer's instructions.

WATCHPOINTS

Surfaces exposed to U.V. rays should be protected within two days (maximum seven days) with the special product from the **MasterSeal** range in order to ensure perfect bonding between the protective layer and FRP.

HEALTH AND SAFETY

*For full information on Health and Safety matters regarding this product the relevant Health and Safety Data Sheet should be consulted.

The following general comments apply to all products.

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs, (which may also be tainted with vapor until the product is fully cured and dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Keep away from children and animals. Reseal containers after use.

SOLVENT BASED PRODUCTS

Use in well ventilated areas; avoid inhaling. Suitable respiratory equipment may be needed, e.g. when spraying. Can cause skin, eye irritation. Wear protective eye shields and gloves during use. Do not smoke or allow sparks or naked lights when stored or in use.

POWDER PRODUCTS

Should be handled to minimize dust formation; use light mask if excessive dust unavoidable. Cement powders when wet or moistened can cause burns to skin and eyes which should be protected during use.

RESIN PRODUCTS

Can cause irritation, dermatitis or allergic reaction. Use protective equipment particularly for skin and eyes. Use only in well ventilated areas.

SPILLAGE

Chemical products can cause damage; clean spillage immediately.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Master Builders Solutions representative.

Master Builders Solutions reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All Master Builders Solutions Products are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health and safety standards of ISO 9001 and Master Builders Solutions ESHQ recommendations.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC-Group in many countries

MasterBrace[®] ADH 4000

Adhesive for MasterBrace LAM Fibre Reinforced Polymer Strengthening Systems

CONTACT

Should you require any further information, please do not hesitate to contact us:

www.master-builders-solutions.com/en-sa
enquirycc.saudi@mbcc-group.com
M: +966 13 853 8600

Master Builders Solutions Saudi Arabia for
Manufacturing LLC.
P.O. Box 1884, Al Khobar, KSA

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

Disclaimer:

In view of widely varying site conditions and fields of application of our products, this technical data sheet is meant to provide general application guidelines only. This information is based on our present knowledge and experience. The customer is not released from the obligation to conduct careful testing of suitability and possible application for the intended use. The customer is obliged to contact the technical help-line for fields of application not expressly stated in the technical data sheet under "Fields of Application". Use of the product beyond the fields of application as stated in the technical data sheet without previous consultation with Master Builders Solutions and possible resulting damages are in the sole responsibility of the customer.

All descriptions, drawings, photographs, data, ratios, weights i.e. stated herein can be changed without advance notice and do not represent the condition of the product as stipulated by contract. It is the sole responsibility of the recipient of our products to observe possible proprietary rights as well as existing laws and provisions. The reference of trade names of other companies is no recommendation and does not exclude the use of products of similar type. Our information only describes the quality of our products and services and is no warranty. Liability is accepted for incomplete or incorrect particulars in our data sheets only in the event of intent or gross negligence, without prejudice to claims under product liability laws.