

MasterTop[®] P 650

Two-component solvent free epoxy surface sealer and primer

DESCRIPTION

MasterTop P 650 is a high grade; low-viscosity, two-component epoxy primer and surface sealer. MasterTop P 650 is used as a sealer or scratch coat with, and without, the addition of quartz sand.

PRIMARY USES

MasterTop P 650 is suitable for the sealing of concrete surfaces, as well as for the filling of fissures and joints. To improve adhesion MasterTop P 650 is sprinkled with quartz sand while still wet to create a mechanical key for subsequent coatings.

MasterTop P 650 may be mixed with sand to the desired consistency to repair patches or form coverings. In either case the mixed mortar must be applied to a surface previously coated with MasterTop P 650 resin and whilst still tacky. Consult your Master Builders Solutions representative.

COLOURS

Colourless

PACKAGING

MasterTop P 650 is available in 15kg units.

Cured at 7 days @20°C	
Pot Life (25°C):	20 mins
Density:	1.09
Bonding strength	Greater than cohesive strength of typical good quality concrete substrate
Application time	approx. 20 mins. at approx. 25°C
Application temperature	10°C to 40°C substrate temp
Recoat after	approx. 6 hours at 30°C approx. 12 hours at 20°C

GUIDE TO APPLICATION

CEMENT BOUND SUBSTRATES

The surface to be coated must be clean and required free of dust, oil and grease; it must be capable of bearing loads. Laitance must be removed by means of captive blasting, grinding or other suitable method.

MIXING:

Pour the B component into the A component then mix until streak free.

On porous surfaces a maximum of 0.5 litres of MasterTop Thinner No. 2 per 12.4kg unit of Primer may be added to improve penetration.

APPLICATION:

Apply by roller brush or airless spray at the required coverage to suit the application for which it is being used.

COVERAGE

From 0.15kg/m² depending on surface texture and porosity.

STORAGE

Shelf life is up to 1 year. Store under cover, out of direct sunlight and protect from extremes of temperature. In tropical climates the product must be stored in an air conditioned environment.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult Master Builders Solutions's Technical Services Department.

SAFETY PRECAUTIONS

Avoid any inhalation of vapours, avoid skin contact! Wear protective gloves and protective goggles! In case of skin contact, rinse immediately with soap and water! In case of eye contact, bathe eyes with water at once, then consult a doctor! Observe the guidelines concerning the handling of epoxy resins and amines issued by the Employer's Liability Insurance Associations

MasterTop® P 650

Two-component solvent free epoxy surface sealer and primer

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Master Builders Solutions representative.

Master Builders Solutions reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All Master Builders Solutions Products are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health and safety standards of ISO 9001 and Master Builders Solutions ESHQ recommendations.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC-Group in many countries

CONTACT

Should you require any further information, please do not hesitate to contact us:

www.master-builders-solutions.com/en-sa
enquirycc.saudi@mbcc-group.com
M: +966 13 853 8600

Master Builders Solutions Saudi Arabia for
Manufacturing LLC.
P.O. Box 1884, Al Khobar, KSA

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

Disclaimer:

In view of widely varying site conditions and fields of application of our products, this technical data sheet is meant to provide general application guidelines only. This information is based on our present knowledge and experience. The customer is not released from the obligation to conduct careful testing of suitability and possible application for the intended use. The customer is obliged to contact the technical help-line for fields of application not expressly stated in the technical data sheet under "Fields of Application". Use of the product beyond the fields of application as stated in the technical data sheet without previous consultation with Master Builders Solutions and possible resulting damages are in the sole responsibility of the customer.

All descriptions, drawings, photographs, data, ratios, weights i.e. stated herein can be changed without advance notice and do not represent the condition of the product as stipulated by contract. It is the sole responsibility of the recipient of our products to observe possible proprietary rights as well as existing laws and provisions. The reference of trade names of other companies is no recommendation and does not exclude the use of products of similar type. Our information only describes the quality of our products and services and is no warranty. Liability is accepted for incomplete or incorrect particulars in our data sheets only in the event of intent or gross negligence, without prejudice to claims under product liability laws.