

# MasterTop® 20

Concrete hardening and dustproofing liquid

## DESCRIPTION

**MasterTop 20** is a colorless low viscosity liquid for application to concrete. It hardens and dustproofs the surface.

## TYPICAL APPLICATIONS

Hardening and dustproofing concrete floors or cement-based wearing screeds and pavings in:

- Factories.
- Garages.
- Industrial units.

## ADVANTAGES

- Permanent treatment.
- New or old floors can be treated.
- Simple and easy to use.
- Used straight from the container.
- Economical.

## ACTION

By combining with the free lime produced during hydration of the cement, **MasterTop 20** forms hard insoluble crystals thus binding the particles together and sealing the surface to form a hard non-dusting surface.

## COMPOSITION

**MasterTop 20** is an aqueous solution of sodium silicate plus surface active chemicals.

## PACKAGING

**MasterTop 20** is available in 210 litre containers.

## APPLICATION PROCEDURE

### Preparation:

Remove all oil, grease, etc. using a degreasing solution. Brush the floor with a hard broom or wire brush. Remove all dust and loose matter using a soft broom or industrial vacuum. If wetting of the floor has taken place during preparation it must be allowed to dry out before commencement of **MasterTop 20** application.

**Method of application:** Stir the **MasterTop 20** before use. Pour evenly or use a plastic watering container to sprinkle the **MasterTop 20** liquid over the surface of the concrete. Then sweep the **MasterTop 20** backwards and forwards over the floor to ensure even penetration.

Any **MasterTop 20** not totally absorbed into the surface should be removed by mops or squeegees before drying.

24 hours after initial treatment, apply a second coat in a similar manner (some floors may require three coats).

24 hours after the final coat, wash down the floor using clean water.

The floor may be walked on and used during the treatment period.

## WATCHPOINTS

### New concrete:

New concrete should be allowed to cure fully (21 days minimum).

### Dense floors:

Hard compacted / power floated surfaces may not have sufficient porosity to allow absorption of the **MasterTop 20**. Prior to treatment test for absorption of water. If concrete is absorbent, test a small area with neat **MasterTop 20** and diluted **MasterTop 20** to see whether penetration is achieved. Then proceed accordingly. If in doubt, ask for technical assistance from your Master Builders Solutions representative.

### Porous floors:

**MasterTop 20** is not suitable for floors of high porosity. In such cases the use of **MasterKure 181** should be considered.

## OTHER PRECAUTIONS

Take care to protect glass, paintwork, brickwork, furnishings, etc., from splashes. Do not use **MasterTop 20** on coloured concrete, brickwork or masonry.

Note: **MasterTop 20** will not work on weak, friable or dusting concrete.

# MasterTop® 20

Concrete hardening and dustproofing liquid

## COVERAGE RATE

As porosity and texture of concrete floors and cement pavings vary considerably, it is not possible to quote accurate coverage rates, but the following will provide a guide:

Tamped concrete:	Approx. 3.5-5m <sup>2</sup> / Liter
Smooth concrete:	Approx. 5-7m <sup>2</sup> / Liter
Dense Power trowelled	Approx. 9-10m <sup>2</sup> / Liter

## EQUIPMENT CARE

All equipment should be washed in clean water immediately after use.

## SPECIFICATION CLAUSE

### MasterTop 20

All concrete, granolithic and screed wearing surfaces shall receive two coats of **MasterTop 20** colorless hardener and dust proofer as manufactured by Master Builders Solutions, or similar approved, to the following specification:

Composition: A colorless, aqueous solution of sodium silicate plus surface active chemicals.

The liquid shall be applied strictly in accordance with the manufacturer's recommendations.

## STORAGE

Store under cover out of direct sunlight and protect from extremes of temperature.

Failure to comply with recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult Master Builders Solutions's Technical Services Department.

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Master Builders Solutions representative.

Master Builders Solutions reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All Master Builders Solutions Products are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health and safety standards of ISO 9001 and Master Builders Solutions ESHQ recommendations.

\* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the MBCC-Group in many countries

## CONTACT

Should you require any further information, please do not hesitate to contact us:

[www.master-builders-solutions.com/en-sa](http://www.master-builders-solutions.com/en-sa)  
[enquirycc.saudi@mbcc-group.com](mailto:enquirycc.saudi@mbcc-group.com)  
M: +966 13 853 8600

Master Builders Solutions Saudi Arabia for  
Manufacturing LLC.  
P.O. Box 1884, Al Khobar, KSA

## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this Master Builders Solutions publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

### Disclaimer:

In view of widely varying site conditions and fields of application of our products, this technical data sheet is meant to provide general application guidelines only. This information is based on our present knowledge and experience. The customer is not released from the obligation to conduct careful testing of suitability and possible application for the intended use. The customer is obliged to contact the technical help-line for fields of application not expressly stated in the technical data sheet under "Fields of Application". Use of the product beyond the fields of application as stated in the technical data sheet without previous consultation with Master Builders Solutions and possible resulting damages are in the sole responsibility of the customer.

All descriptions, drawings, photographs, data, ratios, weights i.e. stated herein can be changed without advance notice and do not represent the condition of the product as stipulated by contract. It is the sole responsibility of the recipient of our products to observe possible proprietary rights as well as existing laws and provisions. The reference of trade names of other companies is no recommendation and does not exclude the use of products of similar type. Our information only describes the quality of our products and services and is no warranty. Liability is accepted for incomplete or incorrect particulars in our data sheets only in the event of intent or gross negligence, without prejudice to claims under product liability laws.