




MasterTop 1785


Water-borne, thin epoxy system with matt – satin finish

Fields of application: Industrial floor bearing low to medium loads, horizontal and vertical surface (indoor).

Consumption:

	Primer Diluted up to 10% Water	MasterTop TC 485 W pigmented, EP, 2 component, waterborne	0,15-0,20 kg/m ²
	Top coat	MasterTop TC 485 W pigmented, EP, 2 component, waterborne	0,20-0,25 kg/m ²
	Optional*	MasterTop TC 485 W pigmented, EP, 2 component, waterborne	0,20-0,25 kg/m ²
	Total thickness of system	ca. 0,15 - 0,20 mm	

Remark: Consumptions are indicative and may be higher, depending on substrate roughness, temperature and porosity, as well as waste produced during application.
 * **For light colours or very porous substrates an extra layer may be necessary.**



MasterTop 1785

Water-borne, thin epoxy system with matt – satin finish

DISCLAIMER

The technical information given in this publication is based on the present state of our best scientific and practical knowledge. **Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti.** is only responsible for the quality of the product **Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti.** is not responsible for results that may occur because the product is used other than advised and/or out of instructions regarding the place and the method of use. This technical form is valid only till a new version is implemented and nullifies the old ones.

CONTACT INFORMATION

Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti.

Adres: Barbaros Mah. Begonya Sok.

Nidakule Kuzey Ataşehir, C Kapısı

No:3 E/5, 34746 Ataşehir İstanbul / Türkiye

Tel: 0216 217 88 00

Mail: mbs.tr@mbcc-group.com

Web: www.master-builders-solutions.com/tr-tr

® Registered trademark of a MBCC Group member in many countries of the world

MasterTop® 1785 Technical Data Sheet -Revision

Date: 09/2023