Product Bulletin



Finetex Finish

100% acrylic polymer finish coat

COLORS

Available in a wide variety of standard colors

PACKAGING 5 gallon pail (19 liter pail)

COVERAGE Varies depending upon texture

For smooth finish application: Approximately 365 - 375 ft² (33.9 to 34.5 m²) per coat, per pail (minimum 2 coats)

For skip trowel: Approximately 150 to 160 ft² (13.9 to 14. 9 m²) per pail



DESCRIPTION

Factory-mixed, 100% acrylic polymer finish coat. Finetex Finish can achieve a wide variety of free-formed, textured appearances, including stipple and skip-trowel.

USES

- 1. Finetex Finish provides an aesthetically pleasing surface color and Finetex for the Finestone Wall Systems.
- Finetex Finish can also be utilized as a textured coating for poured concrete or unit masonry, veneer plaster or gypsum wallboard (interior applications only), conventional stucco, Finestone Stucco Wall System and certain insulating concrete forms.

NOTE: If a "smooth application is required, multiple coats and skillful applications techniques will be required. Over trowelling or "burnishing" may create changes in color.

FEATURES	BENEFITS
Ability to create unique surface Textures	Achieve a wide variety of appearances include stipple and skip-trowel
100% Acrylic polymer chemistry	Long-term durability and weather resistance
Does not require a sealer	Save time and money
Weather resistant	Repels water and resists wind-driven rain
Breathable	Doesn't blister, peel or flake



MIXING

- 1. Thoroughly mix the factory-prepared Finetex Finish with a mixer until thoroughly blended.
- 2. A small amount of clean, potable water may be added to adjust workability.
- 3. Additives are not permitted.
- 4. Close container when not in use.
- 5. Clean tools with soap and water immediately after use.

APPLICATION

- Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (¹/₄" in 10').
- 2. Apply Finetex Finish directly to the Finestone Base Coat/Reinforcing Mesh with a clean, stainless steel trowel.
- 3. Apply and level Finetex Finish during the same operation, to obtain minimum 1.6 mm (1/16") thickness uniform coverage.
- Maintain a wet edge on Finetex Finish by applying and texturing continually over the wall surface.
- 5. Work Finetex Finish to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area.
- 6. Float Finetex Finish to achieve final texture.

LIMITATIONS

- Protect Finestone materials during transportation and installation to avoid physical damage.
- Store Finestone materials in a cool, dry place protected from freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
- 3. Do not apply Finestone materials in ambient temperatures below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail. If using a thicker application of Finetex Finish, longer drying period will be required.
- 4. Do not apply Finestone materials to frozen surfaces.

 Samples of Finetex Finish are available from Finestone for color approval only. Samples for job approval must be made in the field by the applicator, and approved prior to ordering.

TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at finestone.master-builders-solutions.com/en, for additional information about products and systems and for updated literature.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting finestone.master-builders-solutions. com/en, e-mailing your request to mbsbscst@ mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails

to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

For the most current version of this literature, please visit our website at finestone.master-builders-solutions.com/en.

Master Builders Solutions Construction Systems US, LLC

889 Valley Park Drive, Shakopee, MN 55379 finestone.master-builders-solutions.com/en

Customer Service +1 (800) 433-9517 Technical Service +1 (800) 589-1336