

# Sheathing Fabric

Reinforced non-woven polyester fabric

## PACKAGING

4" Sheathing Fabric:  
101.5 mm x 54.8 m (4" x 180') roll.  
Weight is 83 g/m<sup>2</sup> (2.45 oz/yd<sup>2</sup>).

6" Sheathing Fabric:  
152.4 mm x 54.8 m (6" x 180') roll.  
Weight is 83 g/m<sup>2</sup> (2.45 oz/yd<sup>2</sup>).

9" Sheathing Fabric:  
228.5 mm x 54.8 m (9" x 180') roll.  
Weight is 83 g/m<sup>2</sup> (2.45 oz/yd<sup>2</sup>).

## SHIPPING AND STORAGE:

- Protect Master Builders Solutions Wall Systems' materials during transportation and installation to avoid physical damage.
- Store Master Builders Solutions Wall Systems' materials in a cool, dry place. Protect from extreme heat, moisture, cold and direct sunlight.

## SHELF LIFE

2 years when stored in the original unopened container and stored as directed.

## DESCRIPTION

Reinforced non-woven polyester fabric designed for use with Finestop RA, Finestop RS or Finestop VB air/water-resistive barriers. Listed in ICC-ES evaluation reports ESR-3209 and ESR-3310. Tested with Finestop RA, RS or VB in accordance with ICC-ES Acceptance Criteria AC212 for water-resistive barrier coatings, AC 148 for flexible flashing and ASTM E2357 for air barrier assemblies.

## USES

For above grade use with Finestop RA, RS or VB air/water-resistive barriers. 4", 6" or 9" Sheathing Fabric reinforces Finestop RA, RS or VB over acceptable rough openings, sheathing joints and at transitions.

## LIMITATIONS

1. Protect Sheathing Fabric during transportation and installation to avoid physical damage.
2. Store Sheathing Fabric in a cool, dry place protected from exposure to moisture.
3. Reference Finestop RA, RS or VB product bulletin, specifications and details for complete information on installation.
4. Apply at temperatures 4 °C (40 °F) and higher (if LT Additive is used with Finestop RA or Finestop VB, application temperature can be lowered to -4 °C (25 °F)).

## APPLICATION:

Apply mixed Finestop RA, RS or VB at all sheathing joints, terminations, inside and outside corners and rough openings. Immediately place and center 4", 6" or 9" Sheathing Fabric over wet Finestop RA, RS or VB, embedding and completely saturating Sheathing Fabric. Ensure Sheathing Fabric extends evenly on both sides of the sheathing joint. Lap Sheathing Fabric 63.5 mm (2 1/2") minimum at intersections. Allow to dry to the touch before applying Finestop RA, RS or VB to entire wall surface. If spraying Finestop RA, RS or VB "wet on wet" application is acceptable.

## FEATURES

Easy to cut

Applicator friendly

Combines with Finestop RA, RS or VB as a fully qualified air/water-resistive barrier and flexible flashing material

## BENEFITS

Convenient; fast and reliable application

Flexible; easy to handle

Meets ASTM E 2357, ICC-ES AC 212 and ICC-ES AC 148 requirements

---

#### HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting [finestop.master-builders-solutions.com/en](http://finestop.master-builders-solutions.com/en), e-mailing your request to [mbsbscst@mbcc-group.com](mailto:mbsbscst@mbcc-group.com) or calling +1 (800) 433-9517. Use only as directed.

**IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.**

---

#### TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at [finestop.master-builders-solutions.com/en](http://finestop.master-builders-solutions.com/en), for additional information about products and systems and for updated literature.

---

#### LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

**FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.**

For the most current version of this literature, please visit our website at [finestop.master-builders-solutions.com/en](http://finestop.master-builders-solutions.com/en).