

PRODUCT DATA SHEET

SikaWall[®]-75 Sheathing Fabric 4, 6 and 9

Reinforced non-woven polyester fabric

COLOR

Grey

PACKAGING

SikaWall-75 Sheathing 4 Fabric
4" x 180' roll, 18 rolls/case

SikaWall-75 Sheathing 6 Fabric
6" x 180' roll, 12 rolls/case

SikaWall-75 Sheathing 9 Fabric
9" x 180' roll, 12 rolls/case

COVERAGE PER ROLL

Sheathing 4 Fabric:
180 lin/ft (54.9 lin/m)

Sheathing 6 Fabric:
180 lin/ft (54.9 lin/m)

Sheathing 9 Fabric:
180 lin/ft (54.9 lin/m)

SHELF LIFE

Two (2) years when properly stored in original container.

DESCRIPTION

Reinforced, non-woven, polyester fabric designed for use with Senershield[®]-R/-RS/-VB air/water-resistive barriers. Listed in ICC-ES evaluation report ESR-2986. Tested with Senershield-R/-RS/-VB in accordance with ICC-ES Acceptance Criteria AC212 for water-resistive barrier coatings, AC 148 for flexible flashing and ASTM E2357 for air barrier assemblies.

USES

For above grade use with Senergy air/water-resistive barriers. SikaWall[®]-75 Sheathing 4, 6 or 9 reinforces Senershield-R/-RS/-VB over acceptable rough openings, sheathing joints and transitions.

ADVANTAGES

Convenient; fast and reliable application and easy to cut.

Flexible and easy to handle; applicator friendly 2.45 oz/yd² (83g/m²).

Meets ASTM E 2357, ICC-ES AC 212 and ICC-ES AC 148 requirements.

Combines with Senershield-R/-RS/-VB as a fully qualified air/water-resistive barrier and flexible flashing material.

APPLICATION:**FLASHING ROUGH OPENINGS**

Cut Sheathing Fabric to desired size. Apply a generous amount of mixed Senergy air/water-resistive barrier receiving coat across rough opening and out onto the substrate. Immediately embed Sheathing Fabric, ensure complete saturation. An additional coat of barrier may be necessary to ensure a complete, void and pinhole-free membrane. Extend Sheathing Fabric a minimum 2" onto the exterior wall. Reference Senergy air/water-resistive barrier published details for step by step application details.

SHEATHING JOINT REINFORCEMENT

Precoat sheathing joints, inside and outside corners as well as knot holes and check cracks that may exist in plywood or OSB with mixed Senergy air/water-resistive barrier. Immediately place and center Sheathing Fabric over wet barrier. Ensure Sheathing Fabric extends evenly on both sides of the sheathing joint. Completely saturate Sheathing Fabric with Senersshield-R/-RS/-VB. Lap Sheathing Fabric a minimum of 2½" (63.5 mm) at intersections. If using roller or brush application, allow to dry to the touch before applying Senersshield-R/-RS/-VB to entire wall surface. If spraying, "wet on wet" application is acceptable.

Note: Sheathing Fabric can be used to treat sheathing joints up to ¼" wide, not for use in expansion joints. Reference Senersshield-R/-RS/-VB product bulletin and details for complete information on installation

LIMITATIONS

- Apply at temperatures 25°F (-4°C) and higher.

SHIPPING AND STORAGE:

- Protect materials during transportation and installation to avoid physical damage.
- Store materials in a cool, dry place.
- Protect from extreme heat, moisture, cold and direct sunlight.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting usa.sika.com/senergy, e-mailing your request to mbsbscst@mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

TECHNICAL SUPPORT

Consult Sika Facades Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Sika Facades website at usa.sika.com/senergy, for additional information about products and systems and for updated literature.

LIMITED WARRANTY NOTICE

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com/senergy or by calling our Technical Service Department at +1 (800) 589-1336.

Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at usa.sika.com or by calling +1 (800) 589-1336.