

Application of Textured Acrylic Finishes in Indoor Pool and Spa Areas

Textured acrylic finishes can provide a durable and aesthetically pleasing appearance with a wide variety of options for the walls in rooms containing a swimming pool or hot tub. These finishes have performed successfully, exhibiting long-term durability in such environments. In these applications, where high humidity and temperatures are normal, successful results require particular attention be paid to the HVAC/ mechanical design and proper ventilation. The designer and finish applicator must also consider other factors, such as proper slope of pool deck away from interior walls to reduce the potential for ponding of water and properly sealing all terminations to the pool deck and dissimilar materials. Sealing should be accomplished by installing an acceptable sealant at a minimum 1/2" joint and must include closed cell backer rod or bond breaker tape.



The following instructions are guidelines for the application of Senerflex Textured Acrylic Finishes in interior pool rooms when applied over minimum 1/2" substrates of Dens Shield Tile Backer by Georgia Pacific Corporation, PermaBase Cement Board by National Gypsum or other cement-boards conforming with ASTM C1325 (Type A-exterior). All sheathing must be installed in accordance with sheathing manufacturer's recommended guidelines, with a maximum allowable deflection of L/360.

1. Apply Master Builders Solutions Self-Adhering Mesh Tape over all sheathing joints.
2. Apply mixed Xtra-Stop water resistant base coat to the surface of the Self-Adhering Mesh Tape at the joints and allow the Xtra-Stop to dry prior to application of Flexguard 4 Reinforcing Mesh and Xtra-Stop to the field.
3. Apply mixed Xtra-Stop to entire surface of substrate with a stainless steel trowel to embed the Flexguard 4 Reinforcing Mesh.
4. Immediately place Flexguard 4 against wet Xtra-Stop and embed the reinforcing mesh into the Xtra-Stop by troweling from the center to the edges.
5. Lap reinforcing mesh 2-1/2" minimum at edges.
6. Ensure reinforcing mesh is continuous at corners, void of wrinkles and completely embedded in Xtra-Stop so that no mesh color is visible.
7. If required, apply a second layer of Xtra-Stop to achieve full reinforcing mesh embedment and specified base coat thickness.
8. Allow Xtra-Stop with embedded Flexguard 4 reinforcing mesh to dry hard (normally 8 to 10 hours) before proceeding to application of specified Senerflex Textured Acrylic Finish. For additional moisture resistance, the use of a silicone enhanced finish is recommended.
9. Apply Senerflex Textured Acrylic Finish, maintaining a wet edge on finish coat by applying and texturing continually over the wall surface. Work finish coat to corners, joints, or natural breaks, and do not allow material to set up within an uninterrupted wall area.
10. Float finish coat to achieve final texture.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC (“Master Builders”) warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders’ present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

For the most current version of this literature, please visit our website at senergy.master-builders-solutions.com/en.