



# Performance Grouting

Solutions that  
Challenge Movement





# Grouting Solutions

Zero shrinkage in precision and industrial grouting materials is the key to effectively handling tensile, shear and compressive and dynamic loads...preventing low rebar, anchor bolt and dowel bar pull-out strengths in concrete...and ensuring effective bearing-load distribution when grouting base plates and machinery bases. The right grouting materials provide lasting security, stability and alignment.

## Technologies

- Cementitious grouts with metallic or mineral aggregate. Specifically engineered to be highly fluid, non-bleed, non-shrink, with extended working times.
- Epoxy grouts designed for improved chemical resistance and high dynamic load capability.

## Applications

### VOID AND DUCT GROUTING

- Segmental Bridges
- Cellular Transmission Towers
- Precast Post Tensioned Structural Members

### CHEMICAL ANCHORING

- Foundations
- Slabs
- Structural Components (precast or cast in place)

### PRECISION MACHINERY AND ELEMENT ALIGNMENT

- Industrial Facilities
- Transportation Infrastructure
- Commercial Buildings

## Cementitious Grouts

### MasterFlow® 100 Multi-Purpose Grout

A non-catalyzed, multi-purpose construction grout containing mineral aggregate.

### MasterFlow 110AN Anchoring Grout

Designed for a variety of grouting and anchoring applications where high initial strengths are useful, including the anchoring of railings, bolts, and posts as well as the grouting of machinery and equipment bases.

### MasterFlow 555 Mineral-Aggregate Grout

A semi-fluid, non-shrink mineral-aggregate grout. It is ideally suited for grouting machines or plates requiring optimum load bearing support.

### MasterFlow 713 High-Precision Grout

A cement-based grout with specially graded mineral aggregates. It can be used at any consistency from fluid to damp pack for applications that require precision support and early form stripping or shoulder trimming.

### MasterFlow 885 Metallic-Aggregate Grout

A cement-based metallic aggregate grout with extended working time. It is ideally suited for grouting machines or plates requiring optimum toughness and precision loadbearing support, including machine bases subject to thermal movement.

### MasterFlow 928 Extended Working Time Grout

A hydraulic cement-based mineral aggregate non-shrink grout with extended working time. It is ideally suited for grouting machines or plates requiring precision load-bearing support. It can be placed from fluid to damp pack over a temperature range of 45 to 90° F (7 to 32° C).





### New Technology

#### MasterFlow 4316 High-Performance Grout

A unique grout that provides high early and ultimate compressive strengths over a wide variety of application and service temperatures. The superior performance of MasterFlow 4316 lies in its novel hydraulic cement binder with applied nanotechnology and premium mineral aggregates which, when mixed with water, produces a flowable and pumpable grout that can be installed in temperatures ranging from 35 to 100° F (2 to 38° C).

### Epoxy Grouts

#### MasterFlow 647 Machinery Grout

A modified epoxy resin grout, specially formulated for grouting cracks in structures and machinery foundations. Suitable for pressure injection of grouted baseplates beneath compressors, cement mills, and other vibrating and rotating machinery.

#### MasterFlow 648 High-Flow Grout

A high-strength, high-flow epoxy grout providing superior physical properties in high-temperature applications. It offers high early and 7-day strengths for applications requiring fast turnaround, good chemical and crack resistance, and outstanding flow characteristics and versatility of fill rates.

#### MasterFlow 649 High-Performance

A high-performance epoxy grouting material for support of heavy equipment. It ensures the proper transmission of static and dynamic loads to the equipment foundation.

#### MasterFlow 668 Chock Grout

A three-component modified epoxy-resin-based grout. It is used where high-performance properties are required in less-accessible spaces subject to thermal shock and high vibrations. It can be placed from 1/2–3" (12.5–76 mm) thick on a base-grout pour, directly to the concrete or steel to steel.

#### MasterFlow 678 Deep-Pour Grout

A low exotherm non-shrink deep-pour epoxy grout. Can be placed in depths of up to 18" without extension or lifts.



## Master Builders Solutions

The Master Builders Solutions brand brings all of MBCC Groups expertise together to create chemical solutions for new construction, maintenance, repair and renovation of structures. Master Builders Solutions is built on the experience gained from more than a century in the construction industry.

The know-how and experience of a global community of MBCC Group construction experts form the core of Master Builders Solutions. We combine the right elements from our portfolio to solve your specific construction challenges. We collaborate across areas

of expertise and regions and draw on the experience gained from countless construction projects worldwide. We leverage global MBCC Group technologies, as well as our in-depth knowledge of local building needs, to develop innovations that help make you more successful and drive sustainable construction. The comprehensive portfolio under the Master Builders Solutions brand encompasses concrete admixtures, cement additives, chemical solutions for underground construction, waterproofing solutions, sealants, concrete repair and protection solutions, performance grouts and performance flooring solutions.

## Master Builders Solutions products for the Construction Industry:

### MasterAir®

Solutions for air-entrained concrete

### MasterBrace®

Solutions for concrete strengthening

### MasterCast®

Solutions for manufactured concrete product industry

### MasterCem®

Solutions for cement manufacture

### MasterEmaco®

Solutions for concrete repair

### MasterFinish®

Solutions for formwork treatment

### MasterFlow®

Solutions for precision grouting

### MasterFiber®

Comprehensive solutions for fiber reinforced concrete

### MasterGlenium®

Solutions for high-performance concrete

### MasterInject®

Solutions for concrete injection

### MasterKure®

Solutions for concrete curing

### MasterLife®

Solutions for enhanced durability

### MasterMatrix®

Advanced rheology control solutions for self-consolidating concrete

### MasterPel®

Solutions for water tight concrete

### MasterPolyheed®

Solutions for high-performance concrete

### MasterPozzolith®

Solutions for water-reduced concrete

### MasterProtect®

Solutions for concrete protection

### MasterRheobuild®

Solutions for super-plasticized concrete

### MasterRoc®

Solutions for underground construction

### MasterSeal®

Solutions for waterproofing and sealing

### MasterSet®

Solutions for retardation control

### MasterSure®

Solutions for workability control

### MasterTop®

Solutions for industrial and commercial floors

### Ucrete®

Flooring solutions for harsh environments

**Master Builders Solutions**  
**Constructions Systems US, LLC**  
 889 Valley Park Drive  
 Shakopee, MN 55379 USA

**Customer Service (800) 433-9517**  
**Technical Service (800) 243-6739**  
[master-builders-solutions.com/EN-US](http://master-builders-solutions.com/EN-US)



® registered trademark of a Group member  
 in many countries of the world

© 2023 MBCC Group, 1024903 rev 07/2023

**LIMITED WARRANTY NOTICE:** Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. Master Builders MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. Master Builders WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.