

Wood Grain Effect

Acrylic finishes applied to create the look of wood grain

Walnut



Bottom Coat: 125-U Light Brick Red
Top Coat: 215-N Old Earth

Redwood



Bottom Coat: 141-M Ultrasuede
Top Coat: 142-U Red Brown

Chestnut



Bottom Coat: 32-M Light Peach
Top Coat: 125-U Light Brick Red

Cedar



Bottom Coat: 28-M Mellow Pine
Top Coat: 34-N Almond Tan

Driftwood



Bottom Coat: 243-M Dark Mortar
Top Coat: 285-U Gunmetal

Barnwood



Bottom Coat: 267-P Special White
Top Coat: 199-M Woodland Blush

*All colors matched in Master Builder Solutions Color Portfolio fan deck

Wood Grain Effect

Acrylic finishes applied to create the look of wood grain

PACKAGING

Pebbletex Finetex Finish: 31.7 kg per 19 liter pail (70 lbs per 5 gallon pail)

Color Coat: 24.9 kg per 19 liter pail (55 lbs per 5 gallon pail)

COVERAGE

Varies depending on application technique and surface condition.

Pebbletex Finetex Finish: Approximately 13.9 m² (150 ft²) per pail

Color Coat: Approximately 69.6–116.1 m² (750–1,250 ft²) per pail (one-coat application)

COLORS

Barnwood	Chestnut
Cedar	Redwood
Driftwood	Walnut

OPTIONAL SEALER

Recommended for use with CLRSeal by Master Builders Solutions. CLRSeal is a 100% acrylic sealer, applied to seal and enhance the aesthetic appearance of Wood Grain Effect.

40 lbs (18.14 KG) per 5-gallon pail
16 lbs (7.25 KG) per 2-gallon pail



Wood Grain Effect without CLRSeal is shown on the left, Wood Grain Effect with CLRSeal is on the right

DESCRIPTION

Wood Grain Effect is a finish technique utilizing Pebbletex Finetex Finish – Wood Grain Effect Neutral Gray and two Color Coat finishes by Master Builders Solutions to create the look of wood grain panels in a light weight, easily installed architectural wall finish.

FEATURES	BENEFITS
Wood Grain Look	The look of wood grain in an acrylic based finish
Lightweight	The look and feel of wood grain at a fraction of the weight
100% Acrylic polymer chemistry	Long-term durability and weather resistance
Integral Color	Reduced maintenance and recoating; lasting color uniformity
Weather Resistant	Repels water and resists wind-driven rain

USES

Provides a protective, weather-resistant, wood grain surface color and texture for Finestone EIFS Wall Systems.

TOOLS AND EQUIPMENT

- Hawk
- Margin trowel
- 12 x 5 inch stainless steel trowel
- Plastic float
- Hot knife and wire
- Level
- Low speed drill
- Paddle mixer
- 1/4 inch nap roller cover
- Roller frame
- 1 1/2 inch chip brush
- Wood grain tool
- All purpose sanding sponge

PRODUCTS

- Senerflex Texture Finish – Wood Grain Effect Neutral Grey Color
- Color Coat - two colors as specified by standard color formulas
- Standard Mesh 4 oz
- Finestone base coat
- CLRSeal (Optional)

V-GROOVE

Follow all safety guidelines and use appropriate personal protective equipment.

1. Using a level mark the EPS board with horizontal lines to appropriate length, and space the lines to the appropriate width.
2. Slide the hot knife to cut the v-grooves horizontally in the EPS.
3. Clean the EPS to be free of debris.

BASE COAT AND MESH

APPLICATION – BASE COAT AND MESH

1. Measure mesh against the cut EPS, and cut Standard Mesh 4 oz to the appropriate size.
2. Apply Finestone base coat using a stainless steel trowel, paying close attention to work the Finestone base coat in to the V-grooves.
3. Embed the Standard Mesh 4 oz into the Finestone base coat. Overlap successive layers of Standard Mesh 4 oz a minimum of 2.5 inches.
4. Use a stainless steel trowel or groove tool to push the Standard Mesh 4 oz into the v-groove. Ensure Standard Mesh 4 oz is continuous through v-grooves.

5. Ensure EPS board is completely covered with Finestone base coat to ensure that mesh is securely fastened.

6. Take a chip brush and smooth out the Finestone base coat in the grooves, removing any excess Finestone base coat in the process.

7. Allow application of Finestone base coat to dry for a minimum of 24 hours.

8. Clean tools with soap and water immediately after use.

FINISH COAT APPLICATION

MIXING

1. Thoroughly mix the factory prepared Pebbletex Finetex Finish – Wood Grain Effect Neutral Gray with a mixer to a homogeneous consistency.

2. In separate pails, thoroughly mix the tinted Color Coat with a mixer to a homogeneous consistency.

3. Additives are not permitted. However, clean, potable water may be added to adjust workability.

4. Close container when not in use.

APPLICATION – PREP

1. Ensure weather is conducive to application (4 °C (40 °F) and rising for 24 hours prior to and after with no precipitation in weather forecast).

2. Finestone base coat and reinforcing mesh must be cured for a minimum of 24 hours prior to finish application.

3. If needed, lightly sand the surface of the Finestone base coat with 100-grit sand paper or a masonry block to remove any high spots and clean the surface with a brush.

APPLICATION – FINISH AND WOOD GRAIN TEXTURE

1. Apply a tight application of Pebbletex Finetex Finish – Wood Grain Effect Neutral Gray with a stainless steel trowel to a uniform thickness.

2. Detail the aesthetic v-grooves with a chip brush.

3. Depending on the temperature, floating may begin immediately. Do not apply in the direct sun or to hot walls.

4. Using a plastic or steel trowel, float back and forth along the planks in a lengthwise direction to create imperfections that will look like wood grain. Ensure the same trowels are used throughout the job site for application consistency.

5. Allow for Pebbletex Finetex Finish – Wood Grain Effect Neutral Gray to dry completely (at least 24 hours).

6. Lightly sand the surface with an all purpose sander sponge and cleaner brush.

7. Apply the first coat of Color Coat over the dry Pebbletex Finetex Finish using a 1/4 inch nap roller. Detail the v-groove with a chip brush. Allow to dry to touch.

8. Apply the second coat of Color Coat over the dry first coat of Color Coat using a 1/4 inch nap roller. Detail the v-groove with a chip brush.

9. Immediately drag the wood grain tool along the length of the planks in a rocking motion with enough pressure to expose the color underneath.

10. Allow Color Coat to dry completely (up to 48 hours depending on temperature and humidity).

11. If a gloss finish is desired, apply CLRSeal after Wood Grain Effect has completely dried. Refer to CLRSeal product bulletin for application details.

LIMITATIONS

1. Protect Finestone materials during transportation and installation to avoid physical damage.

2. Store Finestone materials in a cool, dry place protected from freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight. Shelf life is two years with unopened and stored as directed.

3. Do not apply Finestone materials in ambient temperatures below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail. Protect from precipitation until dry.

4. Do not apply Finestone materials to frozen surfaces.

5. Samples for job approval must be made in the field by the applicator and approved prior to ordering.

TECHNICAL INFORMATION

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at www.master-builders-solutions.com/en-us, for additional information about products and systems and for updated literature.

VOC CONTENT

<50 g/l less water and exempt solvents

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.com/en-us, e-mailing your request to mbsbcst@mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

For the most current version of this literature, please visit our website at finestone.master-builders-solutions.com/en.