

## MasterEmaco S 488CI

Version 2.0      Revision Date: 12/31/2020      SDS Number: 000000243937      Date of last issue: 06/05/2020  
Date of first issue: 06/05/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterEmaco S 488CI  
Product code : 000000000055400040 000000000055400040

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Construction Systems  
US, LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585

**Recommended use of the chemical and restrictions on use**

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Serious eye damage/eye irritation : Category 1  
Skin corrosion/irritation : Category 2  
Carcinogenicity (Inhalation) : Category 1A (Lung)  
Specific target organ toxicity - single exposure : Category 3 (respiratory tract irritation)  
Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lung)  
Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Kidney, Immune system)

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

---

## MasterEmaco S 488CI

Version 2.0      Revision Date: 12/31/2020      SDS Number: 000000243937      Date of last issue: 06/05/2020  
 Date of first issue: 06/05/2020

H315 Causes skin irritation.  
 H350i May cause cancer by inhalation.  
 H335 May cause respiratory irritation.  
 H372 Causes damage to organs (lung) through prolonged or repeated exposure (inhalation).  
 H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

## Precautionary Statements

:

**Prevention:**

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P201 Obtain special instructions before use.  
 P271 Use only outdoors or in a well-ventilated area.  
 P260 Do not breathe dust or mist.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P270 Do not eat, drink or smoke when using this product.  
 P264 Wash face, hands and any exposed skin thoroughly after handling.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER or doctor/ physician.  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : modified cement mortar

**Components**

| Chemical name               | CAS-No.    | Concentration (% w/w) |
|-----------------------------|------------|-----------------------|
| Cement, portland, chemicals | 65997-15-1 | >= 25 - < 75          |
| crystalline silica          | 14808-60-7 | >= 25 - < 75          |
| Silicon dioxide             | 7631-86-9  | >= 1 - < 15           |
| Iron oxide                  | 1309-37-1  | >= 0 - < 7            |

## MasterEmaco S 488CI

Version      Revision Date:      SDS Number:      Date of last issue: 06/05/2020  
 2.0          12/31/2020          000000243937      Date of first issue: 06/05/2020

|   |            |                  |
|---|------------|------------------|
| Limestone                                       | 1317-65-3  | $\geq 0 - < 5$   |
| Calcium sulphate                                | 7778-18-9  | $\geq 0 - < 5$   |
| calcium oxide                                   | 1305-78-8  | $\geq 1 - < 5$   |
| 2,2-dimethylpropane-1,3-diol                    | 126-30-7   | $\geq 0.3 - < 3$ |
| magnesium oxide                                 | 1309-48-4  | $\geq 0 - < 3$   |
| Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O) | 13397-24-5 | $\geq 0 - < 3$   |
| sodium nitrite                                  | 7632-00-0  | $\geq 0 - < 1$   |

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this material safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.
- If inhaled : After inhalation of dust.  
 Keep patient calm, remove to fresh air.  
 If difficulties occur:  
 Seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
 Under no circumstances should organic solvent be used.  
 If irritation develops, seek medical attention.
- In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.  
 If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
 Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Eye damage  
 Skin irritation
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
 Water spray  
 Dry powder  
 Carbon dioxide (CO<sub>2</sub>)  
 Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are sufficient.
- Unsuitable extinguishing : water jet

## MasterEmaco S 488CI

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 06/05/2020  |
| 2.0     | 12/31/2020     | 000000243937 | Date of first issue: 06/05/2020 |

---

media

- Specific hazards during fire fighting : Product is not combustible or explosive. Exposure to decomposition products may be a hazard to health.
- Hazardous combustion products : harmful vapours
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal. Avoid dust formation. Rinse with plenty of water. Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid formation of respirable particles. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

## MasterEmaco S 488CI

Version 2.0      Revision Date: 12/31/2020      SDS Number: 000000243937      Date of last issue: 06/05/2020  
 Date of first issue: 06/05/2020

Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.  
 Segregate from acids and bases.  
 Segregate from oxidants.  
 Segregate from foods and animal feeds.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

| Components                  | CAS-No.    | Value type (Form of exposure)       | Control parameters / Permissible concentration | Basis                 |
|-----------------------------|------------|-------------------------------------|--|-----------------------|
| Quartz (SiO <sub>2</sub> )  | 14808-60-7 | TWA value (Respirable fraction)     | 0.025 mg/m <sup>3</sup>                        | ACGIHTLV              |
|                             |            | TWA value                           | 0.05 mg/m <sup>3</sup> (Respirable dust)       | 29 CFR 1910.1001-1050 |
|                             |            | OSHA Action level                   | 0.025 mg/m <sup>3</sup> (Respirable dust)      | 29 CFR 1910.1001-1050 |
|                             |            | REL value (Respirable dust)         | 0.05 mg/m <sup>3</sup>                         | NIOSH                 |
|                             |            | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup>                         | OSHA Z-1              |
|                             |            | TWA (respirable)                    | 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2    | OSHA Z-3              |
|                             |            | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5               | OSHA Z-3              |
|                             |            | TWA (respirable dust fraction)      | 0.1 mg/m <sup>3</sup>                          | OSHA P0               |
|                             |            | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup> (Silica)               | ACGIH                 |
|                             |            | PEL (respirable)                    | 0.05 mg/m <sup>3</sup>                         | OSHA CARC             |
|                             |            | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup> (Silica)                | NIOSH REL             |
| Cement, portland, chemicals | 65997-15-1 | TWA value (Respirable fraction)     | 1 mg/m <sup>3</sup>                            | ACGIHTLV              |

# SAFETY DATA SHEET

**MBCC** GROUP

## MasterEmaco S 488CI

Version  
2.0

Revision Date:  
12/31/2020

SDS Number:  
000000243937

Date of last issue: 06/05/2020  
Date of first issue: 06/05/2020

|                       |            |                                     |  |                                |
|-----------------------|------------|-------------------------------------|--|--------------------------------|
|                       |            | REL value (Total)                   | 10 mg/m3                                       | NIOSH                          |
|                       |            | REL value (Respirable)              | 5 mg/m3  | NIOSH                          |
|                       |            | PEL (Total dust)                    | 15 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1)   |
|                       |            | PEL (Respirable fraction)           | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1)   |
|                       |            | TWA value (Total dust)              | 10 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1-A) |
|                       |            | TWA value (Respirable fraction)     | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1-A) |
|                       |            | TWA value                           | 50 millions of particles per cubic foot of air | 29 CFR 1910.1000 (Table Z-3)   |
|                       |            | TWA (Respirable particulate matter) | 1 mg/m3  | ACGIH                          |
|                       |            | TWA (Respirable)                    | 5 mg/m3  | NIOSH REL                      |
|                       |            | TWA (total)                         | 10 mg/m3                                       | NIOSH REL                      |
|                       |            | TWA (total dust)                    | 15 mg/m3                                       | OSHA Z-1                       |
|                       |            | TWA (respirable fraction)           | 5 mg/m3  | OSHA Z-1                       |
|                       |            | TWA (Total dust)                    | 10 mg/m3                                       | OSHA P0                        |
|                       |            | TWA (respirable dust fraction)      | 5 mg/m3  | OSHA P0                        |
|                       |            | TWA (Dust)                          | 50 Million particles per cubic foot            | OSHA Z-3                       |
| calcium oxide         | 1305-78-8  | TWA value                           | 2 mg/m3  | ACGIHTLV                       |
|                       |            | REL value                           | 2 mg/m3  | NIOSH                          |
|                       |            | PEL                                 | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1)   |
|                       |            | TWA value                           | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1-A) |
|                       |            | TWA                                 | 2 mg/m3  | ACGIH                          |
|                       |            | TWA                                 | 2 mg/m3  | NIOSH REL                      |
|                       |            | TWA                                 | 5 mg/m3  | OSHA Z-1                       |
|                       |            | TWA                                 | 5 mg/m3  | OSHA P0                        |
| Gypsum (Ca(SO4).2H2O) | 13397-24-5 | TWA value (Inhalable fraction)      | 10 mg/m3                                       | ACGIHTLV                       |
|                       |            | REL value (Respirable)              | 5 mg/m3  | NIOSH                          |

## MasterEmaco S 488CI

Version 2.0      Revision Date: 12/31/2020      SDS Number: 000000243937      Date of last issue: 06/05/2020  
 Date of first issue: 06/05/2020

|           |           |                                    |                    |                                |
|-----------|-----------|------------------------------------|--------------------|--------------------------------|
|           |           | REL value (Total)                  | 10 mg/m3           | NIOSH                          |
|           |           | PEL (Total dust)                   | 15 mg/m3           | 29 CFR 1910.1000 (Table Z-1)   |
|           |           | PEL (Respirable fraction)          | 5 mg/m3            | 29 CFR 1910.1000 (Table Z-1)   |
|           |           | TWA value (Total dust)             | 15 mg/m3           | 29 CFR 1910.1000 (Table Z-1-A) |
|           |           | TWA value (Respirable fraction)    | 5 mg/m3            | 29 CFR 1910.1000 (Table Z-1-A) |
|           |           | TWA (Respirable)                   | 5 mg/m3            | NIOSH REL                      |
|           |           | TWA (total)                        | 10 mg/m3           | NIOSH REL                      |
|           |           | TWA (total dust)                   | 15 mg/m3           | OSHA Z-1                       |
|           |           | TWA (respirable fraction)          | 5 mg/m3            | OSHA Z-1                       |
|           |           | TWA (Total dust)                   | 15 mg/m3           | OSHA P0                        |
|           |           | TWA (respirable dust fraction)     | 5 mg/m3            | OSHA P0                        |
|           |           | TWA (Inhalable particulate matter) | 10 mg/m3 (Calcium) | ACGIH                          |
| Limestone | 1317-65-3 | REL value (Respirable)             | 5 mg/m3            | NIOSH                          |
|           |           | REL value (Total)                  | 10 mg/m3           | NIOSH                          |
|           |           | PEL (Respirable fraction)          | 5 mg/m3            | 29 CFR 1910.1000 (Table Z-1)   |
|           |           | PEL (Total dust)                   | 15 mg/m3           | 29 CFR 1910.1000 (Table Z-1)   |
|           |           | TWA value (Respirable fraction)    | 5 mg/m3            | 29 CFR 1910.1000 (Table Z-1-A) |
|           |           | TWA value (Total dust)             | 15 mg/m3           | 29 CFR 1910.1000 (Table Z-1-A) |
|           |           | TWA (total dust)                   | 15 mg/m3           | OSHA Z-1                       |
|           |           | TWA (respirable fraction)          | 5 mg/m3            | OSHA Z-1                       |
|           |           | TWA (Total dust)                   | 15 mg/m3           | OSHA P0                        |
|           |           | TWA (respirable dust fraction)     | 5 mg/m3            | OSHA P0                        |

## MasterEmaco S 488CI

Version  
2.0Revision Date:  
12/31/2020SDS Number:  
000000243937Date of last issue: 06/05/2020  
Date of first issue: 06/05/2020

|                                       |             |                                     |   |                                      |
|---------------------------------------|-------------|-------------------------------------|---|--------------------------------------|
|                                       |             | TWA (Respirable)                    | 5 mg/m <sup>3</sup><br>(Calcium carbonate)              | NIOSH REL                            |
|                                       |             | TWA (total)                         | 10 mg/m <sup>3</sup><br>(Calcium carbonate)             | NIOSH REL                            |
| Silica, amorphous, fumed, cryst.-free | 112945-52-5 | REL value                           | 6 mg/m <sup>3</sup>                                     | NIOSH                                |
|                                       |             | TWA value                           | 0.8 mg/m <sup>3</sup>                                   | 29 CFR<br>1910.1000<br>(Table Z-3)   |
|                                       |             | TWA value                           | 20 millions of<br>particles per cubic<br>foot of air    | 29 CFR<br>1910.1000<br>(Table Z-3)   |
|                                       |             | TWA (Dust)                          | 20 Million particles per cubic foot<br>(Silica)         | OSHA Z-3                             |
|                                       |             | TWA (Dust)                          | 80 mg/m <sup>3</sup> /<br>%SiO <sub>2</sub><br>(Silica) | OSHA Z-3                             |
|                                       |             | TWA                                 | 6 mg/m <sup>3</sup><br>(Silica)                         | NIOSH REL                            |
| Iron oxide                            | 1309-37-1   | TWA value<br>(Respirable fraction)  | 5 mg/m <sup>3</sup>                                     | ACGIHTLV                             |
|                                       |             | REL value<br>(Dust and fume)        | 5 mg/m <sup>3</sup><br>(iron (Fe))                      | NIOSH                                |
|                                       |             | PEL<br>(fumes/smoke)                | 10 mg/m <sup>3</sup>                                    | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                                       |             | TWA value<br>(fumes/smoke)          | 10 mg/m <sup>3</sup>                                    | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                                       |             | TWA (Respirable particulate matter) | 5 mg/m <sup>3</sup>                                     | ACGIH                                |
|                                       |             | TWA (dust and fume)                 | 5 mg/m <sup>3</sup><br>(Iron)                           | NIOSH REL                            |
|                                       |             | TWA<br>(Fumes)                      | 10 mg/m <sup>3</sup>                                    | OSHA Z-1                             |
|                                       |             | TWA (total dust)                    | 15 mg/m <sup>3</sup>                                    | OSHA Z-1                             |
|                                       |             | TWA (respirable fraction)           | 5 mg/m <sup>3</sup>                                     | OSHA Z-1                             |
|                                       |             | TWA<br>(Fumes)                      | 10 mg/m <sup>3</sup>                                    | OSHA P0                              |
| magnesium oxide                       | 1309-48-4   | TWA value<br>(Inhalable fraction)   | 10 mg/m <sup>3</sup>                                    | ACGIHTLV                             |
|                                       |             | PEL (Total particulate)             | 15 mg/m <sup>3</sup>                                    | 29 CFR<br>1910.1000<br>(Table Z-1)   |



## MasterEmaco S 488CI

Version 2.0      Revision Date: 12/31/2020      SDS Number: 000000243937      Date of last issue: 06/05/2020  
 Date of first issue: 06/05/2020

|                  |           |                                    |                    |                                |
|------------------|-----------|------------------------------------|--------------------|--------------------------------|
|                  |           | TWA value (Total particulate)      | 10 mg/m3           | 29 CFR 1910.1000 (Table Z-1-A) |
|                  |           | TWA (Inhalable particulate matter) | 10 mg/m3           | ACGIH                          |
|                  |           | TWA (fume, total particulate)      | 15 mg/m3           | OSHA Z-1                       |
|                  |           | TWA (Fume - total particulate)     | 10 mg/m3           | OSHA P0                        |
| Calcium sulphate | 7778-18-9 | TWA value (Inhalable fraction)     | 10 mg/m3           | ACGIHTLV                       |
|                  |           | REL value (Respirable)             | 5 mg/m3            | NIOSH                          |
|                  |           | REL value (Total)                  | 10 mg/m3           | NIOSH                          |
|                  |           | PEL (Respirable fraction)          | 5 mg/m3            | 29 CFR 1910.1000 (Table Z-1)   |
|                  |           | PEL (Total dust)                   | 15 mg/m3           | 29 CFR 1910.1000 (Table Z-1)   |
|                  |           | TWA value (Respirable fraction)    | 5 mg/m3            | 29 CFR 1910.1000 (Table Z-1-A) |
|                  |           | TWA value (Total dust)             | 15 mg/m3           | 29 CFR 1910.1000 (Table Z-1-A) |
|                  |           | TWA (Respirable)                   | 5 mg/m3            | NIOSH REL                      |
|                  |           | TWA (total)                        | 10 mg/m3           | NIOSH REL                      |
|                  |           | TWA (total dust)                   | 15 mg/m3           | OSHA Z-1                       |
|                  |           | TWA (respirable fraction)          | 5 mg/m3            | OSHA Z-1                       |
|                  |           | TWA (Total dust)                   | 15 mg/m3           | OSHA P0                        |
|                  |           | TWA (respirable dust fraction)     | 5 mg/m3            | OSHA P0                        |
|                  |           | TWA (Inhalable particulate matter) | 10 mg/m3 (Calcium) | ACGIH                          |

**Engineering measures** : Provide local exhaust ventilation to maintain recommended P.E.L.

**Personal protective equipment**

Respiratory protection : Breathing protection if dusts are formed.  
 Wear a NIOSH-certified (or equivalent) particulate respirator.

## MasterEmaco S 488CI

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 06/05/2020  |
| 2.0     | 12/31/2020     | 000000243937 | Date of first issue: 06/05/2020 |

---

## Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's directions for use should be observed because of great diversity of types.

## Eye protection

: Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.  
Eye wash bottle with pure water

## Skin and body protection

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.

## Protective measures

: Avoid contact with the skin, eyes and clothing.  
Avoid inhalation of dusts.  
In order to prevent contamination while handling, closed working clothes and working gloves should be used.  
Handle in accordance with good building materials hygiene and safety practice.

## Hygiene measures

: When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : dark gray

Odor : faint, earthy

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : approx. 12 - 13 (68 °F / 20 °C)  
(as aqueous suspension)

Melting temperature : > 1,832 °F / > 1,000 °C

Boiling point : Not applicable

Flash point : Not applicable

Evaporation rate : The product is a non-volatile solid.

Flammability (solid, gas) : not flammable

Upper explosion limit / Upper flammability limit : As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

## MasterEmaco S 488CI

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 06/05/2020  |
| 2.0     | 12/31/2020     | 000000243937 | Date of first issue: 06/05/2020 |

---

with the intended use.

Lower explosion limit / Lower flammability limit : As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

Vapor pressure : No data available

Relative vapor density : The product is a non-volatile solid.

Bulk density : approx. 1.23 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : dispersible (68 °F / 20 °C)

Solubility in other solvents : No applicable information available.

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : not fire-propagating

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No applicable information available.

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong bases  
Strong acids

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

## MasterEmaco S 488CI

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 06/05/2020  |
| 2.0     | 12/31/2020     | 000000243937 | Date of first issue: 06/05/2020 |

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Product:**

Remarks : Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.  
May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

## MasterEmaco S 488CI

Version      Revision Date:      SDS Number:      Date of last issue: 06/05/2020  
2.0          12/31/2020          000000243937      Date of first issue: 06/05/2020

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity      :    This product has no known ecotoxicological effects.

Chronic aquatic toxicity    :    This product has no known ecotoxicological effects.

**Persistence and degradability****Product:**

Biodegradability          :    Remarks: Not applicable for inorganic substances.

**Components:****sodium nitrite:**

Biodegradability          :    Remarks: Not applicable

Stability in water        :    Remarks: Not applicable

**Bioaccumulative potential****Product:**

Bioaccumulation          :    Remarks: No data available.

**Components:****2,2-dimethylpropane-1,3-diol:**

Partition coefficient: n-  
octanol/water            :    log Pow: -0.15 (77 °F / 25 °C)  
Method: Partition coefficient (n-octanol/water), Shake-flask  
method  
GLP: no

**sodium nitrite:**

Partition coefficient: n-  
octanol/water            :    Remarks: Study scientifically not justified.

**Mobility in soil****Product:**

Distribution among environ-  
mental compartments    :    Remarks: Following exposure to soil, adsorption to solid soil  
particles is probable, therefore contamination of groundwater  
is not expected.  
The substance will not evaporate into the atmosphere from  
the water surface.

## MasterEmaco S 488CI

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 06/05/2020  |
| 2.0     | 12/31/2020     | 000000243937 | Date of first issue: 06/05/2020 |

**Other adverse effects****Product:**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

| Components | CAS-No. | Component RQ | Calculated product RQ |
|------------|---------|--------------|-----------------------|
|            |         |              |                       |

## MasterEmaco S 488CI

Version 2.0      Revision Date: 12/31/2020      SDS Number: 000000243937      Date of last issue: 06/05/2020  
 Date of first issue: 06/05/2020

|                |           | (lbs) | (lbs) |
|----------------|-----------|-------|-------|
| sodium nitrite | 7632-00-0 | 100   | 49751 |

**US State Regulations****Pennsylvania Right To Know**

|   |            |
|---|------------|
| calcium oxide                                   | 1305-78-8  |
| Iron oxide                                      | 1309-37-1  |
| magnesium oxide                                 | 1309-48-4  |
| Limestone                                       | 1317-65-3  |
| Silicon dioxide                                 | 7631-86-9  |
| Calcium sulphate                                | 7778-18-9  |
| Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O) | 13397-24-5 |
| Quartz (SiO <sub>2</sub> )                      | 14808-60-7 |
| Cement, portland, chemicals                     | 65997-15-1 |

**New Jersey Right To Know**

|                             |            |
|-----------------------------|------------|
| calcium oxide               | 1305-78-8  |
| Iron oxide                  | 1309-37-1  |
| magnesium oxide             | 1309-48-4  |
| Limestone                   | 1317-65-3  |
| Calcium sulphate            | 7778-18-9  |
| Quartz (SiO <sub>2</sub> )  | 14808-60-7 |
| Cement, portland, chemicals | 65997-15-1 |

**California Prop. 65**

WARNING: This product can expose you to chemicals including Quartz (SiO<sub>2</sub>), which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**TSCA list**


The following substance(s) is/are subject to a Significant New Use Rule:  
 sodium nitrite 7632-00-0

**SECTION 16. OTHER INFORMATION****Further information**


**MasterEmaco S 488CI**

Version 2.0      Revision Date: 12/31/2020      SDS Number: 000000243937      Date of last issue: 06/05/2020  
 Date of first issue: 06/05/2020

**NFPA 704:**



**HMIS® IV:**



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
- 29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- 29 CFR 1910.1000 (Table Z-3) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1001-1050 / OSHA Action level : OSHA Action level:
- 29 CFR 1910.1001-1050 / TWA value : Time Weighted Average (TWA):
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / REL value : Recommended exposure limit (REL):



## MasterEmaco S 488CI

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 06/05/2020  |
| 2.0     | 12/31/2020     | 000000243937 | Date of first issue: 06/05/2020 |

|                 |   |   |
|-----------------|---|---|
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA CARC / PEL | : | Permissible exposure limit (PEL)  |
| OSHA P0 / TWA   | : | 8-hour time weighted average  |
| OSHA Z-1 / TWA  | : | 8-hour time weighted average  |
| OSHA Z-3 / TWA  | : | 8-hour time weighted average  |

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/31/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE

**MasterEmaco S 488CI**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 06/05/2020  |
| 2.0     | 12/31/2020     | 000000243937 | Date of first issue: 06/05/2020 |

---

, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN