

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

**SECTION 1. IDENTIFICATION** 

Product name : MasterEmaco T 1060C

Product code : 00000000057393264 00000000057393264

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems

US, LLC

Address : 23700 CHAGRIN BLVD

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

Category 1

Reproductive toxicity : Category 1B

Reproductive toxicity : Category 1B

Specific target organ toxicity

- single exposure

Category 3

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lung)

**GHS** label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

H372 Causes damage to organs (Lung) through prolonged or

repeated exposure if inhaled.

H360 May damage fertility or the unborn child.

Precautionary Statements

#### Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P260 Do not breathe dust or mist.

P270 Do not eat, drink or smoke when using this product. P264 Wash face, hands and any exposed skin thoroughly after handling.

### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/ doctor/

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

#### Other hazards

In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No data available.

#### Components

| Chemical name               | CAS-No.    | Concentration (% w/w) |
|-----------------------------|------------|-----------------------|
| Cement, portland, chemicals | 65997-15-1 | >= 20 - < 75          |
| Quartz (SiO2)               | 14808-60-7 | >= 0 - < 3            |
| calcium oxide               | 1305-78-8  | >= 0 - < 3            |
| boric acid                  | 10043-35-3 | >= 0 - < 1            |
| Calcium sulphate            | 7778-18-9  | >= 7 - < 50           |
| Limestone                   | 1317-65-3  | >= 0.3 - < 3          |
| Silicon dioxide             | 7631-86-9  | >= 1 - < 3            |
| Iron oxide                  | 1309-37-1  | >= 1 - < 3            |



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

Gypsum (Ca(SO4).2H2O) | 13397-24-5 | >= 0.3 - < 3

**SECTION 4. FIRST AID MEASURES** 

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES** 

Suitable extinguishing media : Water spray

Foam

Carbon dioxide (CO2)

Dry powder

Unsuitable extinguishing

media

High volume water jet

# **MBCC** GROUP

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emergency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Neutralize with acid.

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

Segregate from acids and bases.

Segregate from oxidants.

Segregate from foods and animal feeds.

Further information on stor-

age stability

No data available

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Ingredients with workplace control parameters

| Components    | CAS-No.   | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis                  |
|---------------|-----------|-------------------------------------|--|------------------------|
| calcium oxide | 1305-78-8 | TWA value                           | 2 mg/m3  | ACGIHTLV               |
|               |           | REL value                           | 2 mg/m3  | NIOSH                  |
|               |           | PEL                                 | 5 mg/m3  | 29 CFR                 |
|               |           |                                     |  | 1910.1000              |
|               |           |                                     |  | (Table Z-1)            |
|               |           | TWA value                           | 5 mg/m3  | 29 CFR                 |
|               |           |                                     |  | 1910.1000              |
|               |           |                                     |  | (Table Z-1-A)          |
|               |           | TWA                                 | 2 mg/m3  | ACGIH                  |
|               |           | TWA                                 | 2 mg/m3  | NIOSH REL              |
|               |           | TWA                                 | 5 mg/m3  | OSHA Z-1               |
|               |           | TWA                                 | 5 mg/m3  | OSHA P0                |
| Iron oxide    | 1309-37-1 | TWA value                           | 5 mg/m3  | ACGIHTLV               |
|               |           | (Respirable                         |  |                        |
|               |           | fraction)                           |  |                        |
|               |           | REL value                           | 5 mg/m3  | NIOSH                  |
|               |           | (Dust and                           | (iron (Fe))                                    |                        |
|               |           | fume)                               |  |                        |
|               |           | PEL                                 | 10 mg/m3                                       | 29 CFR                 |
|               |           | (fumes/smok                         |  | 1910.1000              |
|               |           | e)                                  | 10 / 0   | (Table Z-1)            |
|               |           | TWA value                           | 10 mg/m3                                       | 29 CFR                 |
|               |           | (fumes/smok                         |  | 1910.1000              |
|               |           | e)<br>TWA (Res-                     | 5 mg/m3  | (Table Z-1-A)<br>ACGIH |
|               |           | pirable par-                        | 5 1119/1113                                    | ACGIN                  |
|               |           | ticulate mat-                       |  |                        |
|               |           | ter)                                |  |                        |
|               |           | TWA (dust                           | 5 mg/m3  | NIOSH REL              |
|               |           | and fume)                           | (Iron)   | MOONINEE               |
|               |           | TWA                                 | 10 mg/m3                                       | OSHA Z-1               |
|               |           | (Fumes)                             |  |                        |
|               |           | TWA (total                          | 15 mg/m3                                       | OSHA Z-1               |
|               |           | dust)                               | J  |                        |
|               |           | TWA (respirable fraction)           | 5 mg/m3  | OSHA Z-1               |
|               |           | TWA (Fumes)                         | 10 mg/m3                                       | OSHA P0                |
| Limestone     | 1317-65-3 | REL value                           | 5 mg/m3  | NIOSH                  |
| LIMESIONE     | 1317-00-3 | INLL Value                          | i o mg/mo                                      | INICOIT                |



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

|                  |           | (Respirable)                          | ſ  | l                                    |
|------------------|-----------|---------------------------------------|--|--------------------------------------|
|                  |           | REL value<br>(Total)                  | 10 mg/m3   | NIOSH                                |
|                  |           | PEL (Respirable fraction)             | 5 mg/m3  | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                  |           | PEL (Total dust)                      | 15 mg/m3   | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                  |           | TWA value<br>(Respirable<br>fraction) | 5 mg/m3  | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                  |           | TWA value<br>(Total dust)             | 15 mg/m3   | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                  |           | TWA (total dust)                      | 15 mg/m3   | OSHA Z-1                             |
|                  |           | TWA (respirable fraction)             | 5 mg/m3  | OSHA Z-1                             |
|                  |           | TWA (Total dust)                      | 15 mg/m3   | OSHA P0                              |
|                  |           | TWA (respirable dust fraction)        | 5 mg/m3  | OSHA P0                              |
|                  |           | TWA (Respirable)                      | 5 mg/m3<br>(Calcium car-<br>bonate)                  | NIOSH REL                            |
|                  |           | TWA (total)                           | 10 mg/m3<br>(Calcium car-<br>bonate)                 | NIOSH REL                            |
| Silicon dioxide  | 7631-86-9 | REL value                             | 6 mg/m3  | NIOSH                                |
|                  |           | TWA value                             | 6 mg/m3  | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                  |           | TWA value                             | 20 millions of particles per cubic foot of air       | 29 CFR<br>1910.1000<br>(Table Z-3)   |
|                  |           | TWA value                             | 0.8 mg/m3  | 29 CFR<br>1910.1000<br>(Table Z-3)   |
|                  |           | TWA (Dust)                            | 20 Million parti-<br>cles per cubic foot<br>(Silica) | OSHA Z-3                             |
|                  |           | TWA (Dust)                            | 80 mg/m3 /<br>%SiO2<br>(Silica)                      | OSHA Z-3                             |
|                  |           | TWA (Respirable dust)                 | 0.05 mg/m3<br>(Silica)                               | NIOSH REL                            |
|                  |           | TWA                                   | 6 mg/m3<br>(Silica)                                  | NIOSH REL                            |
| Calcium sulphate | 7778-18-9 | TWA value<br>(Inhalable<br>fraction)  | 10 mg/m3   | ACGIHTLV                             |
|                  |           | REL value                             | 5 mg/m3  | NIOSH                                |



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

|                       |            | (Respirable)                                 | 1                     | 1                                    |
|-----------------------|------------|--|-----------------------|--------------------------------------|
|                       |            | REL value<br>(Total)                         | 10 mg/m3              | NIOSH                                |
|                       |            | PEL (Respirable fraction)                    | 5 mg/m3               | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                       |            | PEL (Total dust)                             | 15 mg/m3              | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                       |            | TWA value<br>(Respirable<br>fraction)        | 5 mg/m3               | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                       |            | TWA value<br>(Total dust)                    | 15 mg/m3              | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                       |            | TWA (Respirable)                             | 5 mg/m3               | NIOSH REL                            |
|                       |            | TWA (total) TWA (total                       | 10 mg/m3<br>15 mg/m3  | NIOSH REL<br>OSHA Z-1                |
|                       |            | dust) TWA (respirable fraction)              | 5 mg/m3               | OSHA Z-1                             |
|                       |            | TWA (Total dust)                             | 15 mg/m3              | OSHA P0                              |
|                       |            | TWA (respirable dust fraction)               | 5 mg/m3               | OSHA P0                              |
|                       |            | TWA (Inhal-<br>able particu-<br>late matter) | 10 mg/m3<br>(Calcium) | ACGIH                                |
| Gypsum (Ca(SO4).2H2O) | 13397-24-5 | TWA value<br>(Inhalable<br>fraction)         | 10 mg/m3              | ACGIHTLV                             |
|                       |            | REL value<br>(Respirable)                    | 5 mg/m3               | NIOSH                                |
|                       |            | REL value<br>(Total)                         | 10 mg/m3              | NIOSH                                |
|                       |            | PEL (Total dust)                             | 15 mg/m3              | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                       |            | PEL (Respirable fraction)                    | 5 mg/m3               | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                       |            | TWA value<br>(Total dust)                    | 15 mg/m3              | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                       |            | TWA value<br>(Respirable<br>fraction)        | 5 mg/m3               | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                       |            | TWA (Res-<br>pirable)                        | 5 mg/m3               | NIOSH REL                            |
|                       |            | TWA (total) TWA (total dust)                 | 10 mg/m3<br>15 mg/m3  | NIOSH REL<br>OSHA Z-1                |



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

|                             |            | TWA (respir-                                 | 5 mg/m3                          | OSHA Z-1                           |
|-----------------------------|------------|--|----------------------------------|------------------------------------|
|                             |            | able fraction) TWA (Total                    | 15 mg/m3                         | OSHA P0                            |
|                             |            | dust) TWA (respirable dust fraction)         | 5 mg/m3                          | OSHA P0                            |
|                             |            | TWA (Inhal-<br>able particu-<br>late matter) | 10 mg/m3<br>(Calcium)            | ACGIH                              |
| Quartz (SiO2)               | 14808-60-7 | TWA value<br>(Respirable<br>fraction)        | 0.025 mg/m3                      | ACGIHTLV                           |
|                             |            | TWA value                                    | 0.05 mg/m3<br>(Respirable dust)  | 29 CFR<br>1910.1001-<br>1050       |
|                             |            | OSHA Action<br>level                         | 0.025 mg/m3<br>(Respirable dust) | 29 CFR<br>1910.1001-<br>1050       |
|                             |            | REL value<br>(Respirable<br>dust)            | 0.05 mg/m3                       | NIOSH                              |
|                             |            | TWA (Respirable dust)                        | 0.05 mg/m3                       | OSHA Z-1                           |
|                             |            | TWA (respirable)                             | 10 mg/m3 /<br>%SiO2+2            | OSHA Z-3                           |
|                             |            | TWA (respirable)                             | 250 mppcf /<br>%SiO2+5           | OSHA Z-3                           |
|                             |            | TWA (respirable dust fraction)               | 0.1 mg/m3                        | OSHA P0                            |
|                             |            | TWA (Respirable particulate matter)          | 0.025 mg/m3<br>(Silica)          | ACGIH                              |
|                             |            | PEL (respir-<br>able)                        | 0.05 mg/m3                       | OSHA CARC                          |
|                             |            | TWA (Respirable dust)                        | 0.05 mg/m3<br>(Silica)           | NIOSH REL                          |
| Cement, portland, chemicals | 65997-15-1 | TWA value<br>(Respirable<br>fraction)        | 1 mg/m3                          | ACGIHTLV                           |
|                             |            | REL value<br>(Total)                         | 10 mg/m3                         | NIOSH                              |
|                             |            | REL value<br>(Respirable)                    | 5 mg/m3                          | NIOSH                              |
|                             |            | PEL (Total dust)                             | 15 mg/m3                         | 29 CFR<br>1910.1000<br>(Table Z-1) |
|                             |            | PEL (Respirable fraction)                    | 5 mg/m3                          | 29 CFR<br>1910.1000<br>(Table Z-1) |
|                             |            | TWA value<br>(Total dust)                    | 10 mg/m3                         | 29 CFR<br>1910.1000                |



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

|                |                     | (Table Z-1-A) |
|----------------|---------------------|---------------|
| TWA value      | 5 mg/m3             | 29 CFR        |
| (Respirable    |                     | 1910.1000     |
| fraction)      |                     | (Table Z-1-A) |
| TWA value      | 50 millions of      | 29 CFR        |
|                | particles per cubic | 1910.1000     |
|                | foot of air         | (Table Z-3)   |
| TWA (Res-      | 1 mg/m3             | ACGIH         |
| pirable par-   |                     |               |
| ticulate mat-  |                     |               |
| ter)           |                     |               |
| TWA (Res-      | 5 mg/m3             | NIOSH REL     |
| pirable)       | 10 10               |               |
| TWA (total)    | 10 mg/m3            | NIOSH REL     |
| TWA (total     | 15 mg/m3            | OSHA Z-1      |
| dust)          |                     |               |
| TWA (respir-   | 5 mg/m3             | OSHA Z-1      |
| able fraction) |                     |               |
| TWA (Total     | 10 mg/m3            | OSHA P0       |
| dust)          | - / -               | 00114 50      |
| TWA (respir-   | 5 mg/m3             | OSHA P0       |
| able dust      |                     |               |
| fraction)      | 50 MW               | 00114.7.0     |
| TWA (Dust)     | 50 Million parti-   | OSHA Z-3      |
|                | cles per cubic foot |               |

**Engineering measures** : Provide local exhaust ventilation to maintain recommended

P.E.L.

Personal protective equipment

Respiratory protection : Breathing protection if dusts are formed.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder

Color : gray

Odor : mild

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : 13 (68 °F / 20 °C)

(as aqueous solution)

Melting point : No applicable information available.

Boiling point : No data available

Flash point : does not flash

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Lower explosion limit / Lower

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Bulk density : 1.6 kg/m3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No applicable information available.

# **MBCC** GROUP

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

Partition coefficient: n-

octanol/water

: No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong bases

Strong acids

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

**Product:** 

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

**Product:** 

Remarks : Chromate in this product has been reduced. Sensitization due

to chromate within stated shelf-live is unlikely.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.

**Aspiration toxicity** 

Not classified based on available information.

**Components:** 

calcium oxide:

Not applicable

boric acid:

Not applicable

# **MBCC** GROUP

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

Silicon dioxide:

Not applicable

**Gypsum (Ca(SO4).2H2O):** 

Not applicable

**Further information** 

**Product:** 

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

Product:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

**Product:** 

Biodegradability : Remarks: Not applicable for inorganic substances.

**Components:** 

Cement, portland, chemicals:

Biodegradability : Remarks: Not applicable

boric acid:

Biodegradability : Remarks: Not applicable

**Bioaccumulative potential** 

**Product:** 

Bioaccumulation : Remarks: The product will not be readily bioavailable due to

its consistency and insolubility in water.

**Components:** 

Cement, portland, chemicals:

Partition coefficient: n- : GLP: no

octanol/water Remarks: Not applicable

Quartz (SiO2):

Partition coefficient: n- : Remarks: Not applicable

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

octanol/water

calcium oxide:

Partition coefficient: n-

octanol/water

: Remarks: The value has not been determined because the

substance is inorganic.

Calcium sulphate:

Partition coefficient: n-

octanol/water

GLP: no

Remarks: The value has not been determined because the

substance is inorganic.

Silicon dioxide:

Partition coefficient: n-

octanol/water

Remarks: Not applicable

Iron oxide:

Partition coefficient: n-

octanol/water

Remarks: Study scientifically not justified.

**Gypsum (Ca(SO4).2H2O):** 

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

## Mobility in soil

### **Product:**

Distribution among environmental compartments Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater

is not expected.

The substance will not evaporate into the atmosphere from

the water surface.

#### Other adverse effects

# **Product:**

Results of PBT and vPvB

assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Additional ecological infor-

mation

: There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.



# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

### **SECTION 15. REGULATORY INFORMATION**

#### **US State Regulations**

## Pennsylvania Right To Know

| calcium oxide               | 1305-78-8  |
|-----------------------------|------------|
| Iron oxide                  | 1309-37-1  |
| Limestone                   | 1317-65-3  |
| Silicon dioxide             | 7631-86-9  |
| Calcium sulphate            | 7778-18-9  |
| Gypsum (Ca(SO4).2H2O)       | 13397-24-5 |
| Quartz (SiO2)               | 14808-60-7 |
| Cement, portland, chemicals | 65997-15-1 |

### **New Jersey Right To Know**

| calcium oxide               | 1305-78-8  |
|-----------------------------|------------|
| Limestone                   | 1317-65-3  |
| Calcium sulphate            | 7778-18-9  |
| Cement, portland, chemicals | 65997-15-1 |
| Lithium carbonate           | 554-13-2   |

# **MBCC** GROUP

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer, and

Lithium carbonate, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


### The ingredients of this product are reported in the following inventories:

TSCA: On the inventory, or in compliance with the inventory

#### **SECTION 16. OTHER INFORMATION**


#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

29 CFR 1910.1000 (Table Z- :

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH

INIOSH Pocket Guide to Chemical Hazards (US)

NIOSH REL

USA. NIOSH Recommended Exposure Limits

OSHA CARC

USA. NIOSH Recommended Exposure Limits

OSHA Specifically Regulated Chemicals/Carcinogens

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

# MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

3) / TWA value

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek Permissible exposure limit (PEL)

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;



## MasterEmaco T 1060C

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/21/2020 000000260153 Date of first issue: 10/21/2020

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/21/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN