

MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

SECTION 1. IDENTIFICATION

Product name : MasterFlow 885

Product code : 00000000055518919 00000000055518919

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems

US, LLC

Address : 23700 CHAGRIN BLVD

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

Category 1

Carcinogenicity (Inhalation) : Category 1A (Lung)

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lung)

GHS label elements

Hazard pictograms

EB (



Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

MBCC GROUP

MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure.

H372 Causes damage to organs through prolonged or repeated

exposure if inhaled.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 Obtain special instructions before use.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust or mist.

P202 Do not handle until all safety precautions have been read and understood.

P270 Do not eat, drink or smoke when using this product.

P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P310 Immediately call a POISON CENTER or doctor/ physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : modified cement mortar

Components

Chemical name	CAS-No.	Concentration (% w/w)
Cement, portland, chemicals	65997-15-1	>= 20 - < 50
crystalline silica	14808-60-7	>= 20 - < 50
Silicon dioxide	7631-86-9	>= 1 - < 5

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

calcium oxide	1305-78-8	>= 1 - < 3
Gypsum (Ca(SO4).2H2O)	13397-24-5	>= 0.3 - < 3
Limestone	1317-65-3	>= 0 - < 3
carbon	7440-44-0	>= 0 - < 3
lead	7439-92-1	>= 0 - < 0.1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

Water spray Dry powder

Carbon dioxide (CO2)

Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are

sufficient.

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Neutralize with acid.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.

Segregate from acids and bases.

Segregate from oxidants.

Segregate from foods and animal feeds.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR
				1910.1000
				(Table Z-1)
		TWA value	5 mg/m3	29 CFR
				1910.1000
				(Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Limestone	1317-65-3	REL value	5 mg/m3	NIOSH
		(Respirable)		
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)		1910.1000
				(Table Z-1)
		PEL (Total	15 mg/m3	29 CFR
		dust)		1910.1000
				(Table Z-1)
		TWA value	5 mg/m3	29 CFR
		(Respirable		1910.1000
		fraction)		(Table Z-1-A)
		TWA value	15 mg/m3	29 CFR
		(Total dust)		1910.1000
				(Table Z-1-A)
		TWA (total	15 mg/m3	OSHA Z-1



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

1	1	dust)	İ	1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWÁ (respir- able dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
lead	7439-92-1	TWA value	0.05 mg/m3 (lead (Pb))	ACGIHTLV
		TWA	0.05 mg/m3 (lead)	ACGIH
		PEL	0.05 mg/m3 (lead)	OSHA CARC
		TWA	0.05 mg/m3 (lead)	NIOSH REL
carbon	7440-44-0	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWA value (Respirable particles)	3 mg/m3	ACGIHTLV
		TWA value (Inhalable particles)	10 mg/m3	ACGIHTLV
		REL value (Respirable)	2.5 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable dust)	2.5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	15 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
Silicon dioxide	7631-86-9	REL value TWA value	6 mg/m3 6 mg/m3	NIOSH 29 CFR 1910.1000



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

1	1	1	1	1
				(Table Z-1-A)
		TWA value	20 millions of	29 CFR
			particles per cubic	1910.1000
			foot of air	(Table Z-3)
		TWA value	0.8 mg/m3	29 CFR
				1910.1000
				(Table Z-3)
		TWA (Dust)	20 Million parti-	OSHA Z-3
			cles per cubic foot	
			(Silica)	
		TWA (Dust)	80 mg/m3 /	OSHA Z-3
		, ,	%SiO2	
			(Silica)	
		TWA (Res-	0.05 mg/m3	NIOSH REL
		pirable dust)	(Silica)	
		TWA	6 mg/m3	NIOSH REL
			(Silica)	
Gypsum (Ca(SO4).2H2O)	13397-24-5	TWA value	10 mg/m3	ACGIHTLV
		(Inhalable		
		raction)		
		REL value	5 mg/m3	NIOSH
		(Respirable)	3 3	
		REL value	10 mg/m3	NIOSH
		(Total)		
		PEL (Total	15 mg/m3	29 CFR
		dust)	10 1119/1110	1910.1000
		adot)		(Table Z-1)
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)	o mg/mo	1910.1000
				(Table Z-1)
		TWA value	15 mg/m3	29 CFR
		(Total dust)	J. S. M. G. M. S.	1910.1000
		(1010110101)		(Table Z-1-A)
		TWA value	5 mg/m3	29 CFR
		(Respirable	o mg/mo	1910.1000
		fraction)		(Table Z-1-A)
		TWA (Res-	5 mg/m3	NIOSH REL
		pirable)	39,5	
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total)	15 mg/m3	OSHA Z-1
		dust)	1.5 1119/1110	00.17.2
		TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)	J IIIg/IIIJ	JULIA Z-1
		TWA (Total	15 mg/m3	OSHA P0
		dust)	13 1119/1113	JOHA 1 0
		TWA (respir-	5 mg/m3	OSHA P0
		able dust	J IIIg/IIIJ	JOHAFU
		fraction)		
		TWA (Inhal-	10 mg/m3	ACGIH
		able particu-	(Calcium)	AUGIH
		late matter)	(Calciulii)	
Cement, portland, chemicals	65997-15-1	TWA value	1 mg/m3	ACGIHTLV
Cement, portiand, chemicals	00991-10-1	(Respirable	i ilig/ilio	ACGITIEV
		fraction)		
		Haction)	<u> </u>	



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

		REL value	10 mg/m3	NIOSH
		(Total)	10 1119/1113	NICOIT
		REL value (Respirable)	5 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000
				(Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	50 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA (Res- pirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Dust)	50 Million parti- cles per cubic foot	OSHA Z-3
crystalline silica	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWÁ (respir-	250 mppcf /	OSHA Z-3



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

able)	%SiO2+5	
TWA (respir-	0.1 mg/m3	OSHA P0
able dust		
fraction)		
TWA (Res-	0.025 mg/m3	ACGIH
pirable par-	(Silica)	
ticulate mat-		
ter)		
PEL (respir-	0.05 mg/m3	OSHA CARC
able)		
TWA (Res-	0.05 mg/m3	NIOSH REL
pirable dust)	(Silica)	

Engineering measures : Provide local exhaust ventilation to maintain recommended

P.E.L.

Personal protective equipment

Respiratory protection : Breathing protection if dusts are formed.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : gray

Odor : faint odour



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : approx. 12 (68 °F / 20 °C)

(as aqueous suspension)

Melting point : No applicable information available.

Boiling point/boiling range : Not applicable

Flash point : does not flash

Evaporation rate : Not applicable

Flammability (solid, gas) : not flammable

Upper explosion limit / Upper

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Lower explosion limit / Lower

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No applicable information available.

Bulk density : approx. 1,500 kg/m3

Solubility(ies)

Water solubility : dispersible (68 °F / 20 °C)

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Not explosive



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong bases

Strong acids

Hazardous decomposition

products

formaldehyde

Traces of the substances/groups of substances mentioned

can be released at elevated temperatures.

The substances/substance groups mentioned are formed by

hydrolysis.

The substances/groups of substances mentioned may be

released during processing.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Chromate in this product has been reduced. Sensitization due

to chromate within stated shelf-live is unlikely.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Not applicable for inorganic substances.



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

Components:

lead:

Biodegradability : Remarks: Not applicable

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to

its consistency and insolubility in water.

Components:

carbon:

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

lead:

Partition coefficient: n-

octanol/water

Remarks: Not applicable

Mobility in soil

Product:

Distribution among environ-

mental compartments

Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater

is not expected.

The substance will not evaporate into the atmosphere from

the water surface.

Other adverse effects

Product:

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-



MasterFlow 885

Version Revision Date: SDS Number: Date of last issue: 06/03/2020 1.1 01/05/2021 000000259982 Date of first issue: 06/03/2020

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
arsenic	7440-38-2	1	8928

US State Regulations

Pennsylvania Right To Know

calcium oxide	1305-78-8
Limestone	1317-65-3
carbon	7440-44-0
Silicon dioxide	7631-86-9
Gypsum (Ca(SO4).2H2O)	13397-24-5
Quartz (SiO2)	14808-60-7
Cement, portland, chemicals	65997-15-1
nickel	7440-02-0
arsenic	7440-38-2
chromium	7440-47-3

New Jersey Right To Know

calcium oxide	1305-78-8
Limestone	1317-65-3
carbon	7440-44-0
Silicon dioxide	7631-86-9
Gypsum (Ca(SO4).2H2O)	13397-24-5
Quartz (SiO2)	14808-60-7
Cement, portland, chemicals	65997-15-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

California Prop. 65

WARNING: This product can expose you to chemicals including lead, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Flammability Health 3 0 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- :

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

3)

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

Version **Revision Date:** SDS Number: Date of last issue: 06/03/2020 01/05/2021 000000259982 Date of first issue: 06/03/2020 1.1

1910.1000

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

29 CFR 1910.1000 (Table Z- :

Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

3) / TWA value

29 CFR 1910.1001-1050 / OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / Time Weighted Average (TWA):

TWA value

8-hour, time-weighted average ACGIH / TWA ACGIHTLV / TWA value Time Weighted Average (TWA): NIOSH / REL value Recommended exposure limit (REL):

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek Permissible exposure limit (PEL)

OSHA CARC / PEL OSHA P0 / TWA 8-hour time weighted average 8-hour time weighted average OSHA Z-1 / TWA OSHA Z-3 / TWA 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;



MasterFlow 885

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/03/2020

 1.1
 01/05/2021
 000000259982
 Date of first issue: 06/03/2020

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/05/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN